

EVE-NG PE Professional Edition Cookbook

Version 6.3-10

Author: Uldis Dzerkals

© EVE-NG LTD

The information contained in this document is the property of EVE-NG Limited

The contents of the document must not be reproduced or disclosed wholly or in part or used for purposes other than that for which it is supplied without the prior written permission of EVE-NG Limited.



Table of Contents

PREFACE	10
1 INTRODUCTION	11
1.1 WHAT IS EVE-NG?	11
1.2 WHAT IS EVE-NG USED FOR?	
1.3 Who is EVE-NG for?	
2.1 HARDWARE REQUIREMENTS	
2.1.1 Minimal Laptop/PC Desktop system requirements	
2.1.2 Recommended Laptop/PC Desktop system requirements	
2.1.3 Virtual Server system requirements	13
2.1.4 Dedicated Server (bare metal BM) system requirements	14
2.1.5 Nodes per lab calculator	
2.1.8 EVE INATIAGEMENT NETWORKS	
2.3 UNSUPPORTED HARDWARE AND SYSTEMS	
3 INSTALLATION	16
3.1 VMWARE WORKSTATION OR VM PLAYER	16
3.1.1 VMware Workstation VM installation using ISO image	16
3.1.1.1 EVE VM Setup and Settings	16
3.1.1.2 EVE-NG VM Installation steps	
3.2 VMware ESXI	
3.2.1 VMware ESXi EVE VM installation using ISO image	
3.2.1.1 EVE-NG ESXi VM Setup and Settings	
3.2.1.2 EVE-NG ESXi VM Installation steps	
3.3 BARE HARDWARE (BM) SERVER INSTALLATION	
3.3.1 BM Server installation EVE ISO	
3.4 GOOGLE CLOUD PLATFORM	
3.4.1 Google account	
3.4.2 Preparing Ubuntu boot disk template	
3.4.3 Creating VM	
3.4.4 EVE-NG Pro installation	
3.4.5 Access to Google Cloud EVE-PRO	
3.4.6 Optional: GCP MTU 1460 Firewall rules for native console use	
3.4.7 Optional: Network MTU 1500 settings and firewall rules for GCP	
3.4.8 Optional: GCP MTU 1500 Firewall rules for native console use	
3.5 EVE MANAGEMENT IP ADDRESS SETUP	
3.5.1 Static Management IP address setup (preferred)	
3.5.2 DHCP Management IP address setup	
3.5.3 Internet proxy setup	
3.5.4 Reset Management IP settings	
3.6 NATIVE TELNET CONSOLE MANAGEMENT SETUP	
3.6.1 Windows Native Console	
3.6.2 Linux Native Console	
3.6.3 MAC OSX Native Console	
3.7 LOGIN TO THE EVE WEB GUI	
4 EVE-NG PROFESSIONAL LICENSING	54
4.1 EVE-NG PROFESSIONAL BASE LICENSE	54



	4.2 EVE	-NG LEARNING CENTRE LICENSES	55
	4.3 EVE	-NG CORPORATE LICENSES	57
		R ROLES COMPARISON CHART	
		NSE PURCHASING AND ACTIVATION	
	4.6 LICE	NSE DEACTIVATION	61
	4.7 LICE	NSE REHOSTING.	62
5	EVE-NG	PROFESSIONAL UPDATE & UPGRADE	63
	5.1 EVE	-NG Professional Update	63
		-NG PROFESSIONAL UPGRADE	
6	TYPES	OF EVE MANAGEMENT CONSOLES	65
	6.1 NAT	TVE CONSOLE	65
	6.1.1	Native Console: telnet	
	6.1.2	Native Console: Wireshark	
	6.1.3	Native Console: VNC	
	6.1.4	Native Console: RDP	
	6.2 HTN	1L5 CONSOLE	
	6.2.1	HTML5 Console window functions	69
	6.2.2	HTML5 Console: Telnet	
	6.2.3	HTML5 Console: Wireshark	70
	6.2.4	HTML5 Console: VNC	
	6.2.5	HTML5 Console: RDP	
	6.3 HTN	IL5 DESKTOP CONSOLE	
	6.3.1	Login to HTML5 Desktop console	
	6.3.2	HTML5 Desktop Console: telnet	
	6.3.3	HTML5 Desktop Console: Wireshark	
	6.3.4	HTML5 Desktop Console: RDP	
	6.3.5	HTML5 Desktop Console: ThinClient Files exchange	76
7		B GUI MANAGEMENT	
7		MANAGEMENT PAGE	
7		Management Page	77 77
7	7.1 EVE	Management buttons Right click dropdown menu	77 77 78
7	7.1 EVE 7.1.1 7.1.2 7.1.3	MANAGEMENT PAGE	77 77 78 79
7	7.1 EVE 7.1.1 7.1.2 7.1.3	MANAGEMENT PAGE	77 77 78 79 79
7	7.1 EVE 7.1.1 7.1.2 7.1.3	MANAGEMENT PAGE	77 77 78 79 79
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running.	77 78 79 79 80
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared	77 78 79 79 80 80
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users	77 78 79 79 808080
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder	77 78 79 79 80808182
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users. Create folder Delete folder	77 78 79 79 80808182
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users. Create folder Delete folder Move Folder	77 78 79 79 8080818282
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder	77 78 79 79 808081828383
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8	MANAGEMENT PAGE. Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder	77 77 78 79 808081828383
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2	MANAGEMENT PAGE. Management buttons Right click dropdown menu. Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder Lab files Management.	77 77 78 79 80 80 81 82 83 84 84
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8	MANAGEMENT PAGE. Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder	77 78 79 79 80 80 81 82 83 83 84 84 84
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1	MANAGEMENT PAGE. Management buttons Right click dropdown menu. Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder Lab files Management Create Lab	777 778 79 79 80 80 81 82 83 84 84 84
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Lab files Management Create Lab Delete Lab	777 779 79 80 80 81 82 83 84 84 84 85 85
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3	MANAGEMENT PAGE. Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running. Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Lab files Management. Create Lab Delete Lab Clone Lab	777 779 79 80 80 81 82 83 84 84 84 85 85
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab	777 78 79 79 80 80 81 82 83 84 84 84 85 85 86
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab Export Lab	777 778 79 79 80 80 81 82 83 84 84 84 85 85 86 86
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab Export Lab Import Labs	777 778 786 79 80 80 81 82 83 84 84 84 85 86 87 87
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6 7.3 EVE	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab Export Lab Import Labs EMANAGEMENT DROPDOWN MENU	777 778 779 780 799 800 800 810 821 822 833 844 844 855 866 877 877
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6 7.3 EVE 7.3.1	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab Export Lab Import Labs EMANAGEMENT DROPDOWN MENU EVE User management	777 778 779 780 799 800 801 811 822 833 844 845 856 867 877 878
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6 7.3 EVE 7.3.1 7.3.1.1 7.3.1.2 7.3.1.3	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Delete Lab Move Lab Export Lab Import Labs Export Lab Import Labs EMANAGEMENT DROPDOWN MENU EVE User management Creating a new EVE User Edit EVE User User session termination	777 778 779 780 799 800 801 811 822 833 844 845 857 877 8792 939
7	7.1 EVE 7.1.1 7.1.2 7.1.3 7.2 FOL 7.2.1 7.2.1.1 7.2.1.2 7.2.1.3 7.2.1.4 7.2.1.5 7.2.1.6 7.2.1.7 7.2.1.8 7.2.2 7.2.2.1 7.2.2.2 7.2.2.3 7.2.2.4 7.2.2.5 7.2.2.6 7.3 EVE 7.3.1 7.3.1.1 7.3.1.2	MANAGEMENT PAGE Management buttons Right click dropdown menu Management tabs DERS AND LAB FILES MANAGEMENT Folders Management Default folder Running Default folder Shared Default folder Users Create folder Delete folder Move Folder Export Folder Import Folder Lab files Management Create Lab Delete Lab Clone Lab Move Lab Export Lab Import Labs EMANAGEMENT DROPDOWN MENU EVE User management Creating a new EVE User Edit EVE User	777 778 779 780 799 800 801 811 822 833 844 845 857 877 8792 893



7.3.2	EVE Node management	
7.3.2.1	Node management actions	
7.3.2.2	Node management filtering function	
7.3.3	EVE Lab management	
7.3.3.1	Lab management actions	
7.4 EVE	SYSTEM DROPDOWN MENU	
7.4.1	System Settings	
7.4.2	Cluster Management	101
7.4.3	System status	101
7.4.4	System logs	102
<i>7.4.5</i>	Stop All Nodes	
7.5 EVE	INFORMATION DROPDOWN MENU	103
7.6 EVE	LICENSING DROPDOWN MENU	103
7.7 OTH	ER TAB LINE INFO	103
	PREVIEW AND GLOBAL SETTINGS	
7.8.1	Lab preview window	
	Lab preview buttons	
	Lab preview information	
7.8.4	Lab properties	
	BAR FUNCTIONS	
	Add an object	
7.9.1.1	Node object	
7.9.1.1	Note object	
7.9.1.2	Picture object	
7.9.1.3	·	
7.9.1.4	Custom shape object	
	Text object	
7.9.1.6	Line object	
7.9.2	Nodes	
7.9.3	Networks	
7.9.4	Startup-configs	
7.9.5	Logical Maps	
7.9.6	Configured Objects	
7.9.7	More actions	
7.9.7.1	Start all nodes	
7.9.7.2	Stop all nodes	.113
7.9.7.3	Wipe all nodes	
7.9.7.4	Console to All Nodes	
7.9.7.5	Export all CFGs	
7.9.7.6	Edit lab	
7.9.7.7	Topology screenshot	.115
7.9.7.8	Set node's startup-cfg to default configset	
7.9.7.9	Set node's startup-cfg to none	
7.9.7.10	1 5	
7.9.8	Refresh Topology	
7.9.9	Lab page zoom/unzoom	116
7.9.10	Status	116
7.9.11	Lab details	116
7.9.12	Lab Tasks	117
7.9.13	Lab Chat	117
7.9.14	Lock Lab with password	
7.9.15	Locked Labs Access rules	
7.9.16	Fullscreen	
7.9.17	Hide interface labels	
7.9.17	Dark mode or Light mode	
7.9.10 7.9.19	Close lab	
7.9.19	Logout	
	VE LAB TOPOLOGY MENUS	
7.10		
	Lab topology menu	
7.10.2	CONTRACTION MENU	119



	7.10.3	Network Adding	120
	7.10.4	Bridge or Internal network menu	120
	7.10.5	Cloud and Private network menu	
	7.10.6	Stopped node menu	
	7.10.7	Running node menu	
	7.10.8	Selected nodes menu and features	
		VE LAB NODE STATES AND SYMBOLS	
	7.11.1	Stopped (non-running) nodes	
	7.11.1 7.11.2		
		Running nodes	
	7.11.3	Node connector symbol	
		THER	
	7.12.1	Notifications area	126
8	WORKI	NG WITH EVE LABS	128
	0.4		400
		ATING A LAB	
	8.1.1	Adding nodes to the lab	
	8.1.1.1		
	8.1.2	Edit node	
	8.1.2.1		
	8.1.2.2	· · · · · · · · · · · · · · · · · · ·	
	8.1.3	Wipe Node	
	8.1.4	Interconnecting nodes	
	8.1.5	Edit connection link style	135
	8.1.6	Edit connection link quality	136
	8.1.7	Suspend or resume link connection	137
	8.1.8	Delete connection between nodes	
	8.1.9	Delete Node	
		INING LABS	
	8.2.1	Starting lab	
	8.2.2	Interconnecting running nodes (hotlinks)	
	8.2.3	Link quality delay, packet loss, jitter and rate feature	
		ING LABS	
		PPING LABS	
		RT SAVED LAB	
		RKING WITH MULTIPLE RUNNING LABS	
		DRTING LABS	
		ORTING LABS	
		ETING LABS	
		OVING LABS	
	8.11 S	HARED PROJECT/LAB	
	8.11.1	Create Project Lab share	141
	8.11.2	Remove Lab share	141
	8.11.3	Working with shared lab	142
	8.12 A	SSIGNED SINGLE LAB	
9	EVE CL	OUDS AND NETWORKS	111
Э			
		DGE NETWORK	
	9.2 THE	EXPERIMENTAL SMART BRIDGE FEATURE	144
	9.3 INTE	RNAL NETWORK	145
		/ATE NETWORK	
		Network	
		IAGEMENT CLOUDO INTERFACE	
		NOVE CLOUD INTERFACES	
		IER CLOUD INTERFACES	
		INECTING EXTERNAL VM MACHINES TO THE EVE LAB	
		ESXi VM machines	
	9.9.1	VMWare workstation machines	
	9.9.2		
	9.10 C	ONNECTING EVE LAB TO A PHYSICAL DEVICE	100



	9.10.1	ESXi EVE	
	9.10.2	VMWare workstation EVE	158
	9.10.3	Bare metal server EVE	160
10	ADVA	NCED EVE LAB FEATURES	162
11	0.1 LA	AB DESIGN OBJECTS	162
- ''	10.1.1	Custom shape	_
	10.1.1	Resize square or circle objects	162
	10.1.2	Text	
	10.1.3	Add picture to the topology	
	10.1. 4 10.1.5	Custom object linking with telnet or other protocol	
	10.1.5	Line object	
	10.1.8	Nodes connection links design	
	10.1.7	Cloning objects and overlay positions	
	10.1.8	Objects Editing	
	10.1.9	Lock objects movement	
1/		JSTOM DESIGN LOGICAL TOPOLOGY	
- 11	10.2.1	Custom design upload	
	10.2.1	Custom topology mapping	
	10.2.2	Delete topology or mapping	
1,		ULTI-CONFIGURATION SETS EXPORT FEATURE	
- 11	J.S IVI 10.3.1	Supported nodes for configuration exports	
	10.3.1		
	10.3.2	Startup config management	
	10.3.2.1		
	10.3.2.2		
	10.3.2.4	•	
	10.3.2.5		
	10.3.3	Export Default configuration set	
	10.3.4	Boot nodes from exported Default config set	
	10.3.5	Export new custom config set	
	10.3.6	Edit exported configurations	
	10.3.7	Set lab to boot from config set	
	10.3.7	Set lab to boot from none	
	10.3.9	Delete a config set	
	10.3.10	Rename a config set	
	10.3.10	Export a config set to your local PC	
	10.3.11	Import config set from local PC	
	10.3.12	Export a single nodes config to your local PC	
	10.3.13	Import a single nodes config from your local PC	101
	10.3.14	Set lab nodes to boot from different config sets	
	10.3.15	Lab config script timeout	
1/		AB TIMER	
- 11	10.4.1	Set the Lab Countdown Timer	
	10.4.1	Stop the Lab Countdown Timer	
1/		NB TASKS	
- ''	10.5.1	Creating a new simple task	
	10.5.1	Edit a simple task	103
	10.5.2	Create a multi tabs task (task on multiple tabs/pages)	
	10.5.3 10.5.4		
	10.5.4 10.5.5	Edit a multi tabs task (task on multiple tabs/pages) Edit tabs (Multi tabbed task).	194
	10.5.5 10.5.6	Create a task with your PDF workbook	
	10.5.6 10.5.7	Create a task with Online document (PDF or HTML)	
	10.5.7 10.5.8	Delete a task with Online document (PDF or HTML)	
11	WIRES	SHARK CAPTURE	190
4	1.1 N	ATIVE CONSOLE WIRESHARK CAPTURING	100
-		TML5 CONSOLE WIRESHARK CAPTURING	
•		TML5 CONSOLE WIRESHARK CAPTURING	
- 1	ı.ט ⊓	I IVILU DEUN TUR GUNDULE WIKEDHAKK CAPTUKING	134



12	THII	NCLIENT FILE EXCHANGE	196
12.	1	THINCLIENT FILES DOWNLOADING	196
12.		THINCLIENT FILE UPLOAD	
12.	3	OTHER THINCLIENT FILE OPERATIONS	199
13	DO	CKERS	202
13.	1	EVE INTEGRATED DOCKER STATIONS	202
	' 13.1.1		
	13.1.2		
	13.1.3		
	13.1.4		
1	13.1.5		
1	13.1.6		
1	13.1.7	Docker server-gui SSH root access activation	209
13.	2	DOCKER CONSOLES	
13.	-	DOCKER CLI ROOT ACCESS	
13.	-	DOCKERS RE-INSTALL/UPDATE	
13.		EXTRA DOCKER PACKAGES	
13.		THIRD PARTIES DOCKERS	
	13.6.1		
	13.6.2		
13.		CUSTOMIZE DOCKER IMAGE WITH YOUR OWN CHANGES.	
13.		CUSTOM DOCKER NAME TAGS	
13.	_	DELETE DOCKER IMAGE FROM EVE	
14	EVE	CLUSTER SYSTEM	218
14.	1	EVE CLUSTER LICENSING	218
14.	2	EVE CLUSTER DESIGN MODELS	218
1	14.2.1		
1	14.2.2	ESXi Virtual Machines cluster	219
1	14.2.3	,	
	14.2.4		
	14.2.5		
	3	EVE CLUSTER PRE-REQUISITES	
	14.3.1		
	4.3.2	5	
	14.3.3	5	
	14.3.4		
	14.3.5		
14. 14.	-	EVE CLUSTER MASTER NODE INSTALLATION	
	อ 14.5.1		
	14.5.2		
14.		BARE HARDWARE (BM) SERVER EVE SATELLITE INSTALLATION	
	0 14.6.1		226 226
-	14.6.2		
14.		GOOGLE CLOUD EVE SATELLITE INSTALLATION	
1	4.7.1		
1	14.7.2		
	14.7.3	, ,	230
1	14.7.4		
1	14.7.5	Creating VM	231
1	14.7.6	EVE-NG Satellite installation	234
1	14.7.7	GCP Firewall rules for Cluster	235
14.	-	CLUSTER MANAGEMENT	
	14.8.1	Join Satellite nodes to the Master	
	14.8.2		
1	14.8.3	Re-join Satellite nodes from the Master	237



14.8.4 Change Satellite IP address	
14.9 CLUSTER ASSIGNMENT HIERARCHY	
14.9.1 Single Satellite server assignment	
14.9.1.1 User assignment to the dedicated Satellite (Option 1)	
14.9.1.2 Lab assignment to dedicated cluster Satellite (Option 2)	
14.9.1.3 Creating EVE labs in Cluster (Option 3)	
14.9.2 Multi Satellite servers' assignment	
14.9.2.1 Multi Satellites user Profiles	
14.9.2.2 User assignment to the dedicated Satellites	
14.9.3 Master images synchronization with Satellites	
14.10 CLUSTER SYSTEM MONITORING	
14.10.1 Cluster Monitoring page	
14.10.2 Satellite disaster recovery	
14.10.3 EVE Cluster Status	
14.10.4 Cluster monitoring cli commands	
14.11 CLUSTER SYSTEM UPGRADE	246
15 EVE TROUBLESHOOTING	247
15.1 CLI DIAGNOSTIC INFORMATION DISPLAY COMMANDS	
15.1.1 Display full EVE Pro diagnostic	
15.1.2 Display the currently installed EVE Pro version:	
15.1.3 Display if EVEs Intel VT-x/EPT option on/off:	
15.1.4 Display EVEs CPU INFO:	
15.1.5 Display EVEs CPU manufacturer:	
15.1.6 Display EVEs HDD utilization.	
15.1.7 Display EVEs Bridge interface status	
15.1.8 Display EVEs system services status	
15.2 CORRECT EVE SERVER NETWORK INTERFACES ORDER	
15.3 EXPAND EVES SYSTEM HDD	
15.3.1 HDD space alert	249
15.3.2 Expand HDD on VMware Workstation	250
15.3.3 Expand your HDD on ESXi	250
15.3.4 Expand your HDD on a Bare Metal EVE Server	251
15.4 RESET MANAGEMENT IP	251
15.5 EVE PRO SQL DATABASE RECOVERY	251
15.6 EVE PRO MIGRATION FROM HOST TO HOST	252
15.7 EVE LOG FILES	252
15.8 EVE CLI DIAGNOSTIC INFO	
16 EVE EXTRAS	253
	233
16.1 EVE Pro Radius server setup for user authentication	
16.1.1 EVE User setup for Radius authentication	253
16.2 ACTIVE DIRECTORY USER AUTHENTICATION	254
16.2.1 EVE User setup for AD (LDAP) authentication	255
16.3 LAB CHAT	
16.4 CUSTOM MAC ADDRESS FOR NODE MANAGEMENT	256
16.5 WINDOWS NODE SETTINGS FOR WIFI DONGLE	257
16.6 MASTER SERVER NIC PORTS ORDER CHANGE	259
16.7 SATELLITE SERVER NIC PORTS ORDER CHANGE	
17 IMAGES FOR EVE	261
17.1 QEMU IMAGE NAMING TABLE	
17.2 HOW TO PREPARE IMAGES FOR EVE	262
17.3 HOW TO ADD CUSTOM IMAGE TEMPLATE	
17.3.1 Templates folder choice	
17.3.2 Prepare template file	
17.3.3 Prepare interface format and name lines	
17.3.4 Edit your new template file:	
,	266



17.3.6	Template use	266
	OW TO HIDE UNUSED IMAGES IN THE NODE LIST	
18 EVE B	ACKUP SOLUTION	267
18.1 B	ACKUP MANAGER	267
18.1.1	Backup Manager Installation	267
18.1.2	Setup external SFTP or FTP server	267
	Backup Manager SFTP/FTP settings	
18.2 Ci	REATE AN EVE-NG BACKUP	268
18.2.1	Backup option All	268
	Backup option custom selected	
18.2.3	Backup option with Mirroring selected	269
	ESTORE DATA FROM EVE-NG BACKUP	
18.3.1	Select restore backup folder	270
	Select the items to restore	
19 EVE R	ESOURCES	272



Preface

When I first heard about EVE-NG I was skeptical. Back then I used to Lab mainly with ESX by deploying many virtual Devices and connecting them manually by separate vSwitches for Point-to-Point connections. The Problem with that was, that it was extremely time-consuming and did not scale - for every new Device I had to create multiple vSwitches to interconnect them with the virtual Machines - a Nightmare. I was in the middle of my JNCIE-Exam-Prep when I first saw EVE-NG on Twitter - I downloaded the Community Edition, which was the only Edition back then and I was amazed how easy Labbing all of a sudden was. No more deploying of vSwitches to interconnect nodes and boy did it Scale...

If you follow me on Twitter you know, that I'm one of the hardest Juniper Fanboys and of course my Goal was to "Juniperize" EVE. I started to get in touch with UD and Alain and found myself into the Position as one of the Juniper Test Guys. Meanwhile I added nearly all Juniper related Devices (including vSRX and JATP) and I still test a Lot - but now on EVE-Pro.

The Pro-Edition was a big step forward for the Project. It added some nice Features like "hot-add-interconnect" and the Ability to use EVE-NG with multiple Users. Especially Companies will love EVE as it is THE Solution for Labs and PoC's. I have successfully run over 30 PoC's in EVE and over 100 Labs (Job-Related and Personal Labs) - and I still enjoy it every day thanks to EVE and the amazing Team behind it. When the Guys asked me to write the Introduction, I was of course honored and now this Book is finally coming out to help you on your Quest to Setup, Run and Manage EVE-NG in a lot of possible ways.

Well - enough from my Side. I hope you enjoy this Cookbook and use it wisely for your Everyday EVE Work. If you have Problems there is always the EVE-Forum and Live-Helpdesk - you will also find me there from time to time :)

I wish you happy reading and if you think, that this Product is amazing feel free to support it by buying the PRO-Edition or Donating a bit – it helps to expand this already cool Product even more and it also honors all the work that the Guys spent in it.

Christian Scholz @chsjuniper

© EVE-NG LTD Page 10 of 272



1 Introduction

1.1 What is EVE-NG?

To describe what Emulated Virtual Environment – Next Generation (EVE-NG) is without solely stating dry facts about features, we need to elaborate more on what EVE-NG can be used for and whom it would be useful for.

In some trivial dry words, EVE-NG gives you tools to use around virtual devices and interconnect them with other virtual or physical devices. Many of its features greatly simplify the usability, re-usability, manageability, interconnectivity, distribution and therefore the ability to understand and share topologies, work, ideas, concepts or simply "labs". This can simply mean it will reduce the cost and time to set up what you need or it might enable you to do tasks you would not have thought could be done this simple.

1.2 What is EVE-NG used for?

This is the real question but there is no finite answer, the possibilities are almost limitless and depends on what you want to use it for.

It can be used for studying all kinds of technologies. You can learn about general technologies or vendor specific topics. You can test new technologies like network automation, SDN, etc. It can be used to recreate corporate networks and test changes before putting them into production. You can create proof of concepts for clients. You can troubleshoot network issues by recreating them and e.g. use Wireshark to inspect packets.

It is most definitely not just for networking, it can be used to test software in simulated networks, test out security vulnerabilities of any kind, system engineering like LDAP and AD servers and many more areas.

You could set it up to automate sandboxing unknown files/software and use software to analyse short- and long-term behaviour for malicious intent much simpler than without EVE-NG.

The list of what EVE-NG can be used for could go on indefinitely, possibilities are limited by knowledge and imagination only. Both of which can be improved with EVE-NG.

To get a very small idea of what can be done with EVE-NG, check out the tested/<u>supported images</u> (many have not been tested, almost everything virtual should run on EVE-NG) and refer to section 17.

EVE-NG helps you achieve what you want to and more.

1.3 Who is EVE-NG for?

EVE-NG is for everyone working in the Information Technology Sector, period.

It is for very large enterprise companies, training facilities, service providers, consultants, people who want to train themselves; it is for everyone, it is for YOU!

Use-cases that are more than worth it, almost priceless even, can be found everywhere.

The EVE-NG community version is free for everyone; while the paid professional version adds a few things that make your life easier. Almost everything can still be done with the free version, just less conveniently and therefore more time-consuming.

However, with the free version, the possibility to train yourself with technologies, hone your skills and become an expert even with very no monetary possibilities. For some this is and has been life changing.

© EVE-NG LTD Page 11 of 272



2 System requirements

EVE-NG software is available in the ISO file format. The ISO is an open standard for packaging and distributing install media. It can be used to deploy a VM in hypervisors like VMware Workstation, Player and ESXi. Please note that installing EVE as a Virtual Machine (VM) will mean any nodes deployed within EVE will be nested. Nested virtualization causes degraded performance in deployed nodes. This should be fine for lab purposes as long as the host meets or exceeds the resource requirements for the deployed nodes.

EVE-NG can also be installed directly on physical hardware, without a hypervisor, using the provided ISO image. This is referred to as a "bare metal" install and is the most recommended method of installing EVE-NG.

2.1 Hardware requirements

2.1.1 Minimal Laptop/PC Desktop system requirements

Prerequisites:

CPU: Intel CPU supporting Intel® VT-x /EPT virtualization Operating System: Windows 10, 11 or Linux Desktop VMware Workstation 16.0 or later VMware Player 16.0 or later

PC/Laptop HW requirements	
CPU	Intel i7 (8 Logical processors vCPU), Enabled Intel virtualization in BIOS
RAM	8Gb
HDD Space	500Gb or more
Network	LAN/WLAN
EVE Virtual machine requirements	
CPU	1/8 (Amount of processors/Number of cores per processor) Enabled Virtualize Intel VT-x/EPT or AMD-V/RVI and virtualize IOMMU options
RAM	8Gb or more
HDD	60Gb or more
Network	VMware NAT or Bridged network adapter

Note: Minimal/small PC Desktop/Laptop will be able to run small Labs. The performance and quantity of nodes per lab depend on the types of nodes deployed in the lab.

Example:

IOL image-based nodes: up to 30- nodes per lab Dynamips image-based nodes: up to 20-25 nodes per lab vIOS image-based nodes: up to 8-10 nodes per lab CSRv1000 or XRv image-based nodes: up to 2-3 per lab

© EVE-NG LTD Page 12 of 272



2.1.2 Recommended Laptop/PC Desktop system requirements

Prerequisites:

CPU: Intel CPU supporting Intel® VT-x /EPT virtualization Operation System: Windows 10, 11 or Linux Desktop VMware Workstation 16.0 or later VW Ware Player 16.0 or later

PC/Laptop HW requirements		
CPU	Intel i7 (16 Logical processors), Enabled Intel virtualization in BIOS	
RAM	32Gb	
HDD Space	500Gb or more	
Network	LAN/WLAN	
EVE Virtual machine requirements		
CPU	1/16 (Amount of processors/Number of cores per processor) Enabled Virtualize Intel VT-x/EPT or AMD-V/RVI and virtualize IOMMU options	
RAM	24Gb or more	
HDD	200Gb or more	
Network	VMware NAT or Bridged network adapter	

Note: PC Desktops/Laptops will be able to run small to medium Labs. Performance and quantity of nodes per lab depend on the type of nodes deployed in the lab.

Example:

IOL image-based nodes: up to 120 nodes per lab vIOS image-based nodes: up to 20-40 nodes per lab

CSR image-based nodes: up to 10 per lab

2.1.3 Virtual Server system requirements

Prerequisites:

CPU: Intel Xeon CPU supporting Intel® VT-x with Extended Page Tables (EPT) Operation System: VM Ware ESXi 6.7 or later

	Server HW requirements		
CPU	Recommended CPU 2x Intel Xeon (48 Logical processors) or better supporting Intel® VT-x with Extended Page Tables (EPT) Minimum CPU is any Intel Xeon CPU supporting Intel® VT-x with Extended Page Tables (EPT) or better		
RAM	128Gb		
HDD Space	2Tb		
Network	LAN Ethernet		
	EVE Virtual machine requirements		
CPU	2/24 (48) (Number of processors/Cores per socket) Set Expose hardware assisted virtualization to the guest OS to ON (checked) and set Expose IOMMU to the guest OS to ON (checked)		
RAM	64Gb or more		

© EVE-NG LTD Page 13 of 272



HDD	800Gb or more
Network	vSwitch/VMnet

Note: Performance and quantity of nodes per lab depends from the type of nodes used in the lab.

Example:

120 IOL image-based lab

20 CSRv1000 image-based nodes per lab

2.1.4 Dedicated Server (bare metal BM) system requirements

Prerequisites:

CPU: Intel Xeon CPU supporting Intel® VT-x with Extended Page Tables (EPT) Operation System: Ubuntu Server 22.04 LTS x64

Server HW requirements			
CPU	Recommended CPU Intel Xeon (48 Logical processors) or better supporting Intel® VT-x with Extended Page Tables (EPT) Minimum CPU is any Intel Xeon CPU supporting Intel® VT-x with Extended Page Tables (EPT)		
RAM	128Gb		
HDD Space	2Tb		
Network	LAN Ethernet		

Note: Performance and quantity of nodes per lab depends from type of nodes used in the lab.

2.1.5 Nodes per lab calculator

It is recommended to use the "nodes per lab calculator" to achieve best performance and avoid overloading your EVE system.

https://www.eve-ng.net/index.php/download/#CALC

2.1.6 EVE Management Networks

NOTE: Please make sure if these subnets are NOT used in your network outside of EVE.

172.29.129.0/24 (NAT Interface)

172.29.130.0/24 (Cluster VPN subnet, wg0 interface)

172.17.0.0/16 (Dockers consoles)

To change these networks please refer chapter 7.4.1

2.2 Supported virtualization platforms and software

- VMware Workstation 16.0 or later
- VMware Player 16.0 or later
- VMware ESXi 6.7 or later
- Ubuntu Server 22.04 LTS as platform for bare metal
- Google Cloud Platform

© EVE-NG LTD Page 14 of 272



AMD CPU based PC or Server (the Newest AMD CPU versions are supported)

2.3 Unsupported hardware and systems

The following are currently not supported officially:

- Oracle VirtualBox virtualization
- Citrix XenServer
- Microsoft HyperV
- Proxmox
- MAC OSX M Series CPU
- External HDD, like OneDrive, USB external HDD, DAS, NAS or SAN.
- AWS Cloud VM
- VM Ware NAS or DAS HDD system
- Wireless NIC for Bare server EVE installation

© EVE-NG LTD Page 15 of 272




3 Installation

3.1 VMware Workstation or VM Player

3.1.1 VMware Workstation VM installation using ISO image

Download EVE-NG Professional Full ISO distribution image: https://www.eve-ng.net/index.php/download/

3.1.1.1 EVE VM Setup and Settings





Step 3: Select a Guest Operating system: Linux and select the version: **Ubuntu 64-bit**

Step 4: Enter the name for your EVE-NG-PRO VM and select Location where your EVE VM will be stored on the host PC.

© EVE-NG LTD Page 16 of 272







Step 7a: Select your desirable Network Adapter. For Laptop PC


NOTE: It is recommended to choose the NAT adapter option for Laptops to avoid EVE management interface IP changes. This can happen anytime the laptop is


Step 7b: Select your desirable Network Adapter. For Desktop PC

NOTE: Desktop PC EVE management interface can be either NAT or Bridged to home LAN subnet. Internet and DNS

© EVE-NG LTD Page 17 of 272









© EVE-NG LTD Page 18 of 272








© EVE-NG LTD Page 19 of 272




Step 14: IMPORTANT Set Processors "Number of processors" and "Number of cores per processor". Set Virtualize Intel VT-x/EPT or AMD-V/RVI to ON (checked) and set Virtualize IOMMU (checked)

NOTE: VMware Player will display only one CPU option: Number of processors.




Step 15: Select CD/DVD Option: "use ISO image file." Browse to your downloaded Full EVE-PRO.iso (actual name will be different) file



Step 16: Confirm VM Settings.

Step 17: Optional VM machine boot settings. If you are using Firmware type UEFI, make sure that enable secure boot is disabled.



3.1.1.2 EVE-NG VM Installation steps

EVE VM Installation from ISO has 3 Phases

Phase 1 (Ubuntu installation)


© EVE-NG LTD Page 20 of 272



Step 1: Power ON EVE VM. Chose "Install EVE NG Pro Server" and confirm with Enter.



Step 2: Make sure that English is selected and confirm with Enter.



Step 3: Make sure that English US Keyboard is selected and confirm with Enter.



Step 4: Select "Continue" and confirm with Enter. After completion of this task, the EVE installation will autoreboot to continue Phase 2.



EVE VM Installation Phase 2 (EVE-NG installation)

Step 5: Please wait, the EVE-NG installation **Phase 2** will start automatically.

Do NOT login in this stage!

```
Second stage install in progress....
eve–ng login: _
```

Step 6. After installation EVE VM will autoreboot and EVE login screen will appear, login in CLI with root/eve and follow installation Phase 3

```
The state of the s
```

© EVE-NG LTD Page 21 of 272



EVE VM Installation Phase 3 (Management IP setup and updates)

Step 7: Setup EVEs Management IP address. A Static IP address setup is preferred. Internet and DNS reachability is a MUST

Follow steps in section:

3.5.1 for static IP, 3.5.2 for DHCP IP

Step 8: Internet and DNS reachability is a MUST

After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

If required, follow steps in section: 5.1, 5.2

NOTE: Verify your EVE-NG server installation, type "dpkg -l eve-ng-pro" command, it must display latest EVE Pro version

Step 9: Proceed to section 4 "Obtain EVE-NG Professional license"


IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 16

3.2 VMware ESXi

3.2.1 VMware ESXi EVE VM installation using ISO image

Download EVE-NG Professional Full ISO distribution image: https://www.eve-ng.net/index.php/download/

▲ IMPORTANT NOTE: Make sure that you have set Security Policy (Promiscuous mode, forged transmits and MAC changes) settings on the vSwitch and Port group to Accept.



IMPORTANT NOTE: For EVE VMs running on ESXi, with NIC Teaming Network, please follow the steps below to edit the reverse path settings

© EVE-NG LTD Page 22 of 272



- From the Navigator window select Manage > System > Advanced settings.
- Scroll down or use the search bar to go to the Net.ReversePathFwdCheckPromisc option.
- ❖ Select Net.ReversePathFwdCheckPromisc and click Edit option.
- ❖ In the Edit option Net.ReversePathFwdCheckPromisc window update the New value field to 1 and click Save.
- IMPORTANT NOTE: For EVE VMs running on ESXi, with NIC Teaming Network, managed by vCenter and VDS Network please follow the steps below to edit the reverse path settings
 - From the Side Inventory select the ESXi host where the EVE VM is installed Configure > System > Advanced System Settings.
 - Edit Advanced System Setting
 - Scroll down to find Net.ReversePathFwdCheckPromisc option.

Net.ReversePathFwdCheckPromisc 1


- In the Edit option Net.ReversePathFwdCheckPromisc window update the New value field to 1 and click Save.
- Reboot ESXi host
- Select the VDS Workgroup used for EVE VM networking
- Edit VDS Workgroup security setting to allow promiscuous traffic

Distributed Port Group - Edit Settings | DPortGroup-VLAN10



Download EVE-NG Professional ISO distribution image: https://www.eve-ng.net/index.php/download/


3.2.1.1 EVE-NG ESXi VM Setup and Settings




© EVE-NG LTD Page 23 of 272



Step 3: Enter the name for your EVE-PRO VM and select Guest Operating system Linux and version: Ubuntu 64-bit




Step 4: Select Location where your EVE VM will be stored in HDD.




Step 5: A IMPORTANT OPTION for ESXi 6.7.x or later.

Set Processors "Number of processors" and Set "Cores per Socket". If your server has dual CPU, then Cores per socket will be divided by 2. Example below, shows dual CPU Server VM setup with 48 CPU with 24 cores per socket (2).

Set Expose hardware assisted virtualization to the guest OS to ON (checked) and set Expose IOMMU to the guest OS to ON (checked)



Step 6: Assig desired RAM for your EVE




Step 7: Set the size of HDD for your new EVE VM. It is recommended to set "Thick Provisioned eagerly provisioned". Server

Step 8: Set your Management network. Adapter type VMXNET3

© EVE-NG LTD Page 24 of 272









NOTE: Additional Network Adapters can be added for further use.

Step 9: Set DVD drive to "Datastore ISO File" and browse your uploaded Full-EVE-PRO.iso (ISO name can vary). Make sure that Status is checked ON, "Connect at power on"



Step 10: Set DVD drive to "Datastore ISO File" and browse your uploaded Full-EVE-PRO.iso (EVE ISO name can vary). Make sure that Status is checked ON, "Connect at power on" Hit the "Finish"




Step 11: IMPORTANT If you are using ESX 8.0 or later, select the Edit your VM and switch to "VM Options". Firmware *EFI Boot*.

Follow to "Boot Options" and de-select (uncheck) "Whether or not to enable UEFI Secure boot for this VM"

Step 12: Start VM

© EVE-NG LTD Page 25 of 272






3.2.1.2 EVE-NG ESXi VM Installation steps

EVE ESXi VM Installation from ISO has 3 Phases


Phase 1 (Ubuntu installation)



© EVE-NG LTD Page 26 of 272



Step 3: Make sure if English US keyboard is selected and confirm with Enter.



Step 4: Select "Continue" and confirm with Enter.



EVE VM Installation Phase 2 (EVE-NG installation)

Step 5: Please wait, the EVE-NG installation **Phase 2** will start automatically.

Do NOT login in this stage!

```
Second stage install in progress....
eve-ng login: _
```

Step 6. After installation EVE VM will auto reboot and EVE login screen will appear, login in CLI with root/eve and follow installation Phase 3

```
The state of the s
```

EVE VM Installation Phase 3 (Management IP setup and updates)

Step 7: Setup EVEs Management IP address. A Static IP address setup is preferred. Internet and DNS reachability is a MUST

Follow steps in section:

3.5.1 for static IP, 3.5.2 for DHCP IP

Step 8: Internet and DNS reachability is a MUST

After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

If required, follow steps in section: 5.1, 5.2

NOTE: Verify your EVE-NG server installation, type "dpkg -I eve-ng-pro" command, it must display latest EVE Pro version (please note that version of EVE-PRO will be newest)

root@eve-ng:~# dpkg -l eve-ng-pro
Desired=Unknown/Install/Remove/Purge/Hold
| Status=Not/Inst/Conf-files/Unpacked/halF-conf/Half-inst/trigaWait/Trig-pend

© EVE-NG LTD Page 27 of 272



NOTE: If your newly installed EVE-PRO shows nothing like above, you must check your internet reachability and verify DNS configuration on your EVE-PRO server.

```
root@eve-ng:~# ping www.google.com
PING www.google.com (172.217.22.164) 56(84) bytes of data.
64 bytes from arn09s11-in-f164.1e100.net (172.217.22.164): icmp_seq=1
ttl=120 time=8.84 ms
64 bytes from arn09s11-in-f164.1e100.net (172.217.22.164): icmp_seq=2
ttl=120 time=8.84 ms
^C
--- www.google.com ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1001ms
rtt min/avg/max/mdev = 8.848/8.848/8.849/0.094 ms
root@eve-ng
```

Step 9: Go to section 4 to obtain a license for EVE-NG Professional

- IMPORTANT NOTE: If your Network interfaces order has been changed, please follow instruction to section 16.6
- ▲ IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 17

3.3 Bare hardware (BM) server installation

3.3.1 BM Server installation EVE ISO

IMPORTANT NOTE: The bare server HDD system Raid, etc or single virtual drive, must be set before you start installation!

Download EVE-NG Professional Full ISO distribution image: https://www.eve-ng.net/index.php/download/

Phase 1 (Ubuntu installation)

Step 1: Create a bootable DVD disk or USB flash drive (Rufus tool is strongly recommended) with a Full EVE ISO image. Boot your server from ISO. Chose Bare metal Option, following by Install BM EVE-NG Pro Server and confirm with	Step 2: Select English language. Confirm with Enter.
Enter.	
LINGI.	

© EVE-NG LTD Page 28 of 272







Step 3: Make sure if English US keyboard is selected and confirm with Enter.



Step 4: Select [X] "Use an entire disk" and [X] Set up this disk as and LVM group confirm with Enter. For advnaced (multi hdd as single LVM) setup it can be Custom storage option selected. For Custom storage selection, please refer to the Ubuntu official documentation or

https://www.eve-ng.net/wpcontent/uploads/2023/03/EVE-Doc-3023-LVM-HDD-systems.pdf



EVE VM Installation Phase 2 (EVE-NG installation)

Step 5: Please wait, the EVE-NG installation **Phase 2** will start automatically. Do NOT login in this stage!

Step 6. After installation EVE VM will autoreboot and EVE login screen will appear, login in CLI with root/eve and follow installation

© EVE-NG LTD Page 29 of 272



```
Phase 3

cee-ng login: _

progress...

progr
```

EVE VM Installation Phase 3 (Management IP setup and updates)

```
Step 7: Setup EVEs Management IP address. A Static IP address setup is preferred. Internet and DNS reachability is a MUST

Follow steps in section:

3.5.1 for static IP, 3.5.2 for DHCP IP

Step 8: Internet and DNS reachability is a MUST

After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

If required, follow steps in section: 5.1, 5.2
```

Verification: Verify your EVE-NG server installation, type "dpkg -l eve-ng-pro" command, it must display latest EVE Pro version

```
Step 9: Continue to section 4 to obtain your EVE-NG Professional license
```

- IMPORTANT NOTE: If your Network interfaces order has been changed, please follow instruction to section 16
- ▲ IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 17

3.3.2 BM Server Installation Ubuntu legacy ISO

▲ IMPORTANT NOTE: The bare server HDD system Raid, etc or single virtual drive, must be set before you start installation!

© EVE-NG LTD Page 30 of 272



Mandatory Prerequisites: Internet and DNS must be reachable from your Server. This ISO installation requires internet access to get updates and install the latest EVE-PRO version from the EVE-NG repository. DNS must resolve names!

Download Ubuntu Legacy Server installation image/ISO https://releases.ubuntu.com/jammy/

Phase 1 (Ubuntu installation)


flash drive (Rufus tool is strongly recommended) with an Ubuntu server image.

Boot your server from ISO. Select English language. Confirm with Enter.

Hillsomen Blenverue Heicore Lodgo пожаюваты Heilori (Heild Selection) (Heild Heild Selection) (Heild Selection) (Heild Selection) (Heild Selection) (Heild Selection) (Heild Heild Selection) (Heild Selec

Step 1: Create a bootable DVD disk or USB

Step 2: Select Option Update to the new installer, following by Enter.



Step 3: Make sure if English US keyboard is selected and confirm with Done/Enter.



Step 4: Select Option Ubuntu Server [X], following by Done/Enter.



Step 5: If your network has **DHCP ENABLED**, Continue to **Step 11**

Step 6: If your network has not **DHCP.**Static IP setup. If you have not enabled DHCP in the network, you must assign an IP address manually. Use arrow UP key to

© EVE-NG LTD Page 31 of 272



select your interface for IP address.assignment.

Network connections [Network connections | [Networ

Step 7: Confirm interface selection with Enter, select "Edit IPv4" and confirm with Enter again.



Step 8: Hit Enter on IPv4 Method and select "Manual", confirm with Enter.



Step 9: Enter your "Subnet", "IP Address", "Gateway IP", "Domain server IPs" and "Search domain". Select "Save" and confirm with Enter. NOTE, it is very important that your DNS (Name servers) will resolve Internet names.



Step 10: Select "Done" and confirm with



Step 11: If your DHCP IP settings are correct, select Done and confirm with Enter.

Step 12: If you have proxy in use for your internet, assign your network proxy settings.

© EVE-NG LTD Page 32 of 272






If no proxy in use, with Tab key select Continue and confirm with Enter.




Step 13: Select [X] "Use an entire disk" and [X] Set up this disk as and LVM group confirm with Enter. For advnaced (multi hdd as single LVM) setup it can be Custom storage option selected. For Custom storage selection, please refer to the

Ubuntu official documentation or

https://www.eve-ng.net/wpcontent/uploads/2023/03/EVE-Doc-3023-LVM-HDD-systems.pdf



Step 14: Select "Continue" and confirm with Enter.




Page 33 of 272 © EVE-NG LTD



Step 15: Confirm your HDD configuration Done/Enter




Step 16: Select "Continue" and confirm with Enter.



Step 17: Fill the *non-root user* profile following by Done/Enter



Step 18: Skip Ubuntu Pro installation Continue confirm with Enter.




Step 19: Select [X] "Install OpenSSH Server" and confirm Done/Enter.

Step 20: Select "Continue" and confirm with Enter.

© EVE-NG LTD Page 34 of 272







Step 21: DO NOT Select any other services confirm Done/Enter.



Step 22: Select "Continue" and confirm with Enter.



Step 23: After the Ubuntu "Install Complete" select "Reboot Now" and hit Enter to continue.



Step 24: Remove CD/DVD ISO Media following by Enter.

© EVE-NG LTD Page 35 of 272



Step 25: Login into your Ubuntu server with previously created non-root user: eveuser/test123



Step 26: IMPORTANT: Set root user password, Example:

sudo su test123 passwd root eve eve

eveuser@eve-ng:~\$ sudo su
[sudo] password for eveuser:
root@eve-ng:/home/eveuser# cd
root@eve-ng:~# sudo passwd root
New password:
Retype new password:
passwor password updated successfully
root@eve-ng:~# _

Step 26: Allow permissions for root administrator user SSH to your server.

```
mano /etc/ssh/sshd_config

Edit to: PermitRootLogin yes

ctrl+o Enter for save

crlr +x for exit

restart ssh service

service sshd restart

# #Open850: sshd_config.v 1.101 2017/03/14 07:19:07 dJm Exp #

# #This is the sshd server system-ubde configuration file. See

# sshd_config(s) for more information.

# This sshd was compiled with #ATHE/USDr/bln:/bln:/bsr/sbln:/sbln

# The strategy used for options in the default sshd_config shiped with
# OpenS51 is to specify options with their default value where
# possible, but leave then consented. Uncommented options over-ide the
# whickney /etc/ssh/ssh_host_mas_key
##dottes/family smy
#Listenddiress :
##dottkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_sey
##ostkey /etc/ssh/ssh_host_mas_key
##ostkey /etc/ssh/ssh_host_mas_sey
##ostkey /etc/ssh/ssh_host
```

Step 27: IMPORTANT: Set root user password, Example:

sudo su test123 passwd root eve eve

eveuser@eve-ng:~\$ sudo su
[sudo] password for eveuser:
root@eve-ng:/home/eveuser# cd
root@eve-ng:~# sudo passwd root
New password:
Retype new password:
passwd: password updated successfully
root@eve-ng:~# _

EVE Installation Phase 2 (EVE installation)

Step 28: SSH to your EVE IP using Putty or other SSH client. Log in as root user execute:

apt update

© EVE-NG LTD Page 36 of 272



Step 29: Run EVE Pro online installation script. (it is single line command below)

wget -0 - https://www.eve-ng.net/jammy/install-eve-pro.sh | bash -i

At the end of eve server installation, reboot eve

EVE Installation Phase 3 (Management IP setup and updates)

Step 30: After reboot SSH to your EVE IP as root and Setup EVE Management IP address. A Static IP address for BM setup is preferred.

Follow steps in section: 3.5.1 for static IP, 3.5.2 for DHCP IP

apt remove netplan.io

Step 31: After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

Verification: Verify your EVE-NG server installation, type "dpkg -I eve-ng-pro" command, it must display latest EVE Pro version

Step 32: IMPORTANT After update, Step 32 is completed, continue with type:

apt install eve-ng-dockers
This can take some time depending on your Internet connection and disk speed.

Your output after install must look like:

Totleve-lag "# do !Bagger | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |

Step 33: (Optional) If after dockers first install (Step 32) in the output "dc images" you still seeing some docker name in the list as <none>,



please run the command:

apt install --reinstall eve-ng-dockers

NOTE: If you are installing EVE in the locked environment and cannot install dockers online, please contact with us: info@eveng.net for offline dockers installation option.

© EVE-NG LTD Page 37 of 272




Step 34: Continue to section 4 to obtain	
your EVE-NG Professional license	

- IMPORTANT NOTE: If your Network interfaces order has been changed, please follow instruction to section 16.6
- ▲ IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 16

3.4 Google Cloud Platform

3.4.1 Google account


Step 1: Connect to Google Cloud Platform (GCP) https://console.cloud.google.com/getting-started



- Step 2: Sign into GCP. Create a new GCP account if you do not already have one.
- Step 3: Open your Google Project which assigned to your Google account

3.4.2 Preparing Ubuntu boot disk template

Step 1: On the left side navigate to Compute Engine and press "Activate Cloud Shell"



Step 2: Create a nested Ubuntu 22.04 image. Copy and paste the below command into the shell. Use copy/paste. crtl +c/ctrl +v. **It is single line command**. Confirm with "enter":

gcloud compute images create nested-ubuntu-jammy --source-image-family=ubuntu-2204-lts --source-image-project=ubuntu-os-cloud --licenses https://www.googleapis.com/compute/v1/projects/vm-options/global/licenses/enable-vmx

Welcome to Cloud Shell! Type "help" to get started.

Your Cloud Platform project in this session is set to bamboo-storm-457508-10.

Use 'geloud config set project [ROGNET_ID]" to change to a different project.

download, eveng@cloudshell: Chamboo-storm-457508-103 [bloud compute images create nested-ubuntu-jammy --source-image-family-ubuntu-2204-11s --source-image-project-ubuntu-os-cloud --life

mence https://www.goolgenipi.com/compute/fif/project/pro

© EVE-NG LTD Page 38 of 272



You will get the following output when your image is ready:

```
Welcome to Cloud Shelll Type "help" to get started.


Tour Cloud Platform project in this sension is set to bashoo-storm-457508-10.

Use 'goloud config set project [PROJECT ID]' to change to a different project.

Use 'goloud config set project [PROJECT ID]' to change to a different project in the sension of the change to a different project in the sension of the change of the ch
```

3.4.3 Creating VM


Step 1: Navigate: Navigation Menu/Compute Engine/VM Instances and press "CREATE INSTANCE"



Step 2: Assign the name for your VM

Step 3: Set your own region and zone

Step 4: Edit your **Machine Configuration**. General-Purpose. Choose the series of CPU platform, Preferred are *Intel CPU Cascade Lake*. *Series N2 CPU*



Step 5: Choose Machine Type your desirable CPU and RAM settings.

© EVE-NG LTD Page 39 of 272



Machine type

west2-a


OS and storage

Data protection Snapshot schedules

(bookworm)

Debian GNU/Linux 12

Choose a machine type with preset amounts of vCPUs and memory that suit most workloads. Or, you can create a custom machine for your workload's particular needs. Learn more 🖸



10 GB


Free

default-schedule-1

New balanced persistent disk

Pebian GNU/Linux 12 (bookworm)

Step 7. IMPORTANT Select Custom images, select OS nested-ubuntu-jammy you created previously. Choose Boot Disk type: HDD disk type and size. HDD size can vary depends of your needs.



Туре

Size

Image

Snapshot schedule ②

Licence type ②


Change

Step 8: Edit your Data Protection, select No backups.

Page 40 of 272 © EVE-NG LTD

?






Set a custom hostname for this instance or leave it default. Choice is permanent


Step 10: Edit Security and Disable Secure Boot and vTPM

Hostname



Step 10: (Optional), Skip this step if your EVE VM will not a part of EVE-NG Cluster. Before to select MTU1500 network please follow steps how to create it 3.4.7 Select Networking/Network Interfaces.

Edit network interface and select created network: MTU1500



Step 11: Create VM.

Observability


Install Ops Agent

© EVE-NG LTD Page 41 of 272



3.4.4 EVE-NG Pro installation

Step 1: Click VM Instances to get access SSH to your VM, Connect to the VM with the first option "Open in browser window"



Step 2: Launch installation with:

Type the below command to become root:

```
sudo -i
```

Start EVE-PRO installation

wget -O - https://www.eve-ng.net/jammy/install-eve-pro.sh | bash -i

Step 3: Update and upgrade your new EVE-Pro

apt update

apt upgrade

Confirm with Y

Step 4. Reboot EVE. Allow some time for reboot and then press "Reconnect"

```
by Version of config file /etc/console-setup/compose.ISO-8859-1.inc ...

by Version of config file /etc/console-setup/compose.ISO-8859-1.inc ...


by Version of conset version
```

Step 5: IMPORTANT: Setup IP

Once the IP wizard screen appears, press ctrl + c and type the below command to become root: sudo -i

© EVE-NG LTD Page 42 of 272





Now follow the IP setup wizard. **IMPORTANT**: set IP as DHCP!

Step 6: Reboot

Step 7: Dockers installation. After EVE is rebooted, reconnect the SSH session:

Type command to become root:

sudo -i

Type command to update EVE

apt update

Type command to Install Dockers

apt install eve-ng-dockers



3.4.5 Access to Google Cloud EVE-PRO

Use your public IP for accessing EVE via https.





Default web login: admin/eve

Note: It is strongly recommended that you will change admin password on GUI! Do not delete default admin user account!

© EVE-NG LTD Page 43 of 272



3.4.6 Optional: GCP MTU 1460 Firewall rules for native console use

NOTE: If your GCP VM is using default network (MTU1460), then for native console use, you have to create following FW rules.

Open the google cloud shell and press: "Activate Cloud Shell"

Copy the following commands in SHELL Cloud console:

```
##### Create default network (MTU 1460) Firewall rules for native
console use #####

gcloud compute firewall-rules create eve-all-out --direction=EGRESS -
-priority=1000 --network=default --action=ALLOW --rules=tcp:0-65535 -
-destination-ranges=0.0.0.0/0
gcloud compute firewall-rules create eve-all-in --direction=INGRESS -
-priority=1000 --network=default --action=ALLOW --rules=tcp:0-65535 -
-destination-ranges=0.0.0.0/0
```

Firewall rules summary:

Name	Туре	Targets	Filters	Protocols/ports	Action	Priority	Network ↑	Logs
eve-all-out	Egress	Apply to all	IP	tcp:0-65535	Allow	1000	default	Off
eve-all-in	Ingress	Apply to all	IP	tcp:0-65535	Allow	1000	default	Off

3.4.7 Optional: Network MTU 1500 settings and firewall rules for GCP

If your GCP VM is expected to be as a part of EVE-NG Cluster system please complete the MTU network settings and firewall rules setup before creating the instance.

NOTE: GCP VM by default has MTU 1460 set for the interfaces by default. You may require to set VM machine custom MTU (1500) which is commonly known default setting for ethernet. The MTU settings on the GCP interface must be adjusted if you want it to use as the part of EVE-NG cluster system.

Open the google cloud shell and press: Press "Activate Cloud Shell"

Copy the following commands in SHELL Cloud console:

```
###### Create 1500 MTU subnet #####
gcloud compute networks create mtu1500 --subnet-mode=auto --mtu=1500
--bgp-routing-mode=regional

##### Create 1500 MTU firewall rules #####
gcloud compute firewall-rules create wireguard-in --direction=INGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=udp:60569 --
source-ranges=0.0.0.0/0

gcloud compute firewall-rules create wireguard-out --direction=EGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=udp:60569 --
destination-ranges=0.0.0.0/0

gcloud compute firewall-rules create ssh-in --direction=INGRESS --
priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:22 --
source-ranges=0.0.0.0/0
```

© EVE-NG LTD Page 44 of 272



gcloud compute firewall-rules create ssh-out --direction=EGRESS --priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:22 --destination-ranges=0.0.0.0/0

Firewall rules summary:

Name	Туре	Targets	Filters	Protocols/ports	Action	Priority	Network ↑	Logs
ssh-out	Egress	Apply to all	IP	tcp:22	Allow	1000	mtu1500	Off
wireguard- out	Egress	Apply to all	IP	udp:60569	Allow	1000	mtu1500	Off
ssh-in	Ingress	Apply to all	IP	tcp:22	Allow	1000	mtu1500	Off
wireguard- in	Ingress	Apply to all	IP	udp:60569	Allow	1000	mtu1500	Off

3.4.8 Optional: GCP MTU 1500 Firewall rules for native console use

Open the google cloud shell and press: Press "Activate Cloud Shell""

Copy the following commands in SHELL Cloud console:

```
###### Create MTU 1500 firewall rules for native console use #####
gcloud compute firewall-rules create allow-all-in --direction=INGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:0-65535
--source-ranges=0.0.0.0/0
gcloud compute firewall-rules create allow-all-out --direction=EGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:0-65535
--destination-ranges=0.0.0.0/0
```

Summary FW rules.

Name	Туре	Targets	Filters	Protocols/ports	Action	Priority	Network ↑	Logs
allow-all- out	Egress	Apply to all	IP	tcp:0-65535	Allow	1000	mtu1500	Off
allow-all- in	Ingress	Apply to all	IP	tcp:0-65535	Allow	1000	mtu1500	Off

3.5 EVE Management IP Address setup

▲ NOTE: Please make sure if these subnets are NOT used in your network outside of EVE.

172.29.129.0/24 (NAT Interface) 172.29.130.0/24 (Cluster VPN subnet, wg0 interface) 172.17.0.0/16 (Dockers consoles)

1 To change these networks please refer chapter 7.4.1

© EVE-NG LTD Page 45 of 272




3.5.1 Static Management IP address setup (preferred)

IMPORTANT NOTE: Internet and DNS must be reachable from your Server. The EVE-NG Pro requires internet access to get updates and validate EVE-NG Pro License key. DNS must resolve names!


The steps below will walk you through the network setup and assign a static management IP for EVE.

Step 1: Log into the EVE CLI using the default login **root/eve** After login, type your preferred root password for EVE, default is **eve. Remember it for further use.** Confirm with enter


NOTE: Typed characters in the password field are not visible.



Step 2: Retype your root password again and confirm with enter.



Step 3: Choose your EVE VMs hostname. By default, it is **eve-ng**. You can leave it as it is. Confirm with enter



Step 4: Type your domain name for your EVE VM. By default, it is example.com. The default value can be used as well.




© EVE-NG LTD Page 46 of 272




Step 5: Using the arrow keys, select the option "static", confirm your selection with the space key, followed by enter




Step 6: Type your desirable EVE management IP. Confirm with enter.



Step 7: Type the subnet mask of your EVE management network. Confirm with enter.




Step 8: Type your networks gateway IP. Confirm with enter.




Step 9: Type your networks primary DNS IP. Confirm with enter.

IMPORTANT: DNS must be reachable and resolve public addresses.



Step 10: Type your network Secondary DNS IP. Confirm with Enter.


IMPORTANT: DNS must be reachable and resolve public addresses.



© EVE-NG LTD Page 47 of 272



Step 11: Type your preferred NTP server IP. It can be left empty as well; in this case, your EVE VM will automatically assign the time from its host.



Step 12: **Skip this step.** By default, it is set to direct connection (no proxy).

Confirm selection with enter. EVE will reboot automatically.

NOTE: If required, the Proxy settings can be configured later using EVE WEB GUI System/System Settings described in section 3.5.3



3.5.2 DHCP Management IP address setup

⚠ IMPORTANT NOTE: Internet and DNS must be reachable from your Server. The EVE-NG Pro requires internet access to get updates and validate EVE-NG Pro License key. DNS must resolve names!


⚠ IMPORTANT NOTE: EVE Docker stations for html console access are using network 172.17.0.0/16. Please avoid use this network on the EVE management or other clouds or interfaces.

The steps below will walk you through the network setup and assign a management IP for EVE via DHCP.

Step 1: Log into the EVE CLI using the default login **root/eve** After login, type your preferred root password for EVE, default is **eve. Remember it for further use.** Confirm with enter


NOTE: Typed characters in the password field are not visible.

Step 2: Retype your root password again and confirm with enter.




© EVE-NG LTD Page 48 of 272







Step 3: Choose your EVE VMs hostname. By default, it is **eve-ng**. You can leave it as it is. Confirm with enter




Step 4: Type your domain name for your EVE VM. By default, it is example.com. The default value can be used as well. Confirm with enter



Step 5: Using the arrow keys, select the option "dhcp", confirm your selection with the space key, followed by enter




Step 6: Type your preferred NTP server IP. It can be left empty as well; in this case, your EVE VM will automatically assign the time from its host.



© EVE-NG LTD Page 49 of 272






3.5.3 Internet proxy setup

Step 1: If you have a proxy in use for your Internet, login into your EVE WEB GUI using your EVE IP https://aaa.aaa.aaa.aaa

Default username: admin

Password: eve


Step 2: Select Tab: System/System Settings



Step 3: Enter your Proxy IP and Port following by "Apply". For authenticated Proxy, use your username and password.

© EVE-NG LTD Page 50 of 272





3.5.4 Reset Management IP settings

If for any reason you need to change these settings after the installation, you can rerun the IP setup wizard. Type the following command in the CLI and hit enter:

rm -f /opt/ovf/.configured

Then type:


su -

Once you log into the CLI again, EVE will go through the network setup again. Please follow the steps in section 3.5.1 for Static IP or 3.5.2 for DHCP IP.

3.6 Native telnet console management setup


If you prefer to use a natively installed telnet client to manage nodes inside EVE, follow the steps below:

3.6.1 Windows Native Console



© EVE-NG LTD Page 51 of 272





By default, EVE Windows Client Integration will install **Putty** as your Telnet Client. The default location for the EVE Windows Client Integration software and .reg files is: "C:\Program Files\EVE-NG"

Set the default telnet program manually in Windows 10. Example: Secure CRT


Step 1: Go to: Windows Settings/Apps/Default Apps/Choose Default Apps by Protocol

Step 2: Set your default Telnet program:



NOTE: The first time click on the type of link that is used to access a running node inside EVE via telnet, the browser will ask to choose the telnet program. If you have prepared your default telnet program with the instructions above, you have to choose your default Telnet program.

Example: Firefox browser:



© EVE-NG LTD Page 52 of 272



Set your default application, check the box "Remember my choice telnet links" and click Open link

3.6.2 Linux Native Console

The steps below will show how to setup the native consoles pack for Linux Mint 18 (Ubuntu):

Step 1: Go to the EVE Linux Side integration pack download page: http://www.eve-ng.net/downloads/linux-client-side	Step 2: Open the link to GitHub https://github.com/SmartFinn/eve-ng- integration
Step 3: Scroll down to the installation part Installation Ubuntu and derivatives You can install eve-ng-integration from the official PPA: sudo add-apt-repository ppa:smartfinn/eve-ng-integration sudo apt-get update sudo apt-get install eve-ng-integration	
Step 4: Login as root to your Linux system an NOTE: An internet connection is required. E other sudo add-apt-repository ppa:smartfinn/eve-	nter each command line below one after the

▲ For other Linux native console setup options please refer to: https://github.com/SmartFinn/eve-ng-integration

3.6.3 MAC OSX Native Console

sudo apt-get install eve-ng-integration

Download the EVE MAC OSX Client integration pack and install it:

https://www.eve-ng.net/index.php/download/#DL-OSX

3.7 Login to the EVE WEB GUI

EVE PRO is using https 443. Login to the EVE management UI:

https://<your_eve_ip>/

sudo apt-get update

Default user access: User: admin Password: eve

NOTE: You can change your EVE Admin password, please refer to section 7.3.1.2

▲ IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 17

© EVE-NG LTD Page 53 of 272




4 EVE-NG Professional Licensing

⚠ IMPORTANT NOTE: Internet and DNS must be reachable from your Server. The EVE-NG Pro requires internet access to get updates and validate EVE-NG Pro License key. DNS must resolve names!

EVE-NG Professional and Learning Centre editions require purchasing and uploading a license to activate its features. Licenses are based on an annual subscription.

EVE-NG permits up to **32000 accounts** to be created but restricts the number of simultaneous sessions per role to the licensed amount. To increase the number of active sessions, please purchase additional licenses on top of the base license as shown below.

Definition: Simultaneous session (1 license) means one active connection to the EVE-NG Web GUI.



Example 1 EVE-Professional: The license information page shows 2 Admin accounts. This means 2 Admin users' role-based accounts (2) can be logged into the Web GUI simultaneously. EVE-NG PRO can have up to 32K accounts, but active sessions to the Web GUI are restricted to the number of purchased licenses.

Example 2 EVE Learning Centre: The license information page shows 2 Admin, 3 Editor and 3 Lab user role accounts. This means 2 Admin, 3 Editor and 3 User accounts can be logged into the Web GUI simultaneously. EVE-NG Learning Center can have up to 32K accounts, but active sessions to the Web GUI are restricted by the number of licenses purchased.

4.1 EVE-NG Professional Base license


EVE-NG Professional Edition - 1 Year License https://www.eve-ng.net/index.php/buy/

EVE-NG PRO features multi user support and assigns all accounts as Administrators. The license allows for 2 simultaneous users.

Close

© EVE-NG LTD Page 54 of 272






For EVE-PRO Administrator role permissions, please see section 4.4.

4.2 EVE-NG Learning Centre licenses

EVE-NG Learning Centre Edition - 1 Year License https://www.eve-ng.net/index.php/buy-corporate/

EVE-NG LC features multi user support and assigns accounts as Administrators, Lab-Editors or Lab-Users.

The first minimal Base A license allows for 2 simultaneous Admin users. It is necessary to use an Administrator account to create or manage EVE LC and other user's role-based accounts.



© EVE-NG LTD Page 55 of 272



EVE-NG PRO – A Base License (Mandatory)

This license unlocks all Pro features and two active Administrator accounts sessions. This license is mandatory for EVE LC edition.

The following licenses below can vary per your needs.

EVE-NG PRO - Administrator License

This license unlocks one additional active session for the Administrator role. The Administrator role can manage everything in EVE-NG without restrictions. This includes creating, deleting, and modifying all folders, labs, nodes and accounts. The Administrator is the only role that can create or modify accounts.

EVE-NG PRO - Lab-Editor License

This license unlocks one additional active session for the Lab-Editor role.

The Lab-Editor role is restricted to a personal and the Shared folder and is authorized to create, delete, or modify additional folders, labs, and nodes within them.

EVE-NG PRO - Lab-User License

This license unlocks one additional active session for the Lab-User role.


The Lab-User role is restricted to a personal and the Shared folder and is only authorized to start, stop, and wipe nodes. An Administrator account is required to manage folders and labs within a User's personal folder.

Example: EVE Learning Centre Licensing for 1 Teacher and a 5 Students class. Licence model below includes:

- Two administrator accounts, necessary for EVE LC labs and other user account management
- One Lab-Editor-role based account, assigned to the teacher to create/manage labs and assign them to the Shared folder for Students use. The Lab-Editor role is restricted to a personal folder and is authorized to create, delete, or modify additional folders, labs, and nodes within it.
 - Optional: If wanted / needed, the Lab-Editor account for the teacher can also be replaced by an Administrator account instead.
- Five Lab-User role-based Student accounts allowing running a class with 5 simultaneous students connected to the EVE HTML GUI.

© EVE-NG LTD Page 56 of 272





For EVE-LC role permissions, please see section 4.4.

4.3 EVE-NG Corporate licenses

Essentially, this is EVE Learning Centre edition with Lab-Editor role-based accounts only. This is recommended for corporate use to allow full permissions for EVE labs but to restrict being able to manage other user accounts or labs. The Lab-Editor role is restricted to a shared and a personal folder and has permissions to create, delete, or modify additional folders, labs, and nodes within them.


EVE-NG Learning Centre Edition - 1 Year License https://www.eve-ng.net/index.php/buy-corporate/

EVE-NG Corporate features multi user support and assigns accounts as Administrators or Lab-Editors.

The first (mandatory) Base A license allows for 2 simultaneous Admin users. It is necessary to have an Administrator account to create or manage EVE LC and other user's role-based accounts.

Example: EVE Corporate Licensing for 5 Lab-Editor users. License model below includes:

- Two administrator accounts necessary for EVE Corporate labs and other user accounts management (Mandatory Base license)
- Five Lab-Editor role-based accounts. The Lab-Editor role is restricted to a shared and a personal folder and has permissions to create, delete, or modify additional folders, labs, and nodes within them.



© EVE-NG LTD Page 57 of 272



EVE Corporate role rights, please follow section **4.4**.

4.4 User roles comparison chart

Feature	Administrator Role	Lab-Editor/Teacher role	Lab-User/Student role
User accounts management	yes	no	no
User Accounts visibility	yes	no	no
User edit modal visibility	yes	no	no
User Folder's management	yes	no	no
Full EVE root folder tree	763	110	
access	yes	no	no
Licencing module access	yes	no	no
Nodes management module		yes (only own running	yes (only own running
access	yes	nodes)	nodes)
Lab management module access	VOC	yes (only own running nodes)	yes (only own running nodes)
Shared lab folder	yes	noues)	nodesj
management	yes	yes	no
Shared folder access	yes	yes	yes
Shared project	yes	yes	no
Rename Folders	yes	yes	no
Create labs	yes	yes	no
Delete labs	yes	yes	no
Edit Custom topology	yes	yes	110
mapping	yes	yes	no
Use only Custom topology			
mapping	yes	yes	yes
Lab objects management add text, drawing on labs	VOC	VOS	no
	yes	yes	
Export/import labs	yes	yes	no
Nodes list management	yes	yes	yes, read-only
Networks management	yes	yes	yes, read-only
Start labs	yes	yes	yes
Stop labs	yes	yes	yes
Search labs	yes	yes	yes
Wipe nodes	yes	yes	yes
Console to all nodes	yes	yes	yes
Export all configs	yes	yes	no
Edit lab	yes	yes	no
Set nodes startup-cfg to default configset	yes	yes	no
Set nodes startup-cfg to none	yes	yes	no
Topology refresh	yes	yes	yes
Topology zoom	yes	yes	yes
EVE status	yes	yes	yes
Lab details UUID	yes	yes	yes
See startup configs	yes	yes	no
Delete default startup configs	yes	yes	no

© EVE-NG LTD Page 58 of 272



Create and manage multiconfig sets	yes	yes	no
Close labs	yes	yes	yes
Lock labs	yes	yes	no
System/Stop all nodes	yes	no	no
Information tab access	yes	yes	yes
Work with more than one lab	yes	yes	yes
Lab timer function	yes	yes	no
Lab background dark mode	yes	yes	yes
Hide node labels	yes	yes	yes
EVE Cluster administration	yes	no	no
EVE Cluster servers'			
assignment per user	yes	no	no


4.5 License purchasing and activation

IMPORTANT NOTE: Internet and DNS must be reachable from your Server. The EVE-NG Pro requires internet access to get updates and validate EVE-NG Pro License key. DNS must resolve names!

- ⚠ Before purchasing a license, the customer must have **EVE-NG Professional** installed and readily accessible.
- Recommended browser for license operations are: Chrome or Mozilla Firefox
 You must be logged in to the EVE WEB GUI as Administrator.

Step 1: Obtain your license request from the Licensing tab of the top menu of the EVE PRO WEB GUI. License requests will work only if the host machine (and hypervisor if running a VM) has **Intel VT-x/EPT** enabled! (See section 3 for details)

Step 2: Copy the content of the license request and keep it ready for the order process at later **Step 6**. Orders without a license request cannot be processed.



© EVE-NG LTD Page 59 of 272



Step 3: Go to the EVE PRO or Learning Centre Purchase Portal and choose your Licenses and quantity.

Licenses that are unnecessary for your EVE Learning Centre or Corporate Edition licensing needs, can simply be deleted from your order by clicking on the cross next to them to remove them. Refer to sections: 4.2 and 4.3

EVE-PRO Purchase Portal

EVE-Learning Centre or Corporate Purchase Portal

Step 4: Choose your preferred payment method. We currently support VISA, Mastercard, Bank/Wire transfer and PayPal.



Step 5: Complete the order form. If your license is for commercial/company use, you must select Company option.

Billing Information			
	Licensed to:	Person Company	
	First name*:		
	Last name*:		
	Address*:		

Step 6: At the end please paste your **license request content (including header and footer lines)** from Step 2 and **Please read** and confirm the <u>EULA agreement</u>, which contains vital information about licenses. For companies, if necessary, in the Order Notes you can add additional information/reference, e.g. for your accounting department.

Additional Information			
Order Notes			
Order Notes			
EVE-NG PRO A Base license			
License Request*			
LICENSE FILE DATA	4		
Accept EULA*		_	

Step 7: After a while (usually 10-30 mins), your license is sent to the E-Mail used in the order form.

- ▲ IMPORTANT: Before loading the purchased license, make sure your EVE has Internet access. Your EVE DNS settings must be configured properly to resolve the FQDN. Internet connection is required to validate your EVE license with our EVE-NG license server.
- ▲ IMPORTANT: If your EVE internet is using Proxy, make sure you have set the proxy settings described in section 3.5.3
- ⚠ Offline EVE Pro license is supported for Bare EVE installs only. (Dedicated EVE server). VM Ware and Cloud environment EVE installs require Internet connection.


Step 8: Copy ALL Content of your received License. Important: License key mut include header and bottom lines as well.

© EVE-NG LTD Page 60 of 272






Step 9: On your EVE WEB GUI, click on License Upload,



Paste your licence and click on Upload



4.6 License deactivation

If you decide to deactivate EVE-PRO license on the host, please follow the steps below:

Go to EVE CLI and type:

```
cd /opt/unetlab/html/
rm eve-ng.lic
cp eve-ng.nolic eve-ng.lic
```

© EVE-NG LTD Page 61 of 272



4.7 License Rehosting.

If you decide to re-install EVE-PRO or move it to another host, please follow the steps below:

Pre-requisites:

- EVE must have internet access!
- Only ONE EVE host must be turned ON and connected to the internet, do NOT have more than one EVE with the same license turned on at the same time!
- Step 1. Make sure that you have only ONE EVE-PRO instance with this license running.
- Step 2. Make sure you have unrestricted Internet access with a properly configured DNS server from your EVE server.
- Step 3. Load your purchased license onto EVE server you want to rehost to.
- Step 4. Reboot your new EVE
- Step 5. Wait approximately one hour for the licence validation process to finish on the host.
 - NOTE: The re-hosted EVE server must have internet access to periodically validate the license. EVE receives a token with a licence validity time of 24 hours. During those 24 hours, the re-hosted EVE can be used offline. After 24 hours the token time expires and you have to get EVE online again (for approximately 30 minutes) to receive a new token.

© EVE-NG LTD Page 62 of 272



5 EVE-NG Professional Update & Upgrade

▲ Prerequisites: Internet access and working DNS on your EVE-NG is required.

Verify your internet reachability with named ping. Example: ping www.google.com

```
ping www.google.com

root@eve-ng:~# ping www.google.com


PING www.google.com (216.58.207.228) 56(84) bytes of data.
64 bytes from arn09s19-in-f4.1e100.net (216.58.207.228): icmp_seq=1 ttl=58 time=9.11 ms
64 bytes from arn09s19-in-f4.1e100.net (216.58.207.228): icmp_seq=2 ttl=58 time=19.5 ms
64 bytes from arn09s19-in-f4.1e100.net (216.58.207.228): icmp_seq=3 ttl=58 time=9.50 ms
64 bytes from arn09s19-in-f4.1e100.net (216.58.207.228): icmp_seq=4 ttl=58 time=9.56 ms
64 bytes from arn09s19-in-f4.1e100.net (216.58.207.228): icmp_seq=4 ttl=58 time=9.56 ms
```

If your ping is success, follow next step for update. If named ping has no success, please verify your DNS IP assigned for EVE or firewall. Some cases ping can be blocked by FW, but Internet and DNS are capable to make update/upgrade.

5.1 EVE-NG Professional Update

It is strongly recommended to keep your EVE-NG up to date. To update and upgrade, SSH to your EVE CLI.

To verify your current EVE-NG version, please follow "CLI diagnostic information display commands" in section 15.1.1. You can verify your current EVE version from the System/System Status tab on the top menu of the WEB GUI as well.



The newest version of EVE-NG can be verified by checking the official website: http://www.eve-ng.net. For update to the newest EVE-NG Professional version please follow the steps https://www.eve-ng.net/index.php/1845-2/

Type the below commands followed by Enter

apt update

In case the prompt asks to confirm with Y/N, answer Yes.

© EVE-NG LTD Page 63 of 272



5.2 EVE-NG Professional Upgrade

▲ IMPORTANT NOTE: Make sure you have stopped all your running labs. All nodes in the EVE must be stopped before upgrade!

For upgrade to the newest EVE-NG Professional version please follow the steps https://www.eve-ng.net/index.php/1845-2/


Type commands followed by Enter

```
apt upgrade
```

In case the prompt asks to confirm with Y/N, answer Yes.

▲ IMPORTANT NOTE: If you are upgrading EVE PRO from older version, the installation may ask you to confirm additional! Information:

Answer for prompt above is "N"



Answer for grub-pc version is: "Keep the local version currently installed"

After the completion of the update and upgrade, reboot your EVE Server. Type the following command and hit enter.

reboot

▲ IMPORTANT NOTE: Do NOT make EVE updates or upgrades from within the HTML5 Desktop console!

© EVE-NG LTD Page 64 of 272



6 Types of EVE management consoles

⚠ IMPORTANT NOTE: EVE Console TCP ports. EVE Pro uses a dynamic port range between 1-65000. Dynamic means that every time you start a node on the lab, EVE assigns any free port from this range for Telnet, VNC or RDP access. Static TCP port assignment for Telnet sessions is not available in EVE PRO.

EVE Pro supports three different console types.

6.1 Native console




EVE Native console option requires locally installed software to access your lab nodes. To use the Native console option, you must have Administrator rights on your PC and ensure the TCP port range 1-65000 is not blocked by a firewall or antivirus software.

6.1.1 Native Console: telnet

Windows OS: You can use your preferred telnet program like Putty, SecureCRT or others. Example: Putty as native telnet client on Windows.

To setup Windows native telnet client please follow section 3.6.1



Linux OS: You can use your preferred telnet program like the Native Terminal, SecureCRT, or others.

Example: Telnet client from the native terminal on Linux Mint. To setup Linux native telnet client please follow section 3.6.2



© EVE-NG LTD Page 65 of 272



MAC OSX: You can use your preferred telnet program like the native Terminal, SecureCRT, or others.

Example: Telnet client from the native terminal on MAC OSX. To setup MAC OSX native telnet client please follow section 3.6.3


6.1.2 Native Console: Wireshark

EVE Professional has an integrated Wireshark Docker station. This allows live captures without having Wireshark installed on the client machine. The EVE Capture console uses an integrated HTML session.

Right click on the node you wish to capture, choose capture and the interface. Capture Session will open in a new browser window.

EVE-PRO supports packet captures on ethernet and serial interfaces. Select the interface frame type which will be captured:


- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames (IOL Only): HDLC, PPP or Frame Relay.



Integrated HTML RDP for Wireshark capture

© EVE-NG LTD Page 66 of 272





Example: ISR live interface E0/1 capture.

To save the captured file on your local PC, please refer to section 11.1

6.1.3 Native Console: VNC

Windows OS: Recommended and tested is UltraVNC but any other compatible one can be used.


Example: UltraVNC as Native VNC client on Windows. To setup Windows native VNC client please follow section 3.6.1

Linux OS: Remote Desktop Viewer for VNC Sessions.

Example: Remote Desktop Viewer for VNC sessions on Linux Mint. To setup Linux native Remote Desktop Viewer please follow section 3.6.2

MAC OSX: Preferred VNC program: Chicken VNC

Example: Chicken VNC as Native VNC client on MAC OSX. To setup MAC OSX native RDP Viewer client please follow section 3.6.3



Example: Windows Ultra VNC consoles, Linux and Windows


© EVE-NG LTD Page 67 of 272



6.1.4 Native Console: RDP

Windows OS: Windows Native RDP.

Example: Windows RDP session to Win11 host in the lab.



Linux OS: Remote Desktop Viewer as RDP session to lab Win11 host. Example: RDP session to Win11 host in the lab. To setup Linux native Remote Desktop Viewer please follow section 3.6.2



MAC OSX: Remote Desktop Viewer as RDP session to lab Win10 host. Example: RDP session to Win10 host in the lab.

To setup MAC OSX native RDP Viewer client please follow section 3.6.3

© EVE-NG LTD Page 68 of 272




6.2 HTML5 console



The EVE PRO HTML5 console provides a clientless solution for managing labs and node sessions. Management is achieved directly through the browser by using the Apache Guacamole HTML5 Engine. It is very convenient for Corporate users with restricted Workstation permissions (Locked Telnet, vnc, rdp).

6.2.1 HTML5 Console window functions



6.2.2 HTML5 Console: Telnet


HTML5 Telnet console is integrated and opens telnet sessions in the browser.

© EVE-NG LTD Page 69 of 272






Option: The new Chrome v70.0.3538.110 and higher allows the use of the copy/paste function inside the HTML session. Type in your Chrome browser "**chrome://settings/content/clipboard**" and press **Add** to allow the use of the clipboard extension for your EVE Server: **https://your_ip:443**



Option: The new Firefox v 63.0.3 and higher allows the use of the copy/paste function inside the HTML session. Type in your Firefox browser "**about:config**" and enable clipboard values below:



6.2.3 HTML5 Console: Wireshark


Right click on the node you wish to capture, choose capture and the interface. Capture Session will open in a new browser window.


EVE-PRO supports packet captures on ethernet and serial interfaces. Select the interface frame type which will be captured:

© EVE-NG LTD Page 70 of 272



- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames (IOL Only): HDLC, PPP or Frame Relay.






To save captured file to your local PC, please refer section 11.2

6.2.4 HTML5 Console: VNC

HTML5 VNC console is integrated and opens VNC sessions in the browser.

© EVE-NG LTD Page 71 of 272





6.2.5 HTML5 Console: RDP

HTML5 RDP console is integrated and opens RDP sessions in the browser. For Windows 7, 8, 10, Windows Server 2012, 2016 please mind the note below.




IMPORTANT NOTE: For all Windows nodes, the console type must be set to RDP-TLS in the node template. RDP-TLS node console option is actually only used with HTML5 RDP sessions.

The username and the password can be configured in the node edit settings. This will allow you resize HTML RDP console without re-login in the windows host.

© EVE-NG LTD Page 72 of 272



Example below, Edit node, Win10, Console type rdp-tls, username: user and password: Test123



© EVE-NG LTD Page 73 of 272




6.3 HTML5 Desktop console



EVE PRO HTML5 Desktop provides a full-featured clientless solution for managing labs and node sessions. Management is achieved directly through the browser by using an integrated docker desktop that is accessed through the Apache Guacamole HTML5 Engine. The docker contains a full featured Linux desktop and is very convenient for corporate users with restricted workstation rights (locked telnet, vnc, rdp).

6.3.1 Login to HTML5 Desktop console

Step 1: On your first login to the EVE HTML5-Desktop console, EVE will open a new HTML window session to an integrated Docker management station. On the Desktop you will see another EVE login icon.



Step 2: Double-click the "Link to EVE | Login" icon and log into EVE using NATIVE console.




Inside of the integrated docker station, it will open another session to EVE. All features inside of the Docker Desktop will work as you are used to with the Native console.

© EVE-NG LTD Page 74 of 272



6.3.2 HTML5 Desktop Console: telnet

The integrated management docker station telnet client allows you to telnet to nodes. Telnet sessions are in a tabbed style as shown below.




6.3.3 HTML5 Desktop Console: Wireshark

Right click on the node you wish to capture, choose capture and select the relevant interface. The capture will open in an RDP session window.

EVE-PRO supports packet captures on ethernet and serial interfaces. Select the interface frame type which will be captured:


- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames: HDLC, PPP or Frame Relay.



The integrated management docker station Wireshark client allows you to capture and save captured files onto the docker station. For instructions on how to save files to your local PC, please refer to section 11.3


© EVE-NG LTD Page 75 of 272





6.3.4 HTML5 Desktop Console: RDP

The integrated management docker station RDP client allows you to open Remote Desktop sessions to Windows nodes. For directions on how to transfer files to the local PC, please refer to section 12



6.3.5 HTML5 Desktop Console: ThinClient Files exchange

The HTML5-Desktop console offers an amazing feature that allows you to exchange files between your host PC and the EVE management Linux host. Please refer to section 12 for detailed instructions.


© EVE-NG LTD Page 76 of 272



7 EVE WEB GUI Management

7.1 EVE Management Page

The Main EVE management window



The lab preview actual picture appears after 3-5 seconds.


7.1.1 Management buttons



Button	Description
	Select All or Deselect All folders or labs in the EVE tree
& +	Create/Add new Lab
	Create new folder
	Import an EVE lab or lab folder from a previous export. Import file must be in .zip format
M	Export EVE lab or folder. Select folder(s) and/or labs you wish to export and select this option. The export is saved to your local PC in .zip format and is ready to import to another EVE.
î	Delete selected folders or labs. You cannot delete the Shared, Users or Running folder.

© EVE-NG LTD Page 77 of 272





7.1.2 Right click dropdown menu




Function	Description
	Opens Folder or Lab.
•	Rename Folder or Lab.
A	Move selected item(s) to a different location. To use this option, please select the folder(s) or lab(s) that you want to move.
	Clone Lab. Clone function creates a copy of lab topology and exported configurations.
î	Delete selected folders or labs. You cannot delete the Shared, Users or Running folder.

© EVE-NG LTD Page 78 of 272



7.1.3 Management tabs



7.2 Folders and Lab files management

This section will explain how to manage folders and labs on the EVE management page.

© EVE-NG LTD Page 79 of 272



7.2.1 Folders Management

EVE Professional has three default folders used for various operations. These cannot be deleted or renamed (see below).



- Admins can create additional folders for any user.
- Editors can create or manage folders in their own profile/folder or within the Shared folder

7.2.1.1 Default folder Running

EVE professional allows a single user to run multiple labs and switch between them with the Running folder.




Example:

- Start a lab and close it
- · Open and start another lab and close it

When you open your Running folder, you will see both running labs in it. It is easy to switch between labs.

The example below is showing two running labs in the Running folder.



7.2.1.2 Default folder Shared

To manage the Shared folder an Admin or Editor user account is required.

The EVE Professional Shared folder is visible to all EVE users. Admin and Editor Accounts can create folders or labs and place them into the Shared folder.



Example: An Admin creates a lab and places it into the Shared folder.


© EVE-NG LTD Page 80 of 272




The Shared Lab is recommended to set "any" Cluster Satellite

Step 1: Create a lab, refer to section 8.1

Step 2: Select the lab or folder you wish to move to the Shared folder and press **Move** (or create it in the Shared folder from the start).



Step 3: Another user account can use the lab placed by the Admin in the Shared folder




- NOTE: Every user has its own profile; this means that every user has an independent Running folder where this lab runs independently from other users.
- NOTE: Labs can be created and modified (e.g. settings and preconfigs) by an Admin or an Editor user. The User role can use the lab only exactly the way it was configured by an Admin or Editor and is unable to change any settings.
- ▲ NOTE: Admins and Editors can create folders and labs inside the Shared directory

7.2.1.3 Default folder Users

To manage the Users folder, an Admin user account is required.

The Users directory is a default EVE folder where Editors and Users have their personal folders stored.




Once an Admin has created a new Editor or User account, EVE will automatically create a folder with the user login name under the default directory Users.

Example: Below you can see the folders for the users with the following login names: **test2**, **test3** and **test4**

© EVE-NG LTD Page 81 of 272






▲ NOTE: An Admin can manage any user's folder or place labs in it.

7.2.1.4 Create folder

An Admin or Editor user account is required.

Click to add new Folder, Type the new folder name and click "Create"




NOTE: Editors can only create folders within their own profile folder or in the Shared folder

7.2.1.5 Delete folder

An Admin or Editor user account is required.

Select or right click to the folder you wish to delete and press Delete.




NOTE: All folder content will be deleted as well.

▲ NOTE: Editors can only manage their own or the Shared folder

© EVE-NG LTD Page 82 of 272



7.2.1.6 Move Folder




An Admin or Editor user account is required.

Select or right click the folder you wish to move and press the Move.


▲ NOTE: Editors can only manage their own or the Shared folder

Select the target destination for your folder and confirm by clicking on Move.




7.2.1.7 Export Folder

Select the folder(s) you wish to export from your EVE and press Export.



Save the exported file as .zip to your local PC. The exported zip file is ready to import to another EVE instance.



If your browser is set to save downloaded files to a default directory, your exported file will be saved in the browsers default downloads directory.


© EVE-NG LTD Page 83 of 272



7.2.1.8 Import Folder

IMPORTANT: Importable file MUST be in .zip format, do NOT unzip the file.

Step 1: Press the Import button.




Step 2: Click Select ZIP File, find the zipped file that contains EVE folder with labs.

Step 3: Press the Import Button

7.2.2 Lab files Management

You can manage created labs from the main EVE file manager window




7.2.2.1 Create Lab

The Admin or Editor user account is required.

NOTE: An Editor can create labs only within his personal folder or in the Shared folder

Click on the New Lab button and refer to section 8.1



© EVE-NG LTD Page 84 of 272




7.2.2.2 Delete Lab

The Admin or Editor user account is required to delete labs.

A NOTE: An Editor can delete labs only within his personal folder or in the Shared folder

Step 1: Select the lab or labs you wish to delete and then press the Delete button



7.2.2.3 Clone Lab


The Admin or Editor user account is required to clone labs.

▲ NOTE: An Editor can create labs only within his personal folder or in the Shared folder

The cloning feature provides a very convenient way to duplicate original labs to share with others or base another lab on it.

Cloned labs will copy exported configs (on supported nodes) but will not copy saved states/configurations in Qemu nodes like Windows hosts, Cisco ISE, or other Qemu nodes. Please refer to section 10.3 for more information on configuration export for labs.

Step 1: Right click on the lab you wish to clone. Click on Clone.




Step 2: Your lab will be cloned with all your exported configurations or configuration sets with a new name.




Step 3: The lab has been cloned lab and can be renamed to your liking. Right click to the cloned lab and choose Rename.

© EVE-NG LTD Page 85 of 272





Step 4: Rename it, and click Rename to confirm



7.2.2.4 Move Lab


The Admin or Editor user account is required to move labs.

▲ NOTE: An Editor can create labs only within his personal folder or in the Shared folder

Step 1: Select the lab you wish to Move and click move.



Step 2: Choose the path to the new destination and confirm by clicking Move



7.2.2.5 Export Lab


Select the Lab(s) you wish to export from your EVE Server and press Export.



© EVE-NG LTD Page 86 of 272



Save exported file as .zip to your local PC. The exported zip file is ready to import into another EVE.




If your browser is set to save downloaded files to default directory, your exported file will be saved in the browsers default downloads directory.


7.2.2.6 Import Labs

▲ IMPORTANT: Importable file MUST be in .zip format, do NOT unzip the file.

Step 1: Press the Import button.




Step 2: Select the zipped file which contains the EVE labs.



Step 3: Press the Import Button

7.3 EVE Management Dropdown Menu

7.3.1 EVE User management



The User Management page, under the Management dropdown, will allow Admin accounts to manage other user accounts.


© EVE-NG LTD Page 87 of 272




▲ Only the Admin role is allowed to create or edit user accounts.

7.3.1.1 Creating a new EVE User

Step 1: Open the User management submenu. Management>User management and click Add user



Step 2: The Add New User management window will pop up. Fill in the main information about your EVE user



Step 3: If your user will be Radius authenticated, please Select Radius from Authentication menu. Passwords will be stripped off, because authenticator will look Radius server for user password. How to setup radius server IP and Shared secret please follow Section:16.1




Step 4: If your user will be Active Directory (LDAP) authenticated, please enable Active Directory from Authentication Menu. Passwords will be stripped off, because authenticator will look Active Directory server for user password. How to Active Directory server IP please follow

© EVE-NG LTD Page 88 of 272




NOTE: Username for Active Director must contain domain at the end of username. Example: test4@eve-ng.net




Step 5: If you have bought other EVE licenses, you can choose the preferred user role. For licensing and user roles please refer to section 4



Step 6: Set the Console type for the user. If Console type is set exact: Native, HTML or HTM5 Desktop, user after login in the EVE will be forced to use selected Console Type. If Console Type is set to "any", user is able to choose Console type on Login page which Console will be used.



Step 7: Assigned single Lab. Applies for User role only. Set the specific Lab for the user "assigned/sticky lab". After login in the EVE User will directed only to this lab. He cannot close the lab to get in main Lab management page. User can Start/Stop/Wipe lab, as well save his lab work on the lab devices. Follow Section: 7.3.1.5



© EVE-NG LTD Page 89 of 272



Step 8: Satellites assignment per user (Editor or User) require Administrator account



The User Cluster Server value "any" is set by default.

Set the Cluster Satellites for the Lab Editor. This applies for Lab Editor roles. Lab Editor will stick to selected Satellites. Lab Editor will be forced and allowed to use only selected Satellite server or choose between the Satellite servers if it is assigned more than one server. If the Lab has set to use any satellite server, then Lab Editor will be assigned to use lowest satellite ID.

Example: If Lab Editor has assigned to use SAT1 (ID1) and SAT2 (ID2). The Lab has set to use "any" satellite. This Editor lab will be automatically assigned to use first available Satellite with lowest ID1, SAT1.

Editor has rights to change Satellite per node for own created Labs.

Editor cannot change satellite assignments for Shared Lab. The Shared Lab is recommended to set "any" Cluster Satellite,

If the Lab is created on the Satellite servers which are NOT in the Lab Editor allowed Satellites list, this lab will not start.

Example: If Lab is created to use Master server only, but Lab Editor is allowed to use only SAT1 Server. Lab Editor will not be allowed to start this Lab.

If the Lab contains nodes which are assigned to run on the Satellite server which is NOT in Lab Editor allowed Satellites list, this node will not start.

Example: If Lab several nodes are assigned to use Master server only, but Lab Editor is allowed to use only SAT1 Server. Lab Editor will not be allowed to start these nodes.

Set the Cluster Satellites for the Lab User. This applies for Lab User roles. Lab User will stick to selected Satellites. Lab User will be forced and allowed to use only selected Satellite server or servers.

Example: If Lab User has assigned to use SAT1 (ID1) and SAT2 (ID2). The Lab has set to use "any" satellite. This Lab User lab will be automatically assigned to use first available Satellite with lowest ID1, SAT1.

If the Lab is created on the Satellite servers which are NOT in the Lab User allowed Satellites list, this lab will not start.

Example: Lab is created to use Master server only, but Lab User is allowed to use only SAT1 Server. Lab User will not be allowed to start this Lab.


If the Lab contains nodes which are assigned to run on the Satellite server which is NOT in Lab User allowed Satellites list, this node will not start.

Example: Lab several nodes are assigned to use Master server only, but Lab User is allowed to use only SAT1 Server. Lab User will not be allowed to start these nodes.

© EVE-NG LTD Page 90 of 272



User Profile and Lab nodes Satellite use hierarchy



Step 9: User time access to the EVE server.

 EVE-NG Users time database is using UTC time zone. To convert user time zone to the UTC, please use online time convert https://dateful.com/convert/utc

UTC Time Zone Converter



- Set the access date and time in UTC timezone From To. If the fields are left empty (untouched), your user will have no time restrictions for accessing the EVE Server. Account validity with time settings is available for Editor and User roles only.
- Admin accounts have no time limit for account validity and resource, and Account Validity time or resource cannot be set.
- To remove date/time: Delete date, esc, type value "-1"



Step 10: The POD number is a value assigned to user accounts automatically. POD numbers are like user profiles inside of EVE and are a unique value for every user Think of PODs like a virtual rack of equipment for each user. Admins can assign a preferred number between 1-32786. Please keep POD numbers unique between users!

Step 11: Set user limitation to use eve resources. "-1" value is unlimited EVE resource. Only Editor and User roles can be set for EVE resource limitation, Quota.


Example: editor user is allowed to run/create labs for x4 CPU and 8Gb RAM.

© EVE-NG LTD Page 91 of 272





In case of violation these settings, user will receive alert message in the notification area:




Step 12: Press Save for add user or confirm edited user settings.

7.3.1.2 Edit EVE User

Step 1: Open the User management submenu. Management -> User management and choose which user you want to edit.



Step 2: The Edit user management window will pop up. Now you can edit necessary user information, roles, or access time. Confirm settings by pressing Save at the bottom of the window.



© EVE-NG LTD Page 92 of 272



7.3.1.3 User session termination

Administrator has rights to terminate active user session to the EVE server. Press Kick to disconnect user from EVE HTML session.



7.3.1.4 User monitoring

There is a dropdown menu next to "Add User" called "More Info" that can provide additional information about your users. Click the checkbox next to the relevant information that you would like displayed. Additional columns will be added for each checkbox that is chosen. Red or Green label will show user status, which is logged or not in the EVE.



7.3.1.5 User role assigned lab


Assigned Lab. Applies for Lab User role only. Set the specific Lab for the user, "assigned/sticky lab". After login in the WEB, EVE User will direct only to this lab. He cannot close the lab to get in main Lab management page. User can Start/Stop/Wipe lab, as well save his lab work on the lab devices.


Pre-requisites for this feature: The user must be created before. It must exist in EVE database. Only then use Edit user and set desired Assigned/Sticky lab. For Lab selection from the list, the Lab must be upload in the Shared folder by admin first. If Lab Menu is selected to "None", User can close the Lab and open another shared Lab for him. The value "None" is set as default.

© EVE-NG LTD Page 93 of 272



Edit User





7.3.2 EVE Node management




The Management dropdown has a submenu called "Node Management." The Node management menu displays all currently running nodes within EVE. Within this menu, an Admin account can manage or even console to any user's nodes.

▲ NOTE: Editor and User accounts are able to see and open console sessions to their own running nodes only

NOTE: Admin accounts are able to see and open console session to all users running nodes

© EVE-NG LTD Page 94 of 272





7.3.2.1 Node management actions

Button	Action
Ţ	Open a console session to the running node
•	Stop the running node

7.3.2.2 Node management filtering function


Each column in the Node Management Menu has a field or sort sign that will allow you to filter the list to only display information related to the entered value.

Example: Click on "CPU Usage" The CPU column will sort running nodes with most CPU consummation on the top.



Each column can be sorted alphanumerically by clicking on the column name.

Example: click on the column Username and EVE will sort all running nodes in alphabetic order by username.



© EVE-NG LTD Page 95 of 272




7.3.3 EVE Lab management



The Lab Management page, under the Management Dropdown, displays running or stopped labs for all users. In this menu an Admin account can manage or even open up any user's running labs.

In the columns CPU and Memory usage will be displayed actual running lab CPU and RAM utilization.

- NOTE: Only labs which are using space on EVE HDD will be displayed.
- ▲ NOTE: Editor and User accounts are able to see and open their own running labs only
- ▲ NOTE: Admin accounts are able to see, open, and join to any user's running or stopped lab.



Several columns in the Lab Management Menu have a field that will allow you to filter the list to only display information related to the entered value.

Example: Enter username in the field to filter labs created by "admin"



Example: Click State to sort running labs on the top.



Example: Click on "Disk Usage" sorting labs with most HDD usage on the top

© EVE-NG LTD Page 96 of 272







7.3.3.1 Lab management actions

Button	Action
Ø	Open the running or stopped lab.
	Stop the running lab. The running labs will be displayed on top of list.
♦	Wipe lab. Clean up HDD space. NOTE: this action will delete saved lab configurations.

Once an admin has opened another user's running lab, that user's username will be displayed at the top of the left menu to help the admin keep track of which user's lab was opened.



7.4 EVE System Dropdown menu



The EVE System dropdown contains the system settings, Cluster Management, system utilization status, log files, and an option to stop all running nodes on the server.


7.4.1 System Settings



The System Settings page, under the System Dropdown, will show EVE System settings for:

© EVE-NG LTD Page 97 of 272





- Cluster Network. EVE-NG cluster members VPN network, used for intercommunication between EVE-NG cluster members. Customizable, please, change the first three octets to your preferred network. Format of network A.B.C.0/24. The mask /24 is hardcoded. (Value example: 192.168.90.0). The master EVE server IP of wg0 interface will be assigned: A.B.C.254. Rest Cluster members IPs of wg0 interface will be assigned accordingly EVE satellite ID, First EVE satellite ID1 IP will be A.B.C.1. NOTE, after changes of this network, the whole EVE cluster members reboot is required!
- Docker Network. EVE-NG Dockers network. Used for dockers and docker consoles.
 Customizable, please, change the first two octets to your preferred network. Format
 of network A.B.0.0/24. The mask /16 is hardcoded. (Value example: 172.18.0.0).
 The master EVE server IP of docker0 interface will be assigned: A.B.C.1 NOTE, after
 changes of this network, the whole EVE cluster members reboot is required!
- NAT Network. EVE-NG NAT Network, "Natting" internal EVE NAT network to the
 management pnet0/cloud0 EVE management interface IP. Used to have Internet in
 the labs with different network. DHCP service is enabled on this interface
 automatically. Customizable, please, change the first three octets to your preferred
 network. Format of network A.B.C.0/24. The mask /24 is hardcoded. (Value
 example: 192.168.100.0). The gateway and DNS IP of the NAT network interface will
 be assigned: A.B.C.254. NOTE, after changes of this network, the master EVE server
 reboot is required!
- External Radius Server, IP port and shared secret key
- Active Directory Authentication support
 - ✓ IP address of AD and port 389 or 3268 (TLS)
 - ✓ For TLS Active directory communication option, select TLS
 - ✓ DN: Example if domain is eve.lab, then DN syntax is: dc=eve,dc=lab
 - ✓ EVE-NG Active Directory Group: Example: EVE Users. EVE will search Your Group name in whole domain folder tree.


© EVE-NG LTD Page 98 of 272





Note: The username in the Active directory user account must match with AD username. Username must have domain at the end of username. Example:

aduser@eve.lab



- Proxy server IP and port, for authenticated proxy use username and password
- Template visibility is default settings for templates list on topology. Hide state will not show on topology Nodes list with unloaded images. In the Nodes list will appear only uploaded images. Show state (default) will show all available image templates.



- License check is value where you can set EVE user session login behave.
 - ✓ The Value Strict does not allow user login if all available licenses have active sessions (screenshot below, Insufficient Licenses). If user has finished work with EVE server and closed browser, EVE server will clear this user connection session automatically after 1 minute.
 - The Auto logout will terminate oldest connected user session to the EVE server.



Note: Administrator has rights terminate any user session, please refer Section: 7.3.1.3

© EVE-NG LTD Page 99 of 272





 Disk critical size is value when EVE will start alert you about HDD space limit is reached. If you will set 5Gb value, your EVE will start show warning messages in notification area.

The formula in Linux how to set desirable threshold is: [Your full HDD size] * 5% + [desirable size in GB]. Example: 500GB * 5% + 10GB = 35GB value of must be set for 10GB threshold.



 HTML5 Terminal settings Option to change console colour scheme, fonts, font size and backgrounds.

color scheme	Font name	Font size	
Black on White 💌	monospace *	11	
Management Interface :	Settings		

- Management interface settings Option to enable IPv6 on the EVE Management interface
- **WEB Service caching.** Option to enable WEB caching EVE for Management interface Web Service Settings Enable caching
- CPU/Memory Settings dedicated cores for EVE services.
 Suitable for EVE machine with more than 8 vCPU cores.
 Select the dedicated amount of CPU cores for system use.

CPU/Memory Setting	gs
Dedicated CPU for Se	ervices (Reboot required)
1	


CPU NUMA Balancing enables or disables CPU NUMA balancing settings. Suitable for EVE machines with up to x6 vCPU cores. If your EVE has 8 or more vCPU cores disabling this option will force to use of CPUs if full scale and you will achieve better and more nodes to start in your labs.

Numa Balancing

© EVE-NG LTD Page 100 of 272




7.4.2 Cluster Management



The Cluster Management page, under the System Dropdown, will show Cluster Management options, and cluster members resources utilization. Please refer to Chapter EVE Cluster System 14


7.4.3 System status



KSM – "KSM (kernel same-page merging) is a Linux kernel feature that allows the KVM hypervisor to share identical memory pages among different process or virtual machines on the same server." It can be disabled globally for EVE on this page. It is recommended to keep KSM **enabled**.

© EVE-NG LTD Page 101 of 272





CPU Limit – CPU limit is used to limit CPU overloads during the nodes run time. It acts like a smart CPU usage option. If a running node reaches 80% CPU utilization, the CPU Limit feature throttles CPU use for this node to 50% until process usage drops under 30% for a period of 1 minute.

It is recommended to keep the Global CPU Limit option enabled.


CPU Limit can be turned for individual nodes in a lab. EVE node templates are set, by default, with the recommended CPU limit settings. An Unchecked CPU Limit option means that this node will boot without CPU

limit.


Reference:

https://searchservervirtualization.techtarget.com/definition/KSM-kernel-samepage-merging


7.4.4 System logs



In the menu you can select a specific log file for inspection.



7.4.5 Stop All Nodes



The Stop All Nodes option, under the System Dropdown, is an option that stops all running nodes on the EVE server. This option is accessible only by Admin users.


Same can be achieved issuing cli command:

/opt/unetlab/wrappers/unl wrapper -a stopall

© EVE-NG LTD Page 102 of 272



7.5 EVE Information Dropdown menu



The Eve Information Dropdown contains links to the Local latest EVE Cookbook, EVE Website, EVE forum, EVE YouTube channel, and the web-based EVE Live Help chat.


To join the EVE Forum, in order to make posts or download materials, a forum user account must be created.

To join the EVE Live Chat for support, please use your Google account for access, or create a new user account for this chat. Please note the forum and live chat use separate user accounts.

7.6 EVE Licensing Dropdown menu

The EVE Licensing dropdown contains options for managing your EVE license.

The License Information Window will display the expiration date along with the number of licenses that have been activated



License information display:



For License Request and License Upload, please refer to section 4.5 for more information.

7.7 Other Tab line info



Other items on the top menu are: Current version of EVE-NG, Real-time clock, a shortcut to edit the currently logged in user, and a sign-out button.


7.8 Lab preview and global settings

Once you click on a lab in the folder tree, a main window on the right side will display schematic content of the lab as well as lab management options like open, edit, and delete.

The actual lab topology appears after 1-3 seconds.


© EVE-NG LTD Page 103 of 272





7.8.1 Lab preview window

The lab preview window displays the schematic position of nodes and their connectivity. The actual lab topology appears after 3-5 seconds. The Scale option allows you change the lab preview size.



7.8.2 Lab preview buttons

In the lab preview, these buttons allow you to manage the selected lab.

Button	Description
OPEN	Opens the Lab to the Topology Canvas
EDIT	Opens the Labs Global Settings. Refer to section 7.8.4 for more info.
DELETE	Deletes the lab

© EVE-NG LTD Page 104 of 272




7.8.3 Lab preview information

Description, version, UUID etc.



7.8.4 Lab properties

Lab Properties Page is opened when you click on the Edit button below the Lab preview window.



This page allows you to fill out important information about the lab. The red numbers in the picture correlate with the numbers listed below

- 1. Lab name.
- 2. Version: Version numbers allow a lab author to assign a value to a unique state of a lab. Increase the number to correspond to new developments in the lab. If left unfilled, EVE will assign a value of 0 automatically.
- 3. Author: You can add a lab author name in this field
- 4. EVE Cluster Satellite choice. By default, EVE will assign a value of "any" automatically. For cluster hierarchy please follow: Chapter 14.9
- 5. Lab sharing Feature, please follow Chapter 8.11
- Config Script Timeout: It is the value in seconds used for the "Configuration Export" and "Boot from exported configs" operations. Refer to section 10.3 for more information.
- 7. Lab Countdown Timer: It is the value in seconds to provide a time limit (countdown timer) for completing a lab. Refer to section 10.4 for more information. Default Lab
- 8. Links width, you can set default thickness of links for whole lab.
- 9. Topology background grid on/off.

© EVE-NG LTD Page 105 of 272



- 10. Description: In the Description field you can write a short description of the lab.
- 11. Tasks: In the Tasks field you can write the task for your lab.




The Lab details window can be opened from the Topology Canvas page sidebar during labbing, to read the Tasks for the lab.



EVE WEB Topology page

Once you open a lab, the topology page for that lab will open.




7.9 Side bar functions

Move your mouse pointer over to the left on top of the minimized sidebar to expand the interactive sidebar as shown in below screenshot


© EVE-NG LTD Page 106 of 272





7.9.1 Add an object

The "Add an object" menu can be accessed in two different ways, from the sidebar and by rightclicking on the Topology Page




7.9.1.1 Node object

The Node object opens the "Add a new node" window. Only nodes that appear blue in the dropdown menu can be added. A grey image name signifies that you have not yet properly uploaded an image to the proper folder. A blue image name means that at least one image exists in the proper folder for this template. If the "Show unprovisioned templates" is checked, EVE will display unloaded image templates. To hide it, uncheck "Show unprovisioned templates" checkbox or follow section 7.4.1


© EVE-NG LTD Page 107 of 272






7.9.1.2 Network object

The Network object opens the "Add a new network" window. This function is used to add any kind of network (Cloud, Bridge or NAT). For details on these, please refer to section 9



7.9.1.3 Picture object

The picture object opens the "Add Picture" window and allows you to upload custom topologies in jpg or png format. After uploading, you can edit these pictures and map selected areas to nodes from the topology to use your own designs as a lab topology from which you can directly connect to the nodes. For details, refer to section 10.2




© EVE-NG LTD Page 108 of 272





7.9.1.4 Custom shape object

The Custom shape object allows you to add shape elements onto the topology; these currently include squares, round squares and circles. For details, refer to section 10.1



7.9.1.5 Text object

The Text object allows you to add MS Office elements onto the topology. For details, refer to section 10.1.3




© EVE-NG LTD Page 109 of 272



7.9.1.6 Line object

The Line object allows you to add line elements onto the topology; these currently include single arrow, double arrows and simple lines. For details, refer to section 10.1



7.9.2 Nodes

A Nodes

The Nodes object in the sidebar opens the "Configured Nodes" window.



In this window, you can make changes for nodes that are on the lab topology. More options can be found in the detailed node specific menu, for details refer to section 8.1.2.

NOTE: Running nodes are highlighted in Blue, their settings cannot be changed. You can only change settings of nodes that are not currently running.

You can change the following values:

- Node Name
- Boot image
- Number of CPUs for the node
- Live CPU usage
- Enable or disable CPU Limit (Refer to section 7.4.3)
- IDLE PC for Dynamips node
- NVRAM in Kbyte
- RAM in Mbyte
- Live RAM usage
- Ethernet quantity. **NOTE**: The Node must be disconnected from any other nodes to make this change. You cannot change the interface quantity if the node is connected to any other node.
- Serial interface quantity, IOL nodes only. You cannot change Serial interface quantity if the node is connected to any other node.
- Type of Console
- Node Icon that appears on the Topology

© EVE-NG LTD Page 110 of 272



Startup configuration to boot from

Actions Buttons (Stopped node):





- Start node
- Stop node
- Wipe node
- · Export the nodes config
- Networks
- Edit node
- Delete Node

Actions Buttons (Running node):




- · Console to the node
- Stop node
- Wipe node
- Export the nodes config
- Edit node
- Delete Node

7.9.3 Networks



The Networks object in the sidebar will open the "Configured Networks" window.

The "Configured Networks" window will only show networks that were specifically added to the topology; it will not show node interconnections. The example below is showing information for networks on the Topology. For Cloud networks and how to connect EVE labs to a network external to EVE, please refer to section 9



© EVE-NG LTD Page 111 of 272







- Edit Network
- Delete Network


7.9.4 Startup-configs

E Startup-configs

The Startup-configs object in the sidebar opens the "Startup-configs" window.

This window will show you startup-config for each node (for PRO it shows the startup configs of the current config set) and if the node is set to boot from it (ON) or not (OFF).

The "Startup-configs" window in the EVE Professional version contains additional features, please refer to section 10.3.



7.9.5 Logical Maps

NOTE: The Logical Maps object will only appear in the sidebar after you have uploaded a custom topology picture to the lab EVE lab (Please refer to section 7.9.1.3). The Pictures object in the sidebar opens the "Picture Management" window.

For details on the Picture / custom topology feature, refer to section 10.2

© EVE-NG LTD Page 112 of 272



7.9.6 Configured Objects

A Configured objects

The "Configured Objects" window will display a list of all objects that are added onto the topology. For details on different objects, refer to


section 10.1

NOTE: You will not see any objects in this window if none have been added to the lab yet.



7.9.7 More actions

The More actions menu in the sidebar has a submenu with the following functions.



7.9.7.1 Start all nodes

▶ Start all nodes

The "Start all nodes" action will start all nodes on your topology, taking the (configurable) startup delay of each node into consideration.

⚠ IMPORTANT. Starting many nodes at once can seriously spike your CPU utilization. Please make sure that you are not using the "Start all nodes" option for heavy labs or that you have configured a proper delay between the nodes. For heavy nodes and large quantities, it is recommended to start them in smaller groups, wait for them to finish booting and then start another small group of nodes.

7.9.7.2 Stop all nodes

■ Stop all nodes

Stopping all nodes will power off all nodes on your topology.

NOTE: It is recommended to save your (running) configurations on the nodes in your lab before you stop the lab if you want to continue where you left off the next time. Stopping the nodes will leave the images in a temporary folder and will take up space on your drive until they have been wiped.

7.9.7.3 Wipe all nodes



The "Wipe all nodes" action will wipe the NVRAM or currently saved image of all your nodes in the current lab.

© EVE-NG LTD Page 113 of 272



Example: You have saved the nodes configuration by saving the running configuration to the startup configuration. The Wipe command will delete the saved NVRAM startup configuration and on the next boot it will boot from factory defaults.

The same applies to images without configurations, e.g. a linux node. If you make modifications to the system and afterwards wipe this node, the next time it will boot from the original base image again as the modified image was deleted.

The "Wipe node" action is commonly used with initial startup configuration modifications. The Wipe node action does not delete configured startup configurations or sets. Please refer to section 10.3

7.9.7.4 Console to All Nodes

"Console to all nodes" will open a console to all of your running nodes in the current lab. This includes all different kinds of configured console types for lab nodes like VNC, Telnet and RDP.

7.9.7.5 Export all CFGs


The "Export all configurations" action will export current configs to the EVE startup-configs.

Export configurations are supported for:

Cisco Dynamips all nodes	Juniper VRR
Cisco IOL (IOS on Linux)	Juniper vEX
Cisco ASA	Juniper VMX
Cisco ASAv	Juniper vMX-NG
Cisco CSR1000v	Juniper vQFX
Cisco Catalyst 9000v	Juniper vSRX
Cisco Catalyst 8000v	Juniper vSRX-NG
Cisco Nexus 9K	Mikrotik
Cisco Nexus Titanium	PFsense FW
Cisco vIOS L3	Timos Alcatel
Cisco vIOS L2	vEOS Arista
Cisco Viptela vEdge, vSmart, vBond, till	Aruba CX Switch
version 18.4 only, version 19.x and later is	
not supported due implemented password	
setup feature on the first boot.	
Cisco XRv	
Cisco XRv9K	


For a full explanation of exporting configurations, please refer to section 10.3

7.9.7.6 Edit lab




© EVE-NG LTD Page 114 of 272





7.9.7.7 Topology screenshot



Feature to export actual topology in png format



7.9.7.8 Set node's startup-cfg to default configset

Sets nodes to the default startup-config. NOTE: If you have nothing saved in the default config set for any node, that node will boot from factory default instead. This is commonly used with the wipe nodes function so the node will boot from the configured startup-config on next boot and not from the startup-config in its NVRAM in case the node was started before already.

Please refer to section 10.3

7.9.7.9 Set node's startup-cfg to none

Setting all lab nodes to boot from factory default. Used commonly with the wipe nodes function. The example below shows the steps to set a lab to boot from factory default.

Step 1: Wipe all nodes

Step 2: Set all nodes to startup-cfg none


Please refer to section 10.3

7.9.7.10 Delete default startup-cfgs



▲ WARNING: this action will delete all configurations saved to your saved default config set. Please make sure that is what you want to do before you execute this.

7.9.8 Refresh Topology




Sometimes it is necessary to refresh the topology if many objects are added on the topology.

© EVE-NG LTD Page 115 of 272



7.9.9 Lab page zoom/unzoom




7.9.10 Status



Opens the EVE Status window.

Especially useful while working with labs to monitor your EVE's resource utilization. It shows EVEs CPU, RAM and disk utilization in real time. You can also see the number of running nodes per node type. For details on KSM and CPU Limit, please refer to section 7.4.3



7.9.11 Lab details

Lab details Lab details display information about a lab, its UUID, description and lab tasks. To edit the lab description and lab tasks, please refer to section 7.8.4 and 7.9.7.6

© EVE-NG LTD Page 116 of 272






7.9.12 Lab Tasks

Opens a Lab Task feature. The EVE LabTasks is a feature that allows users (including admins and editors) to to create task or workbook for the Labs. Detailed how to create lab workbooks please refer Secton 10.5

7.9.13 Lab Chat




on the sidebar. To close and exit from the chat, click "Lab Chat" on the sidebar again. The EVE Lab chat is a feature that allows users (including admins/teachers) to communicate with each other during lab sessions.



7.9.14 Lock Lab with password


"Lock Lab" disables some of the functions on the lab topology. If the lab is locked, you cannot move any node or object nor edit any node settings. Basically, the whole lab will be in read-only mode except for the lab settings itself, which you can still edit as Administrator or Editor from the main menu. The Lock Lab function is also used in conjunction with the countdown timer function, for details on this please refer to section 10.4



To unlock a Lab, simply press on the red "Unlock Lab" button with an Administrator or Editor account.


© EVE-NG LTD Page 117 of 272






Warning: Please remember your Lab lock password. In case of a lost password, you will not be able to recover it. Unlocking a lab / removal of password can be done by EVE-NG support only.

7.9.15 Locked Labs Access rules



- Administrator CAN delete locked lab including shared folder. No unlock password is required.
- ❖ Lab Editor CAN NOT delete locked labs, including shared folder. Editor CAN unlock Shared folder Lab and delete it, if the unlock password is known.
- ❖ Lab User CAN NOT delete locked labs at any location.

7.9.16 Fullscreen




7.9.17 Hide interface labels



© EVE-NG LTD Page 118 of 272



7.9.18 Dark mode or Light mode



7.9.19 Close lab

Closes the lab topology. The lab can be closed while the nodes in the lab are still running as well. It will appear as running lab under the Running folder. Please refer to section 7.2.1.1

7.9.20 Logout



Log out from the EVE WEB GUI session.

7.10 EVE Lab topology menus

Right-clicking within the EVE topology can open new menus with various functions and options for managing nodes.

7.10.1 Lab topology menu



Right-clicking on the (free/unused) canvas of the EVE topology opens a new menu. (Add-) Node, Network, Picture, Custom Shape and Text are the same functions referred to in section 7.9.1.

Auto Align. This function will help align objects on the topology. The lab creator does not need to worry about small displacements of objects. AutoAlign will align all objects to a virtual grid with a single click and can make neatly arranged labs look even neater.

7.10.2 Connection menu



Right-clicking on the connection between nodes allows you to delete this connection.

© EVE-NG LTD Page 119 of 272




7.10.3 Network Adding



When you have chosen Add a Network, the ADD A NETWORK window will open where you can change the placement, **network type** or name/prefix.

NOTE: You can add multiple networks (clouds) on your EVE topology, which will act as same cloud but in different locations on your EVE. Literally, like, the ethernet socket in the wall.




7.10.4 Bridge or Internal network menu



Right-clicking on a Bridge or Internal network allows you to Edit, Manage or Delete it.

If you have chosen Edit, the Network edit window will open a window where you can change the placement, name/prefix or icon.

For details on how to operate EVE Cloud networks and external connections, please refer to section 9





If you have chosen Manage, the Network Manage window will open a window where you can change Port assignments or protocol used for the bridge network.

For details on how to operate EVE Cloud networks and external connections, please refer to section 9

© EVE-NG LTD Page 120 of 272



7.10.5 Cloud and Private network menu

When you have chosen Add a Network, the ADD A NETWORK window will open where you can change the placement, **network type** or name/prefix.

NOTE: You can add multiple networks (clouds) on your EVE topology, which will act as same cloud but in different locations on your EVE. Literally, like, the ethernet socket in the wall.



For details on how to operate EVE Cloud networks and external connections, please refer to section 9

Right-clicking on a Cloud or Private network allows you to edit or delete it.

7.10.6 Stopped node menu

Right-clicking on a stopped node (grey) also opens a menu:




Start node: This will start the selected node in this lab

Wipe node: Wiping a node will erase the NVRAM (running config) or the temporary image snapshot depending on the type of node. This option is used to clean up a node in order to boot it from factory defaults or a custom set of configurations.

Edit node: Opens the Edit node window (picture on the right). For details, please refer to section 8.1.2

Delete node. Deletes the node from the lab. It is recommended to disconnect (delete connections to it) the node before you delete it.



7.10.7 Running node menu



Right-clicking on a running node (blue) also opens a menu:

© EVE-NG LTD Page 121 of 272





Stop. Blue arrow: clicking on Stop will stop the node depending on the method the node supports (power off / shutdown are auto-selected based on the template)

Stop menu. Red arrows: There are more options to stop a node, clicking on the chevron on the left side of "Stop" opens a submenu.

- **Shutdown**: Perform an orderly shutdown of the node if that node supports it (shutdown signal is sent down to the node)
- Power off: Kills the running nodes process within EVE (hard poweroff).
- Hibernate. Save Node state (Disk and Memory are saved in an internal snapshot).
 Used for fast boot of a node. The hibernation process can take some time. Once the hibernation process is completed, the node will turn grey (shutdown state).

Details: Details of running node template and graphical resource usage.



Wipe node: Wiping a node will erase the NVRAM (running config) or the temporary image snapshot depending on the type of node. This option is used to clean up a node in order to boot it from factory defaults or a custom set of configurations.

Export CFG: This function is used to export the saved running configuration to the EVE startup configuration sets. Reference section 10.3



Capture. Integrated live Wireshark capture. Select the interface which you wish to capture. Reference section 11

© EVE-NG LTD Page 122 of 272






Graph. Integrated live interface activity monitoring. Displaying live interface utilization activity.




7.10.8 Selected nodes menu and features

It is possible to select many objects or nodes at once in EVE. Using your mouse, you can select an area which will cover your nodes and/or you can click on nodes while holding the CTRL key on your keyboard.



A right-click on any of the selected nodes opens a group menu:



Start Selected: This will start the selected nodes in this lab.

Stop Selected: This will stop the selected nodes in this lab

Wipe Selected: The Wipe Selected nodes action will wipe the NVRAM or currently saved image of the selected nodes in the current lab.

Example: You have saved the nodes configuration by saving the running configuration to the startup configuration. The Wipe command will delete the saved NVRAM startup configuration and on the next boot it will boot from factory defaults.

The same applies to images without configurations, e.g. a linux node. If you make modifications to the system and afterwards wipe this node, the next time it will boot from the original base image again as the modified image was deleted.

The Wipe node action is commonly used with initial startup configuration modifications. The Wipe node action does not delete configured startup configurations or sets. Please refer to section 10.3

© EVE-NG LTD Page 123 of 272



Console To Selected Nodes: Console To Selected Nodes will open a console to all selected running nodes in the current lab. This includes all different kinds of configured console types for lab nodes like VNC, Telnet and RDP

Export all CFGs: The Export all configurations action will export current configs of selected nodes to the EVE startup-configs.

For a full explanation of exporting configurations, please refer to section 10.3

Set nodes startup-cfg to default configset: Sets nodes to Default startup config, used commonly with the wipe nodes function. NOTE: If you have nothing saved in the default config set for any node, that node will boot from factory default instead. This is commonly used with the wipe nodes function so the node will boot from the configured startup-config on next boot and not from the startup-config in its NVRAM in case the node was started before already.

Please refer to section 10.3

Set nodes startup-cfg to none. Setting selected lab nodes to boot from factory default. Used commonly with the wipe nodes function. The example below shows the steps to set selected nodes to boot from factory default.

Step 1: Wipe selected nodes

Step 2: Set nodes startup-cfg to none

Please refer to section 10.3

Horizontal Align. Aligns the selected nodes in one horizontal line.

Step 1: Select the nodes you wish to align.

Step 2: Right click on one of the selected nodes and choose Horizontal align, this will align all nodes to the selected node.

Picture before:

Picture after:







Vertical Align: Aligns the nodes in one vertical line.

Step 1: Select the nodes you wish to align.

Step 2: Right click on one of the selected nodes and choose Vertical align, this will align all nodes to the selected node.

Picture before:





© EVE-NG LTD Page 124 of 272




Circular Align: Aligns the nodes in a circle.

Step 1: Select the nodes you wish to align.

Step 2: Right click on one of the selected nodes and choose Circular Align, this will align all nodes in a circle, the midpoint of the circle will be at the coordinates the selected node was at before.

Picture Before



Picture After




Delete nodes startup-config.

WARNING, this action will delete the configurations of the selected nodes that are saved to your Default config set. Please make sure that is what you want to do before you execute this.

Delete selected: This will delete the selected nodes from your current lab.

Selected nodes can be moved as a group across the topology.

Example: You can select nodes and objects to better position them on the Topology.



7.11 **EVE Lab node states and symbols**

7.11.1 Stopped (non-running) nodes



Grey colour and a square symbol below a node means that the node is stopped and not running. Once you will start it, the node will change to one of the running states below.



A grey node with an exclamation mark inside a triangle below the node means that there was a problem during the boot process, this could be a corrupted boot image, insufficient resources or problems with the initial configuration. A node in this state cannot be started again.

Workaround: Right-click on the node and wipe it, the symbol will then change to a grey colour with a square symbol below it. Then edit the node and make sure you have configured sufficient

Page 125 of 272 © EVE-NG LTD



resources and the correct settings for this node, if it has startup-configs you can check them as well. Afterwards start the node again.

7.11.2 Running nodes



The blue colour and black Play triangle symbol means that the node is started and running, the node is in a working/functional state.



A running node with a clock symbol below the node means that the node is waiting to finish loading from the set exported/startup configuration. Once the configuration has been successfully applied, the node symbol will change to a Play triangle symbol.



If the node has finished booting but the clock symbol does not change to the Play triangle symbol, the problem could be in the uploaded startup configuration. For how to use exported configurations and boot nodes from them, please refer to section 10.1


A running node with a turning red gear symbol means that the node is either in the process of hibernating the node or it has sent the shutdown signal to the node and is waiting for it to turn off. Once this process has successfully finished, the symbol will turn into a grey node with a black square symbol below it (stopped state).

NOTE: If the node does not support a system shutdown or does not recognize the shutdown signal (example: Cisco router), after clicking on Shutdown, the node can stay with a turning red gear symbol below it indefinitely.

Workaround: Use Stop or Stop/PowerOff to stop the node.

Example nodes where Stop/Shutdown is supported: Microsoft Windows and most Linux nodes as well as a lot of appliances based on linux.

7.11.3 Node connector symbol



Connector symbol: If you move your mouse pointer on top of a running or stopped node, an orange connector symbol appears. It is used to connect nodes on the topology in a drag and drop style.

Drag the symbol from one node and release the mouse pointer on the second node. A new window will appear where you can select the interfaces the link should connect to.


7.12 Other

7.12.1 **Notifications area**



The Notification area in the top right is displaying informational or error messages.

Unwrapped notifications:



Page 126 of 272 © EVE-NG LTD



The Notification messages bar appears automatically for any EVE-PRO activity made on Topology.

Success 4	Success message counter. For review, click on green ball to unwrap notifications. To wrap notifications, click to the ball again or click at any point of topology
Error 1	Error message counter. For review, click on red ball to unwrap notifications. To wrap notifications, click to the ball again or click at any point of topology
•	Unwrap or wrap notifications bar.
×	Close notifications bar. Note: Notifications bar appears automatically on any EVE topology activity.

© EVE-NG LTD Page 127 of 272



8 Working with EVE labs

▲ IMPORTANT NOTE: You must prepare and upload at least a couple of images to start building your labs. Refer to section 17

8.1 Creating a lab

Step 1: Click Create new lab. For more information on creating new labs, please refer to section 7.2.2.1



Step 2:

Fill out the lab information. Name and Version are required fields. Next hit Save. Refer to section 7.8.4 for more information about the different fields in the Edit lab window.



8.1.1 Adding nodes to the lab

The new Topology page will open. There are two different ways to add nodes to the topology canvas:


Step 1: Object/Add Node

Left Side Bar > Add object > node. Refer to section 7.9.1.1 for more information.

Right click on a free area of the topology page and click on "Node" to add a new node. Refer to section 7.10.1 for more information.


© EVE-NG LTD Page 128 of 272





Step 2: The Add new node window will appear. You can scroll down to choose which node you wish to add to the lab topology, or you can type the node name to filter through the node list.


NOTE: It will only be possible to select and add nodes that have images preloaded in EVE. These nodes will be displayed in a blue font. To prepare images for EVE, refer to section 17




Step 3: Edit "Add a new node" settings. Please refer to the picture and table below.

© EVE-NG LTD Page 129 of 272





8.1.1.1 Node values Table



© EVE-NG LTD Page 130 of 272



2.	Number of nodes to add Chose the number of nodes of this type you want to add to the topology	
3.	Choose your preferred version from preloaded images list (if you have more than one image loaded for a single template).	
4.	Name/prefix CSR Type your preferred node name. If you are adding more than one, EVE will automatically append numbers to the nodes name. Example. We are adding 5 CSR nodes with the name R. On the topology they will appear as R1, R2, R3, R4, R5. Later using the Nodes window, you can edit the node names per your needs. Refer to section 7.9.2 or edit the node individually, refer to section 8.1.2.	
5.	Node icons can be changed from the default per your preference, simply choose the preferred icon from the dropdown list. Node icons can be changed from the default per your preference, simply choose the preferred icon from the dropdown list. Node icons can be changed later per your needs. Refer to section 7.9.2	
6.	The UUID number is assigned automatically after a node is created. You may also set it manually in case you are using a license that is tied to a particular UUID.	
7.	CPU limit per node. This option is already set (checked/unchecked) per EVE recommendations. Refer to section 7.4.3	
8.	Each node template has a pre-set CPU value that aligns with vendor requirements. This value can be changed per your needs.	
9.	Each node template has a pre-set RAM value that aligns with vendor requirements. This value is displayed in MB and may be changed per your needs.	
10.	Ethernets 4 The number of ethernets interfaces.	


© EVE-NG LTD Page 131 of 272



	NOTE for IOL nodes: Ethernet interfaces for IOL nodes are placed into groups of 4. A value of 1 for Ethernet means your node will have 4 interfaces.	
	The serial interface option is available for IOL nodes only and follows the same grouping structure as ethernet interfaces. A value of 1 for Serial means your node will have 4 serial interfaces.	
11.	Custom MAC address for Qemu nodes only. You can define your own MAC address for first interface: First Eth MAC Address aa:bb:cc:00:de:ad	
12.	QEMU Version EVE will pre-set the best recommended QEMU version for each node template. This value can be changed per your needs.	
13.	Qemu architecture is pre-set per image vendor recommendations. This value can be changed per your needs	
14.	Type of Qemu NIC is pre-set per image vendor recommendations. This value can be changed per your needs. Type of Qemu NIC is pre-set per image vendor recommendations. This value can be changed per your needs.	
15.	QEMU custom options -machine type=pc-1.0,accel=kvm-cpu Nehalem-serial mon:stdio-nographic-r Qemu custom options are pre-set per image vendor recommendations. This value can be changed per your needs	
16.	Startup configuration None Startup configuration: Value can be changed to set your node to boot from saved configurations. Refer to section 10.3 for more details.	
17.	The Delay value is set in seconds and can be used to delay a node from booting after it is started. Example: if the value is set to 30, the node will wait 30 seconds before processing its boot sequense. This feature is useful in conjunction with the "Start all nodes" function if your lab requires certain nodes to start up before others or to avoid a mass-start of very heavy nodes.	

© EVE-NG LTD Page 132 of 272





8.1.2 Edit node

EVE provides two ways to edit nodes after being added to the topology canvas.

🕂 Add an object

NOTE: To force and apply a new settings, node must be wiped each time if an image, parameters or start up configuration has been changed.

8.1.2.1 Edit nodes globally

From the Topology page. Click "Nodes" from the left sidebar to bring up the nodes list. Refer to section 7.9.2 for more details.

8.1.2.2 Edit node individually.




Right click on the node and click Edit

The "Edit node" window will appear. It is very similar to the window that is displayed when you add a new node. To change values for the node, refer to the nodes value table in section 8.1.1.1.

© EVE-NG LTD Page 133 of 272





8.1.3 Wipe Node



The "Wipe node" function will clear the NVRAM of the node. Each time a node setting is changed (CPU, RAM, boot image or startup configuration) a wipe must be issued on that node. For more information refer to section 10.3

8.1.4 Interconnecting nodes

To connect nodes on the lab, use the drag and drop style method



Connector symbol: Moving the mouse over a node will make an orange male plug appear. The male plug is used to connect nodes on the topology, drag and drop style. Release the mouse pointer on the second node.


© EVE-NG LTD Page 134 of 272









The connection window will appear. Choose the interface you want to use to interconnect the nodes. Click Save when finished.






8.1.5 Edit connection link style

Right click on the connection link and choose Edit Style



Straight link style



© EVE-NG LTD Page 135 of 272



Flowchart link style



Style: Allows you to choose solid or dashed style for link. This can be edited later in the "Shape Edit" menu.

Link colour: Allows you to choose a colour for the link. This can be edited later in the "Shape Edit" menu.

Pos "interface" label: Allows move and position interface label

Link Style: Allows you to choose a style Straight, Bezier, Flowchart or StateMachine for the link. This can be edited later in the "Shape Edit" menu.

Link Width: Allows you to choose a thickness for the link. Default thickness of liniks is 2.

Link label: Allows you to add a label on the link. This can be edited later in the "Shape Edit" menu.

Pos Label: Allows move and position Link label, position it on the link

Curviness: Link curviness feature for Bezier style link

Midpoint: Link mid point change, Flowchart style only


Round: Link round angles, Flowchart style only

Stub: Stub link connection beside node, Straight style only

For edit Link style use mouse right click on link to call out link style editor.

8.1.6 Edit connection link quality

Right click on the connection link and choose Edit Quality. This function will allow apply on live connection Delay in ms, Jitter in ms, Packet loss in % and rate in kbs. If the Link quality is in use, then Orange indicators on the link will report where it is applied,



It is recommended to apply value divided by 2 on both link interfaces to achieve precise connection quality. In the example below is applied 25% and 25% packet loss, which gives result of 50% packet loss in connection between nodes.




© EVE-NG LTD Page 136 of 272



8.1.7 Suspend or resume link connection


The EVE-Pro has integrated feature to detect connection state on the interface.

For IOL nodes please select enable L1 Keepalive under Edit node to allow suspend feature.



Right click on the connection link and choose Suspend

Link. This function will suspend connection between the two nodes. Literally, it will act like disconnected cable from the node, and interface will detect it as no connection. Suspended link will be marked with red dots. To resume link connection, right click on the link connection and choose **Resume Link**.



Supported nodes with suspend/resume feature:

Supported nodes for Link Suspend/resume	Not supported
IOL vIOS XRv9K CSR CSR SD-WAN ASAv Firepower FTD Juniper vSRX 12.1X47 Juniper vSRX NG Juniper vMX VCP/VFP Juniper VRR Nokia Timos SR 19.5.1 Windows All Linux All Apple OSX Mikrotik Palo Alto F5 Fortigate Checkpoint Cumulus Cyberoam FW Sophos FW SonicWall FW Viptela Velocloud Versa Networks sd-wan pfSense	Arista NXOS 9k ASA ported XRv Old Juniper vMX Juniper vQFX Dynamips Titanium Nexus 7.x

© EVE-NG LTD Page 137 of 272



Brocade vADX Barracuda NGFW HP VSR1000	
--	--

NOTE: Avoid use Link suspend feature if you have configured:

IOL L3 router image with:

If the IOL L3 node interface is configured as DHCP client (ip dhcp), IOL node is attempting to bring up interface in up/up state. If you have enabled Link suspend feature on such configured interface, the node will flap link connection up/down/up.

Same behave is observed if your Serial interface is configured with PPP encapsulation.

Other observations:

vIOS L2 image has minor internal issue. LACP protocol does not detect interface state as down/down

8.1.8 Delete connection between nodes



To delete a connection, right click on it and hit "Delete."

8.1.9 Delete Node




To delete a node, right click it and hit "Delete." This is a non-reversable function

NOTE: It is strongly recommended to delete connections from a node before deleting the node itself.

8.2 Running labs

8.2.1 Starting lab

Nodes inside a lab may be started individually, in groups, or all at once.



The Start all nodes option will start all nodes on your topology.


IMPORTANT. Starting all the nodes at once can result in major spikes in CPU utilization. Please make sure you are not using the "Start all nodes" option for heavy labs. Instead, it is recommended to start nodes in small groups.

Starting a node or group of nodes:

Right click on single node or node group and hit "Start."

Page 138 of 272 © EVE-NG LTD





Running nodes will turn blue. Refer to section 7.11 for node states



8.2.2 Interconnecting running nodes (hotlinks)


Eve Professional offers the hotlinks feature which allows you to interconnect node in the running state.



Connector symbol. Moving the mouse over a node will make an orange male plug appear. The male plug is used to connect nodes on the topology, drag

and drop style. Release the mouse pointer on the second node





8.2.3 Link quality delay, packet loss, jitter and rate feature

Please refer to Section 8.1.6

8.3 Saving labs

To save a running lab, refer to the vendor recommended save commands for each node.

Example: Cisco: "copy run start"

Juniper "commit"

Your current work will be saved in the nodes' NVRAM and the lab can be stopped safely. Starting the lab again will allow you to pick up from where you left off.

WARNING: Using the wipe action on a node will clear its NVRAM. This is similar to doing a factory reset on a device.

The configurations of nodes can be exported and used as initial or startup configurations for your labs. To export configurations and configuration sets for labs refer to section 10.1

© EVE-NG LTD Page 139 of 272



8.4 Stopping labs

■ Stop all nodes option will stop all nodes on your topology.

NOTE: It is recommended to save your running configurations before you stop your nodes.


Stopping a node or group of nodes:

Right click on single node or node group and hit "Stop."

For individual node Stop options refer to section 7.10.7

8.5 Start saved lab

Click to the lab you want to start and click "Open". To start Lab refer section 8.2.1



8.6 Working with multiple running labs

Refer to section 7.2.1.1

8.7 Importing labs

Refer to section 7.2.2.6

8.8 Exporting labs

Refer to section 7.2.2.5

8.9 Deleting labs

Refer to section 7.2.2.2

8.10 Moving labs

Refer to section 7.2.2.4

© EVE-NG LTD Page 140 of 272



8.11 Shared Project/Lab


EVE-NG provide an option to share single running lab between users. It is designed to run single lab for many users who can participate in lab session and configure it.

Note: Lab sharing option can be used between any of EVE NG User roles.


- ✓ Administrator can share lab for other Administrators, Lab Editors or Lab Users.
- ✓ Lab Editor can share lab for Administrators, other Lab Editors or Lab Users
- ✓ Lab User can share lab for Administrators, Lab Editors or other Lab Users.

8.11.1 Create Project Lab share

Step 1. Navigate to EVE main Lab tree and select which lab you want to share with others. *Do not create shared Project lab from Shared folder to avoid lab names duplication.*



Step 2: From menu "Shared with" select Users to whom you want to share lab



8.11.2 Remove Lab share


Note: Only owner of lab share can remove sharing.

© EVE-NG LTD Page 141 of 272



Step 1. Navigate to EVE main Lab tree and select shared and click "Edit"

Step 2: Deselect to remove users from Shared with



8.11.3 Working with shared lab

- Step 1: Owner of shared lab starts the lab. To join in the shared project lab, owner of lab must start it.
- Step 2: Other user to whom this lab is shared, log into EVE with his account
- Step 3: Open Shared Lab folder, the lab shared to him will appear as shared lab with owner user in brackets. (Example: admin user shared lab for test2 user)




Accordingly, permissions of user roles:

- ✓ Administrator can start, stop or edit lab.
- ✓ Lab Editor can start, stop or edit lab.
- ✓ Lab user can start and stop lab

When you join in the shared lab, on the top of left side bar menu, you will notice the name of lab owner.

© EVE-NG LTD Page 142 of 272





Note: If the Lab is been edited by Administrator, changed links connections or nodes, other shared lab users must refresh this lab topology to obtain changes.

Note: Parallel Consoles

Telnet Consoles: can be opened parallelly for any user


VNC Console: can be opened parallelly for any user

RDP Console: Only one user at same time can use RDP console to the node

8.12 Assigned single lab

Pre-requisites for this feature: For Lab selection from the list, the Lab must be upload in the Shared folder by admin first. If Lab Menu is selected to "None", User can close the Lab and open another shared Lab for him.

Applies for Lab User role only. Set the specific Lab for the user "Assigned/sticky lab". After login in the EVE User will directed only to this lab. He cannot close the lab to get in main management page. User can Start/Stop/Wipe lab, as well save his lab work on the lab devices. Follow Section: 7.3.1.5



© EVE-NG LTD Page 143 of 272




9 EVE Clouds and Networks

9.1 Bridge Network


The EVE Bridge interface acts like an unmanaged Switch. It supports passing along tagged dot1q packets.

Example: We have to connect many nodes in a flat (dot1q) network

Step 1: Add a Bridge Network onto the topology. There are two ways to do this: Right-clicking on the topology area and selecting "Add Network" or in the sidebar click "Add an Object" and then select "Network." Please refer to sections 7.10.5 and 7.9.1.2




Step 2: Name/prefix can be changed in order to rename your Bridge network. Make sure your network type is set to bridge.



Step 3: Connect your nodes using the drag and drop connector. Refer to sections 8.1.4 and 7.10.5


9.2 The experimental Smart Bridge feature.



Smart bridge feature is available for EVE *Bridge and Internal Networks*. Using smart bridge feature, you are able to assign connected bridge ports with VLAN ID. Select "Manage"

© EVE-NG LTD Page 144 of 272





VLAN ID 0 – untagged port with native VLAN 1, used for trunk assignment.

Smart Bridge, enables 802.1q option.


Enable 802.1ad option allows to use bridge for QinQ mode.

9.3 Internal Network


Internal cloud network is used as an extended connector between nodes inside of one lab. It is isolated cloud which not visible for other labs or users.

EVE Pro is offering 3 independent Internal clouds/domains. It is isolated from each other. Inside of single lab you can have up to 3 isolated cloud/domain networks. Example of Internal cloud usage below:

Step 1: Add two internal cloud networks onto the topology.



Step 2: Connect your lab nodes to internal cloud. Your configured nodes will work like being connected to the same switch (or the same bridge in EVE). CDP works. It is convenient if it is



necessary to have connections across the lab and you don't want to have connections going from one end of the lab to the other.


© EVE-NG LTD Page 145 of 272



9.4 Private Network

Private cloud network is used as an extended connector between labs in the one user POD. Private cloud is isolated and not visible for other users.

EVE Pro is offering 3 independent Private clouds/domains. It is isolated from each other. Inside of single user POD you can have up to 3 isolated Private cloud/domain networks. Example of Private cloud usage below:




Example: Single user is running multi labs (Lab1 and Lab2), and want interconnect it.

Step 1: Add private cloud network onto the topology Lab1.

Step 2: Add private cloud network onto the topology Lab2.

Step 3: Connect your lab node to Private cloud. Your connected nodes in Lab1 and Lab2 will work like being connected to the same network. CDP works. It is convenient if it is necessary to have connections across the multi labs.

▲ NOTE: Using Private cloud, avoid to connect nodes with same ID to it. It will raise MAC address collision in your connection. Pic below shows correctly interconnected Node ID1 in Lab1 and Node ID5 in Lab2.



9.5 NAT Network

EVE-NG PRO has an embedded NAT interface with the subnet 172.29.129.0/24. This feature is similar to the VMWare NAT interface, but EVE is translating the 172.29.129.0/24 (this subnet is hardcoded in EVE and is not configurable) subnet to EVE's management interface pnet0. NAT network can be changed per your needs, please refer 7.4.1

To add a NAT Cloud onto the EVE topology:

© EVE-NG LTD Page 146 of 272






Step 1: Add A New Network onto the topology. There are two ways to do this: Right-clicking on topology area and selecting "Network" or in the sidebar, "Add an Object" and then select "Network."

Step 2: Name/prefix can be changed in order to rename your NAT network. Make sure your network type is set to NAT.

Step 3: Connect your nodes using the drag and drop connector. Refer to sections 8.1.4 and 7.10.5



If your EVE management is connected to the Internet, adding a NAT cloud onto the EVE lab enables you to have internet access from within your EVE lab using NAT.

EVE NAT Gateway IP is: **172.29.129.254/24**

DHCP is enabled on the EVE NAT Cloud.

9.6 Management Cloud0 interface

EVE management interface is also known as the Cloud0 network for labs. The Cloud0 interface is bridged with your EVEs first NIC. "Cloud" is used as an alias to pnet. Pnet is the bridge interface name inside of EVE.

```
# The primary network interface
iface eth0 inet manual
auto pnet0
iface pnet0 inet dhcp
bridge_ports eth0
bridge_stp off
```

Cloud0 is commonly used inside EVE labs to get management access to nodes running inside EVE from a host machine external to EVE.

- ▲ IMPORTANT NOTE: For EVE VMs running on ESXi, with NIC Teaming Network, please follow the steps below to edit the reverse path settings
 - From the Navigator window select Manage > System > Advanced settings.
 - Scroll down or use the search bar to go to the Net.ReversePathFwdCheckPromisc option.
 - Select Net.ReversePathFwdCheckPromisc and click Edit option.
 - ❖ In the Edit option Net. ReversePathFwdCheckPromisc window update the New value field to 1 and click Save.


▲ IMPORTANT NOTE: For EVE VMs running on ESXi, make sure your management interface bridged with the vSwitch (Port group) has the security settings set to Accept. Any port group or vSwitch used to connect an external network to an EVE Cloud network needs to have the:

© EVE-NG LTD Page 147 of 272




Promiscuous mode: "Accept"
 MAC Address changes: "Accept"
 Forged transmits: "Accept"

vSwitch Settings



Portgroup Settings



EVE Cloud0 bridging table.


Lab name	EVE interface name (inside)	Туре	Notes
Cloud0	pnet0	Bridged	Cloud0/pnet0 is bridged with your primary EVE ethernet port. It is assigned a management IP address used for WEB GUI access. The EVE management subnet can be used as a management network in labs.

© EVE-NG LTD Page 148 of 272




Question: How can I obtain my Cloud0 subnet and gateway IP. Many EVE VMs only have a DHCP address assigned on the pnet0 interface.

Answer: SSH to EVE and type the following from the CLI:



Example: We want to use Cloud0 as a management network for an ASAv node in an EVE lab. From the above-obtained information, we know that our Cloud management subnet is 192.168.90.0 with a mask of 255.255.255.0 and the Gateway IP is 192.168.90.1.




Step 1: Add A New Network onto the topology. There are two ways to do this: Right-clicking on topology area and selecting "Network" or in the sidebar, "Add an Object" and then select "Network."

Step 2: Name/prefix can be changed in order to rename your Cloud0 network. Make sure your network type is set to Management(Cloud0).

Step 3: Connect your ASAv using the drag and drop connector to the Cloud0 network. Refer to sections 8.1.4 and 7.10.5


Step 4: Start the node and configure the interface connected to Cloud0 with an IP address from the management subnet (192.168.90.0/24 in this example). Make sure you do not assign duplicate IPs.




The native management host (home PC) can be used to manage nodes in the EVE lab over https. Example below showing http connection to Fortigate FW node in the EVE lab from native PC using Chrome browser.

© EVE-NG LTD Page 149 of 272






NOTE: Cloud interfaces can be used to connect multiple nodes to a single cloud instance on the topology.



9.7 Remove cloud interfaces

For security reasons you can make cloud (Cloud0-9) interfaces invisible for the Lab Editors and Lab Users.

echo -n 1 > /opt/unetlab/natonly



To set back Clouds0-9 visible:

echo -n 0 > /opt/unetlab/natonly

© EVE-NG LTD Page 150 of 272



All Clouds 0-9 will remain visible for Admin users.

Other cloud interfaces 9.8

Other cloud interfaces can be used to extend a lab connection inside of EVE or bridged with other EVE interfaces to connect external networks or devices.

EVE Cloud bridging table.

Lab cloud name	EVE interface name (inside)	Туре	ESXi VM corresponding interface	VMware Workstation corresponding interface	Bare HW Server	Notes
Cloud0	Pnet0	bridged	Network adapter 1	Network Adapter	First ethernet Eth0	Cloud0/pnet0 is bridged with your primary EVE ethernet port. It is assigned a management IP address used for WEB GUI access. The EVE management subnet can be used as management network in the labs.
Cloud1	Pnet1	bridged	Network adapter 2	Network Adapter 2	Second ethernet Eth1	Cloud1 can be bridged with your EVE second ethernet port to achieve connection to another network or device. The IP address is not required to be configured on it. It will act like a pure bridge your external connection with EVE lab node.
Cloud2	Pnet2	bridged	Network adapter 3	Network Adapter 3	Third ethernet Eth2	Same as Cloud1
Cloud3	Pnet3	bridged	Network adapter 4	Network Adapter 4	Fourth ethernet	Same as Cloud1
Cloud4-9	Pnet4-9	bridged	Network adapter 5-10	Network Adapter 5-10		Same as Cloud1

If some of the clouds (e.g. Cloud1) are bridged to another ethernet (VMnet) you can connect your EVE lab to an external VM or physical device (like e.g. a switch, IP phone or access point).

A For ESXi make sure that you have set Promiscuous mode security settings on the vSwitch and Port group to Accept. Please refer to section 9.6

Page 151 of 272 © EVE-NG LTD



The next sections will explain how you can use Cloud networks in EVE to connect to other external (e.g. VMWare) VMs or physical devices.

9.9 Connecting external VM machines to the EVE Lab

9.9.1 ESXi VM machines

External ESXi VM machines can be connected to EVE labs using cloud interfaces.


NOTE: A single Cloud interface can be used to connect more than one external VM to the EVE lab.

Example: Connecting a Web Security Appliance (WSA) to the lab using the Cloud1 interface.

Step 1: Create a new or use an existing portgroup on your ESXi and assign it to EVE and WSA VMs as shown below. Make sure you have set Promiscuous mode on the vSwitch (portgroup WSA-MGMT) to Accept.

▲ NOTE: VM machines must be in a powered off state to assign network interfaces.


Portgroup WSA-MGMT (with vSwitch5 as parent) settings:




© EVE-NG LTD Page 152 of 272



Parent vSwitch5 settings:



EVE and WSA VMs settings




EVE Lab connected to the WSA (Cloud1)

- ▲ NOTE: ESXi WSA VM obtained the IP 192.168.10.3 from the DHCP pool on the lab switch. The gateway is 192.168.10.1
- NOTE: The Firefox Docker node user for management obtained the IP 192.168.10.2 from the DHCP pool configured on the lab switch.

© EVE-NG LTD Page 153 of 272





9.9.2 VMWare workstation machines

External (meaning not running inside EVE) VMWare workstation machines can be connected to EVE labs using cloud interfaces.


NOTE: A single Cloud interface can be used to connect more than one external VM to the EVE lab.

Example: Connecting Web security Appliance (WSA) to the lab using **Cloud2** interface.

NOTE: VMs must be in a powered off state to assign network interfaces.

Step 1: Open your VMWare Workstation Virtual Network Editor and configure the VMnet interface for the Cloud and WSA VMs. If necessary add a new VMnet. The example below is showing VMnet2 Settings in VMWare workstation. DHCP must be disabled for VMnet2.


Virtual Network Editor settings:



© EVE-NG LTD Page 154 of 272




EVE and WSA VMs settings



EVE Lab connected to the WSA (Cloud2)

- ▲ NOTE: ESXi WSA VM obtained the IP 192.168.10.3 from the DHCP pool on the lab switch. The gateway is 192.168.10.1
- NOTE: The Firefox Docker node user for management obtained the IP 192.168.10.2 from the DHCP pool configured on the lab switch.



© EVE-NG LTD Page 155 of 272



9.10 Connecting EVE Lab to a physical device

9.10.1 ESXi EVE

To connect a physical device (e.g. router, switch) to an EVE lab over a cloud interface, we have to bridge the ESXi NICs ethernet port to a VMnet interface.


- IMPORTANT NOTE: Make sure that you have set Security Policy (Promiscuous mode, forged transmits and MAC changes) settings on the vSwitch and Port group to Accept.
- ▲ IMPORTANT NOTE: If you are building trunk between EVE lab node to real Switch, please make sure you have set your ESXi vSwitch interface to accept all vlans. Reference: https://kb.vmware.com/s/article/1004074
- ▲ IMPORTANT NOTE: For EVE VMs running on ESXi, with NIC Teaming Network, please follow the steps below to edit the reverse path settings
 - From the Navigator window select Manage > System > Advanced settings.
 - Scroll down or use the search bar to go to the Net.ReversePathFwdCheckPromisc option.
 - Select Net.ReversePathFwdCheckPromisc and click Edit option.
 - ❖ In the Edit option Net.ReversePathFwdCheckPromisc window update the New value field to 1 and click Save.

The Example below is showing ESXi Server settings of the virtual network bridged to the physical interface.

Logical chain of the networking bridge:

EVE Lab Cloud0 →Portgroup "Management 90 UD"→vSwitch 1→Physical Adapter eth1


vSwitch1 settings bridged with Server Ethernet port vmnic1 (physical adapter)



© EVE-NG LTD Page 156 of 272




Portgroup "Management 90 UD" Settings associated with vSwitch1



EVE VM Settings

EVE VM Cloud0 is connected to Portgroup "Management 90 UD"




EVE Lab Connected to a physical device

Physical Topology

Cisco 887M device port Fastethernet 3 is physically connected to Server port eth1.

© EVE-NG LTD Page 157 of 272





EVE Lab Topology

EVE lab switch port G0/0 is configured as trunk and connected to Cloud0 over bridged chain to the physical Cisco 887M Router switchport Fastethernet 3




9.10.2 VMWare workstation EVE

Similar to the ESXi connection, it is recommended to have a second ethernet interface on your PC. It can be a USB ethernet extender as well. Not all ethernet adapters fully support a layer2 connectivity over it. MS Windows OS itself strips off any tags added to the packet. Even if your NIC supports 802.1q VLAN tagging, Windows 10 strips these tags off. The example below will show a Windows 10 host connected to a physical 3750G-24 switch. The Windows 10 Host has an Intel (R) PRO/1000 PT Dual port server adapter and is bridged with VMWare workstation (version 14) VMnets.

Virtual Network Editor Settings, Bridged VMnet interfaces with Real NIC Ports

© EVE-NG LTD Page 158 of 272






EVE VM Settings. Network adapter is bridged to VMnet0 (ethernet Intel Pro 1), and Network adapter 2 is bridged to VMnet1 (ethernet Intel Pro 2).

Responding cloud interfaces on EVE VM:

Cloud0→Network Adapter→VMnet0→IntelPro


Cloud1→Network Adapter 2→VMnet1→IntelPro#2




Physical connection scheme and VMware bridging.

© EVE-NG LTD Page 159 of 272





EVE Lab scheme.



The following solution allows Windows hosts to transmit tagged packets over ethernet. This has been used in the example above.

▲ Warning. You are making changes to your Windows registry files! This is at your own risk

 $\underline{\text{https://www.intel.co.uk/content/www/uk/en/support/articles/000005498/network-and-i-o/ethernet-products.html}$

9.10.3 Bare metal server EVE

A physical server usually has more than one ethernet port, free ports can be bridged with EVE clouds and used for external connections. EVEs internal interface settings are already bridged in order, pnet0-9 are mapped to eth0-9. Refer to the bridging table in section 9.7

```
# Cloud devices
iface ethi inet manual
auto pneti
iface pneti inet manual
bridge_ports ethi
bridge_stp off

iface eth2 inet manual
auto pnet2
iface pnet2 inet manual
bridge_ports eth2
bridge_stp off
```

```
cat /etc/network/interfaces
```


Basically, your servers physical port eth0 is bridged to pnet0 which is Cloud0 in your labs, eth1 is bridged to pnet1 which is Cloud1 in your labs (and so on). Refer to the bridging table in section 9.7

The example below shows how to connect a bare-metal EVE server with a physical Cisco 3750E switch.

© EVE-NG LTD Page 160 of 272



Physical connection topology:



The EVE lab switch's CDP neighbour is the 3750E switch's port Gig 1/0/25: A trunk has been configured between the EVE lab switch and the physical 3750E switch.

© EVE-NG LTD Page 161 of 272





10 Advanced EVE Lab features

10.1 Lab design objects

EVE Pro has drawing elements integrates to add drawings and text information to the lab topology. Objects can be placed on the topology in two ways.

Example below, EVE lab with design elements:





10.1.1 Custom shape

There are three custom shapes that can be added to the topology: square, round square and circle (sphere).

© EVE-NG LTD Page 162 of 272



Type: Square, round square or circle

Name: This field can be filled with your preferred shape's name. If the field is left empty, EVE will generate a name for the shape.

Border type: Two options: line or dashed



Border width: Increase or decrease the width of the border. This can be edited later in the "Shape Edit" menu.

Border colour: Allows you to choose a colour for the shape's border. This can be edited later in the "Shape Edit" menu.

Background colour: Allows you to choose a colour to fill your shape with. This can be edited later in the "Shape Edit" menu.

Example: Added a circle and square on the topology. Shapes can be moved around the topology drag and drop style (click and move with mouse).



10.1.2 Resize square or circle objects

Move your mouse over the right bottom corner of the object until a corner symbol appears. Left click and drag your mouse to change object size or style (rectangle, sphere)




10.1.3 Text

It is also possible to add text or other MS Office objects to your EVE topology. Rich HTML Office option allows you to copy texts from MS Word, Excel or Visio.




© EVE-NG LTD Page 163 of 272






Example: Excel table on topology:





Example: text objects added to the topology.

Example: Visio object added to the topology



10.1.4 Add picture to the topology

Custom images may be added by using HTML editor:


Step 1: Add a text object to the topology and press Image button for import.

© EVE-NG LTD Page 164 of 272






Step 2: User browse to import your image.



Step 3: Double click on object you wish to resize, then change width and height.




10.1.5 Custom object linking with telnet or other protocol

This feature allows you to link your eve topology object with external source. It can be web site or other protocol like Telnet to call out console for external object.

Step 1. Add the text or picture using HTML editor. Sections 10.1.3 or 10.1.4.

© EVE-NG LTD Page 165 of 272







Example: Custom icon added from MS Visio.

Step 2. Position your object in place where you want it to be.


Step 3. Highlight text or activate object.



Step 4. Use link button to assign custom protocol for your object. Example: Protocol Other, type in URL: **telnet://10.1.1.10**



Step 4. Tab Target, Example: Target/New Window



© EVE-NG LTD Page 166 of 272



Step 5. OK for Save.


NOTE to edit picture object assigned with link, use mouse mark area of object and it and double click on area beside object.



10.1.6 Line object

Line object allows you to draw and design lines on the topology.

Step 1. Add a Line object to the topology



Width: Increase or decrease the width of the line. This can be edited later in the "Shape Edit" menu.

Arrow Style: Allows you to make arrows to your Line object. Single arrow, Double arrows or no Plain. This can be edited later in the "Shape Edit" menu.

Paint Style: Allows you to solid or dashed style for line. This can be edited later in the "Shape Edit" menu.

Line Style: Allows you to choose a style Straight, Bezier, Flowchart or StateMachine for the line. This can be edited later in the "Shape Edit" menu.

Line colour: Allows you to choose a colour for the line. This can be edited later in the "Shape Edit" menu.

Line label: Allows you to add a label on the line. This can be edited later in the "Shape Edit" menu.

Example, Dashed, Bezier, double arrow line with label:

BGP Peer

Positioning and moving line object. Line object has invisible connection points at the ends. Use mouse to find that point, drag and drop move line connection point to your preferred lab location. Use mouse to move other line endpoint on lab location.

BGP Peer

To move all line, use CTRL to mark line endpoint and move line over topology to position it.

Edit Line object. Right click on line to call out edit window:



© EVE-NG LTD Page 167 of 272





10.1.7 Nodes connection links design

Refer Section 8.1.5

10.1.8 Cloning objects and overlay positions

Right click on the object you want to clone and choose "Duplicate". You can also change the object's overlay position using the "Send to Back" or "Send to front" options.



10.1.9 Objects Editing

Right click the object and choose "Edit" for additional options.



At the bottom of the "Topology Canvas" page, additional object options will appear



Z-index: Used to change the object's overlay position on the "Topology Canvas." An object with a higher numerically valued z-index will cover an object with a lower numerically valued z-indexed.

Example: The blue object has a z-index of -1 and the orange object's z-index is 0. Orange object is top over blue object.


Border width: Used to change the object's border width.

Border type: Used to change the border style of the object between solid and dashed.

Border colour: Used to change the colour of the object's border

Background colour: Used to change the background colour of the object

Transparent: Turns off background colour (filling) and makes the object transparent.



© EVE-NG LTD Page 168 of 272



Rotate: Used to rotate the object on the



topology.

Name: Used to change the object's name.

To save the object, press Save (green button).



10.1.10 Lock objects movement

The "Lock Lab" feature prevents objects from being moved around on the canvas (among other things). For more information about this feature, refer to section 7.9.14.

10.2 Custom design logical topology

EVE Pro includes a feature to upload your own custom topology picture and map nodes to it for easy access.


10.2.1 Custom design upload

Before you upload a custom picture in the lab, make sure it is in .png or jpg format with resolution 130-150x130-150 pixels.


TIP: It is best is to create a topology in the MS Visio and after convert it to the .png picture format with resolution 140x140.



Step 1: Open "Add an Object" and then "Pictures" from the left sidebar or right click on a free area on topology canvas and hit "Add Picture."



Step 2: Browse your PC for a .png or .jpg file and hit "Add".



Once the picture is added to the topology canvas, the sidebar will display a new option: "Logical maps"

© EVE-NG LTD Page 169 of 272



Step 3: Open the "Logical maps" menu item.



Pictures window management

	Delete uploaded picture from the lab
Ø	Image Map: Map nodes to places in the picture
Topology	Display uploaded picture. Work with lab and custom topology
	Zoom/unzoom uploaded custom topology
*	Makes the window transparent to see the "Topology Canvas" behind it. Clicking again returns to the normal view.
×	Close "Pictures" window.


10.2.2 Custom topology mapping

This feature allows you to map the lab nodes to your custom topology picture.


Step 1: Open the Image Map window:



Step 2: Select a node, from the dropdown menu, that you want to map to the topology.




Step 3: Move your mouse over a node icon on the "Image Map" and click to map it. The grey circle means that the node is mapped.



Step 4: Continue mapping the rest of the nodes.

© EVE-NG LTD Page 170 of 272





Step 5: OPTIONAL. You can also add a mapping for a device external to your EVE server in order to telnet, VNC, or RDP to it. This way you can open sessions to all your devices (whether external or internal) in one place.



Change image map adding protocol, IP and port.



Step 6: Save your mapping and refresh the browser with F5.



10.2.3 Delete topology or mapping

To delete a single node mapping, right click on node mapping circle and click "Delete."



To delete the entire custom topology, click delete.



10.3 Multi-configuration sets export feature

Eve Professional/Learning Center includes a "Multi-configuration Set" feature that allows you to save and manage multiple sets of configurations in a single lab. The "Configuration Export" and "Startup-configs" features will allow you to set these saved configurations as startup configs for your nodes when they boot.

▲ IMPORTANT NOTE: Before you start using the "Multi-configuration Set" feature, you must complete at least one configuration export.


© EVE-NG LTD Page 171 of 272





Nodes will be greyed out without the option to enable "Startupconfigs" until you complete at least one configuration export for each node.

Node boot order:



NVRAM: NVRAM is used as writable permanent storage for the startup configuration. During the boot process, the node will always check NVRAM for a saved configuration. Saving the configuration to NVRAM requires a vendor specific command. Cisco: copy run startup (wr), Juniper: commit, etc. It is MANDATORY to save a node's configuration before you can export it.

Exported configuration: A node configuration that has been exported from the node. It can be used to backup configurations or to set them as startup-configs.

Wipe node: Wiping a node will erase the NVRAM (running config) or the temporary image snapshot, depending on the type of node. Upon a successful wipe, the node will boot with the factory default configuration or the configuration included in the base image you are using. If you have the "Startup-config" feature enabled for the node, then it will boot with the chosen config set. You must wipe a node after changing certain node template settings like the image or startup-config. You also must wipe the node the first time you want to enable the "Startup-config" feature.

Factory default configuration: The base configuration that is applied from the manufacturer.

10.3.1 Supported nodes for configuration exports

Cisco Dynamips all nodes

Cisco IOL (IOS on Linux)

Cisco ASA

Cisco ASAv

Cisco CSR1000v

Cisco Catalyst 8000v

Cisco Catalyst 9000v

Cisco Nexus 9K

Cisco Nexus Titanium

© EVE-NG LTD Page 172 of 272



Cisco vIOS L3

Cisco vIOS L2

Cisco Viptela vEdge, vSmart, vBond, till version 18.4 only, version 19.x and later is not supported due implemented password setup feature on the first boot.

Cisco XRv

Cisco XRv9K

Juniper VRR

Juniper vEX

Juniper VMX

Juniper vMX-NG

JunipervQFX

JunipervSRX

Juniper vSRX-NG

Mikrotik

PFsense FW

Timos Alcatel

vEOS Arista

Aruba CX Switch


10.3.2 Startup config management

10.3.2.1 Global commands



Configurations can be managed via the "Startup-configs window which can be accessed from the sidebar menu while on the Topology page.

Topology page, More Options:



Export all CFGs – Exports all supported node configurations.

Set nodes startup-cfg to default configset- Sets all supported nodes to boot from the default configuration set.

Set nodes startup-cfg to none - Sets all supported nodes to boot from NVRAM configuration.

Delete default configuration set. Warning, this will delete your exported default configuration set for all nodes.

10.3.2.2 Individual node commands

Select node, right click




Wipe: Wipes the NVRAM for a single node

Export CFG: Exports the configuration for a single node

© EVE-NG LTD Page 173 of 272



10.3.2.3 Multiple selected nodes commands



Wipe Selected: Wipes the NVRAM for selected nodes

Export all CFGs: Exports the configuration for selected nodes


Set nodes startup-cfg to default configs set: Set selected nodes to the default config set

Set nodes startup-cfg to none: Set nodes to boot from NVRAM or from factory default if wiped.

Delete nodes startup cfg: Delete selected node's startup cfg. (clean default set)

10.3.2.4 Startup-configuration window


No configuration exports or manual configs loaded for nodes



Startup-configs are exported and the "Configuration Export" feature can be used.



10.3.2.5 Startup-config window information



© EVE-NG LTD Page 174 of 272



№ R1	No configuration is available for node. Grey node
№ R1	Configuration is available and can be used. Blue node. Exported configuration persist
№ R2 OFF	Configuration persist but it is disabled. Node will boot from NVRAM or factory default if it is wiped
№ R1 / ON	Configuration persists and node will boot from the configuration after being wiped
CONFIG SET Rane Rine And Canal	Add new config set.
CONFIG SET Note harmod Tota Cancel	Rename config set. The Default Config Set cannot be renamed.
★ Config Set IP Addressing ✓	Select a Config Set and delete it. You cannot delete the Default Config Set. The Default configuration set can be cleaned using the sidebar / More options / Delete default configuration set
±	Upload configuration set from your local PC
*	Download configuration set to your Local PC
•	Apply Config Set button: Sets all nodes to boot from the chosen config set.
,	Config Reset button: Sets all nodes to boot from none. Node will check boot order. If the Wipe function is used, nodes will boot from factory default.
SV2 COM Last configuration change at 19:52:1 wession 15:4 weslon 15:4 service timestamps debug datetime	Individual node export or import configuration. Configuration export/import file format is .txt.

© EVE-NG LTD Page 175 of 272






Ace Editor. Different vendor configuration edit option. Just Text visual format.

10.3.3 Export Default configuration set

NOTE: The default configuration set is hardcoded. It is mandatory to export a nodes configuration you can start building custom configuration sets.

Example:




Step 1: MANDATORY: Configure your nodes and make sure you applied the vendor specific command to save the running configuration to NVRAM. If you do not save the configuration, it will not be exported and in the notification area, you will receive an error message stating the node cannot be exported.

In this example the nodes have been configured with hostnames only and the configurations have been saved to NVRAM.

Step 2: Chose any method to export configurations to the Default Config Set. You can use export a single node, a group of nodes, or all nodes. Only supported nodes configurations will be exported.

Step 3: In the example below a group of nodes were selected to export configurations.





Default configuration set is completed. The notification area will display "Export All: done" when complete.

NOTE: you can configure your nodes with your preferred configuration and make it the default configuration set.


© EVE-NG LTD Page 176 of 272



10.3.4 Boot nodes from exported Default config set

Step 1: Stop all nodes

Step 2: Open sidebar and click Startup-configs. Make sure your config is set to default and the nodes config switch is green (switch on/off beside node). Press the green "Apply Config Set" button (Set all nodes to selected config set) and all your nodes will boot with the default config set after wiping them.



Step 3: Wipe nodes. For more information refer to section 8.1.3

Step 4: Start nodes

10.3.5 Export new custom config set


This section will describe how to create a new custom configuration set for the same example above.

⚠ Make sure your nodes are running and booted from the default set.

Step 1: Create new custom named (e.g. "IP Addressing") configuration set, Press Add new config set.



Name it and press Add.



The new configuration set is created.

▲ NOTE: It will duplicate the default configuration set under your IP Addressing config

Step 2: Select newly created Config set IP Addressing and hit the green confirm button (Set all nodes to selected config set) on the right.

© EVE-NG LTD Page 177 of 272



Step 3: Make sure your nodes have the Startup-config slider switched to "ON" and verify the config set menu has the "IP Addressing" set selected.




Step 4: Return back to your lab and continue configuring nodes until your preferred configuration is complete. In this Example, the IP addresses are configured on the nodes.

Step 5: IMPORTANT: YOU MUST save the configuration on all nodes, even if the configuration was not changed.

Step 6: Use any method (individual, group or all) to export the new configurations to the IP Addressing set.

Step 7: You can verify that the configs were exported by re-opening the "Startup-config" window.

Make sure the correct config set is selected, and check if the configuration is exported for the node or nodes.



Repeat steps 1-7 of this section for the next configuration set.

10.3.6 Edit exported configurations

It is possible to edit your configurations for the nodes manually.


Step 1: Select a config set and apply it with the green confirm button (Set all nodes to selected config set) on the right.



Step 2: Select the node you want to edit the configuration of and make your changes. Click "Save" when you are finished.

© EVE-NG LTD Page 178 of 272





Step 3: Apply the config set to all nodes with the green "Apply Config Set" button on the right (Set all nodes to selected config set).



NOTE: you can manually copy/paste any configuration into the config set editor and apply it to your node. Make sure your configuration interfaces match the lab node's interface names.

10.3.7 Set lab to boot from config set

To set your lab nodes to boot from the exported configuration, follow the steps below:

Step 1: Wipe nodes. Refer to section 8.1.3 for information about wiping nodes and the order of operations during boot.

Step 2: Open the "Startup-configs" window from the left sidebar.

Step 3: Select your preferred config set and apply it by pressing the green "Apply Config Set" button on the right (Set all nodes to selected config set).



Step 4: Start nodes.

10.3.8 Set lab to boot from none

To reset your lab nodes' configuration to factory default follow the steps below:

Step 1: Wipe nodes. Refer to section 8.1.3 for information about wiping nodes and the order of operations during boot.

Step 2: Open the "Startup-config" window from the left sidebar

Step 3: Press the red "Config Reset" button on the right (Set all nodes to no startup-config).




Step 4: Start nodes

© EVE-NG LTD Page 179 of 272



10.3.9 Delete a config set

Select the config set you want to delete and click the "Delete" button. You cannot delete the default config set.



10.3.10 Rename a config set

Step 1: Select the config set you want to rename. Change the name and hit "Save." You cannot rename the default config set.



10.3.11 Export a config set to your local PC

It is possible to export configuration sets to your local PC.

Step 1: Select the config set you wish to export.



Step 2: Save it on your local PC.

NOTE: You can open this archive and edit your node configs manually. Archived configs are saved in txt format. After editing you can archive it back to .zip format and import it in EVE.


10.3.12 Import config set from local PC.

It is possible to import config sets to your lab.



© EVE-NG LTD Page 180 of 272





Browse to the file on your PC, select the archive or config set and upload it.

Uploaded config sets without a Name will appear in the config set menu with the name "Import". To rename config sets, refer to section 10.3.10


10.3.13 Export a single nodes config to your local PC

Open the "Startup-configs" window from the Side bar. Select the node that you want to export the configuration of and click the "Export" button.



10.3.14 Import a single nodes config from your local PC

Open the "Startup-configs" window from the sidebar. Select the node that you want to import the configuration to and click the "Import" button. Browse to the file on your local PC and click "Upload."



NOTE: The configuration must be in txt file format.

10.3.15 Set lab nodes to boot from different config sets

The "Multi Configuration set" feature allows you to set nodes to boot from different config sets in the same lab.


Option 1: Open the "Nodes" list from the left sidebar. Choose your node and select a config set from the dropdown. Stop the node, wipe it and start it again. Your node will boot from the selected config set.

© EVE-NG LTD Page 181 of 272





Option 2: Stop the node, right-click on the node and click "Edit." Select your preferred config set for the node and click "Save."



10.3.16 Lab config script timeout

Lab config script timeout is used when nodes are waiting to boot from a config set. The node will literally wait during boot until the configuration is applied from the config set.

Hit "More actions" and then "Edit lab" from the sidebar. Set the config script timeout in seconds. By default, this timer is set to 300 seconds for new labs.



10.4 Lab Timer

For self-controlled lab timing, EVE Pro has integrated a "Lab Timer" feature.

10.4.1 Set the Lab Countdown Timer

Step 1: Click "More Options" and then "Edit Lab" from the sidebar.

Step 2: Set the "Lab Countdown Timer" in seconds for the time you wish to display on the topology and confirm by clicking "Save". 7200 seconds = 120 minutes.



Step 3: To start your lab, be sure all nodes are running.

Step 4: Hit "Lock Lab" from the sidebar. A red sign means that the lab is locked.

01:59:57

Step 5: When ready to start, click "Refresh Topology" from the sidebar. The countdown timer will be displayed on the "Topology Page" in the top left corner.

© EVE-NG LTD Page 182 of 272



10.4.2 **Stop the Lab Countdown Timer**

Step 1: Click "Unlock Lab" Grey means that the lab is unlocked.



Step 2: Hit "Refresh Topology" from the sidebar

▲ NOTE: The lab timer does not stop nodes or disconnect sessions from the lab.

10.5 Lab Tasks

Lab task or workbook creation feature.

10.5.1 Creating a new simple task

Step 1: On the side bar click on "Lab Task(s)" to open the Lab Task(s) management window.



Step 2: Click on the "+" sign to create a new task. Enter the name of the task name and click on "Add" to create the task.





10.5.2 Edit a simple task


Step 1: Press the edit button next to the name of the newly created task.



Step 2: Use the rich text editor Window to create your Task / Workbook. It is a recommended option to copy/paste task content from MS Word. Save your Task content by clicking on the "Save" button.


Page 183 of 272 © EVE-NG LTD





10.5.3 Create a multi tabs task (task on multiple tabs/pages)

Step 1: Click on the "+" sign to create a new task. Enter the name of the task name and click on "Add" to create the task.



10.5.4 Edit a multi tabs task (task on multiple tabs/pages)


Step 1: Press the edit button next to the name of the newly created task.




Step 2: Click on the "Insert tabs" button.

© EVE-NG LTD Page 184 of 272






Step 3: Enter the name of your new task group and choose the number of tabs (must be between 2 and 9). Tab names can be changed later.



Step 4: To save your your tabbed task, press "Save".



10.5.5 Edit tabs (Multi tabbed task).


Step 1: Activate the tab for which you want to edit its content and press the edit button.

© EVE-NG LTD Page 185 of 272






Step 2: Rename your tab,



Step 3: Press the "Show Blocks" button, this will help find the right place to create the task tab content. Make sure that you are copying or creating the tabbed task content into the correct place (Tab 1 Content)

NOTE: It is strongly recommended to use "full screen" for the rich html text editor when you are working with tabbed tasks. Press the "full screen" button to work with tasks. Press it again to exit full screen mode.




Step 4: Save your modified task by clicking on "Save". To edit another tab, repeat steps 1-3.

10.5.6 Create a task with your PDF workbook

Step 1: create new Task and name it and press Add:

© EVE-NG LTD Page 186 of 272






Step 2: Press edit Task and locate PDF button, Press it



Step 3: Navigate to your pdf document, Press OK.



Step 4: To view your uploaded book, use, Side Bar/Tab Tasks/your taskname



© EVE-NG LTD Page 187 of 272




10.5.7 Create a task with Online document (PDF or HTML)

Online document or web site task (https ONLY, iFrame allowing use Secure http only)


Step 1: Have ready your link to online web site or document. Example:

https://www.eve-ng.net/images/EVE-COOK-BOOK-latest.pdf

Step 2: create new Task and name it and press Add:




Step 3: Press edit Task and locate iFrame button, Press it



Step 4: Type the path to your online document, set Width to 100%, and Height resolution to 10000.


The path location is https://www.eve-ng.net/images/EVE-COOK-BOOK-latest.pdf, which prepared in Step 1. Press OK for iFrame properties and Save Task, Press Save



© EVE-NG LTD Page 188 of 272



Step 5: To view your uploaded book, use, Side Bar/Tab Tasks/your taskname



10.5.8 Delete a task

Step 1: From the Side bar click on "Task Management":



Step 2. Click on the delete symbol next to the task name which you want to delete.



© EVE-NG LTD Page 189 of 272



11 Wireshark capture

All EVE-NG Professional and Learning Centre console types have the integrated Wireshark capture feature. This means that it is not necessary to have Wireshark installed on the client machine you are using to access EVE with.


EVE-NG Professional currently supports ethernet interface capturing only.


11.1 Native Console Wireshark capturing

Step 1: Right click on the node you wish to capture, choose "Capture" and then the relevant interface. The capture will open in an HTML session. EVE-PRO supports capture for ethernet and serial interfaces.

Select the interface frame type which will be captured:

- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames: HDLC, PPP or Frame Relay.






Step 2: To save the captured file to your client PC, stop the capture and choose File/Save As

© EVE-NG LTD Page 190 of 272





Step 3: Choose the location where you want to save the captured file

IMPORTANT:

/nobody/thinclient_drives/GUACFS/Download


Enter a name for your captured file and press Save. Your browser will offer to download your capture fil and save on your local PC. Refer Section 11.2

11.2 HTML5 Console Wireshark capturing

Step 1: Right click on the node you wish to capture, choose "Capture" and then the relevant interface. The capture will open in an HTML session. EVE-PRO supports capture for ethernet and serial interfaces.


Select the interface frame type which will be captured:

- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames: HDLC, PPP or Frame Relay.




© EVE-NG LTD Page 191 of 272





Step 2: To save the captured file to your PC, stop the capture and choose File/Save As



Step 3: Choose the location where you want to save the captured file


© EVE-NG LTD Page 192 of 272




IMPORTANT:

/nobody/thinclient_drives/GUACFS/Download

Enter a name for you captured file and press Save.



Step 4: A window will open that will allow you to save your captured file on your client PC. If the client PC's browser is set to download automatically, your captured file will be saved in the default browser download folder.



© EVE-NG LTD Page 193 of 272





11.3 HTML5 Desktop Console Wireshark capturing

Step 1: Right click on the node you wish to capture, choose "Capture" and then the relevant interface. The capture will open in an RDP session. EVE-PRO supports capture for ethernet and serial interfaces.


Select the interface frame type which will be captured:

- Ethernet for Ethernet, Fast Ethernet, Gigabit Ethernet.
- Serial interface frames: HDLC, PPP or Frame Relay.






Step 2: Stop capturing with the STOP button.



Step 3: Chose File/Save As



© EVE-NG LTD Page 194 of 272




Step 4: Chose the path to save the captured file,


IMPORTANT:

/nobody/thinclient_drives/media/nobody/thinclient_drives/GUACFS/Download/

Enter a name for captured file. Press Save.



Step 4: A window will open that will allow you to save your captured file on your client PC. If the client PC's browser is set to download automatically, your captured file will be saved in the default browser download folder.



© EVE-NG LTD Page 195 of 272



12 Thinclient File Exchange

NOTE: Thinclient file exchange feature is available for HTML5 or desktop HTML5 consoles only. Make sure you are logged in EVE with one of it.


The Thinclient file exchange feature allows you to transfer files between your native client workstation and the integrated Docker Desktop. It is used when managing EVE via HTML5 consoles. This feature eliminates the need for file transfer software on your client workstation and makes it very easy to import/export labs or download Wireshark captures.

12.1 Thinclient files downloading

The Thinclient file exchange feature allows you to download files from your EVE Server over an HTTP/HTTPS session to your client PC. Examples below will show you how to download exported lab files. This feature is not restricted to just lab files or Wireshark captures. It can be used to download or upload any miscellaneous files you may need.

Example: HTML5 console to server-gui Docker node: We want to export our test.txt file and download it to our client PC over HTML5.






Step 2: Navigate to the desktop of the HTML5 server-gui station and double click thinclient_drives and navigate to: thinclient_drives/GUACFS/Download/


Step 3: Drag and drop the test.txt file from right to left.

© EVE-NG LTD Page 196 of 272





Step 4: A window will open that will allow you to save your captured file on your client PC. If the Native PC's browser is set to download automatically, your selected file will be saved in the browsers default download folder.



NOTE: Please refer to section 11 for downloading Wireshark capture files from EVE HTML5 consoles.

12.2 Thinclient File upload


Sometimes it is necessary to upload files to your EVE labs. The Thinclient file exchange feature allows you to upload files from your client PC to the EVE HTML5 server-gui station. The

© EVE-NG LTD Page 197 of 272




example below will show you how to upload a text file to the EVE HTML5 server-gui station. Any other files can be uploaded the same way.

Step 1: Adjust your browser so that you can see it and the file that you want to transfer.




Step 2: On the EVE HTML5 Desktop navigate to: thinclient_drives/GUACFS/ and drag and drop the file from your client PC to opened location on HTML5 Desktop.




Step 3: Next you will see a notification in the bottom right corner.

© EVE-NG LTD Page 198 of 272





Step 4: To finish the operation and see the uploaded file in the HTML desktop station, press the refresh button. Our Text file SW.txt has been uploaded.



12.3 Other Thinclient file operations


Files that have been uploaded via the thinclient feature can also be transferred to nodes inside your EVE labs via TFTP. In the example below we have uploaded a config file (sw.txt) and would like to transfer it to node R1.

Step 1: Add the **eve-gui-server** docker node to your lab and edit its settings. Set the console type to RDP and configure the IP address settings (DHCP or static) accordingly so that the


© EVE-NG LTD Page 199 of 272



docker node can reach the destination node (R1 in this example). For Docker IP addressing please refer to section 13



Step 2: Click on the **eve-gui-server** docker node to open an RDP session.




Step 3: Open the **thinclient_drives** location where you uploaded your file to:


/thinclient_drives/media/nobody/thinclient_drives/GUACFS/

Next, drag and drop your file to the desktop folder named TFTP.


© EVE-NG LTD Page 200 of 272







Step 4: Open the destination node's (R1) console and use the tftp command to copy your file:



© EVE-NG LTD Page 201 of 272



13 Dockers

13.1 EVE integrated docker stations

EVE-NG Professional and Learning Centre edition have integrated Docker stations that allows your server to use its resources more efficiently. Dockers offer the advantage of not having to duplicate processes already running on the host system. With a Docker, you run only the processes you need for the hosted application. In comparison, virtual machines have to run a complete guest operating system, including many of the same processes that are already running on the server host.

▲ IMPORTANT NOTE: EVE Docker stations for html console access are using network 172.17.0.0/16. Please avoid use this network on the EVE management or other clouds or interfaces.

13.1.1 Docker Machines

eve-gui-server (default)

- Fully featured Linux workstation with integrated Thinclient. For more information on the Thinclient operation please refer to section 12.
- napalm
- ansible
- python
- iperf3
- RDP console
- DHCP or Static IP address
- WWW Server (web page home directory www is located on desktop)
- TFTP Server (for access to TFTP server, root/eve or nobody/eve, home directory TFTP is located on desktop)
- FTP server (for access to FTP server, root/eve, home directory for ftp is root)
- Java Integration for ASDM access to Cisco ASA/IPS. For access to ASDM where Java is required, please follow this reference link:

https://192.168.100.5/admin/public/asdm.jnlp

Where 192.168.100.5 is the ASA IP for ASDM connection


NOTE: Older ASA require to configure extra SSL encryption to communicate with Java on the docker station. ASA 9.1.5 CLI:

ssl encryption aes256-sha1

Example: Access to ASAv ASDM from Docker server-gui station

© EVE-NG LTD Page 202 of 272





eve-firefox (default)

- A Docker for hosting a Mozilla Firefox browser. Useful for accessing another nodes management interface using http or https. The browser already has Java integrated so that you can utilize GUIs that require it, like ASDM for Cisco's ASA.
- RDP console
- DHCP or Static IP address

eve-wireshark (default)

- Fully featured Wireshark workstation with integrated Thinclient. For more information on the thinclient operation please refer to section 12.
- RDP console

eve-chrome (extra install, section 13.5)


- A Docker for hosting a Google Chrome browser. Useful for accessing another nodes
 management interface using http or https. The browser already has Java integrated so
 that you can utilize GUIs that require it, like ASDM for Cisco's ASA.
- DHCP or Static IP address

eve-ostinato (extra install, section 13.5)

- A Docker for hosting a Ostinato 0.9 GUI. Fully featured Ostinato 0.9 packet generator and network traffic generator machine
- DHCP or Static IP address
- Fully featured Ostinato GUI

© EVE-NG LTD Page 203 of 272






13.1.2 Docker DHCP IP address setup

EVE integrated Docker stations have two options for setting an IP address.

DHCP IP address option.

Step 1: Add the node to the topology and make sure the DHCP option is **enabled** under the edit node window. Refer to section 13.2 for the correct console type.

Step 2: Ensure the docker's DHCP request can reach a DHCP server either in your lab or externally through a Cloud Network like Cloud0.



13.1.3 Docker Static IP and MAC address setup

Step 1: Add the node to the topology and make sure the DHCP option is **disabled** under the edit node window Reference section 13.2 for the correct console type.

Step 2: On the left sidebar menu open Startup-config and use the example syntax below to set the ip for your Docker node. Make sure you are using the exact syntax for your static IP setup:

© EVE-NG LTD Page 204 of 272




```
# Set ip address and Default route
ip addr add 10.100.100.103/24 dev eth0 || true
ip route add default via 10.100.100.1 || true

# Set DNS server
cat > /etc/resolv.conf << EOF
nameserver 8.8.8.8
EOF</pre>
```

Step 2.1 (Optional): On the left sidebar menu open Startup-config and use the example syntax below to set the custom MAC for your Docker node. Make sure you are using the exact syntax for your static MAC setup:

```
# Set ip address and Default route
ip link set dev eth0 address XX:XX:XX:XX:XX:XX || true
ip addr add 10.100.100.103/24 dev eth0 || true
ip route add default via 10.100.100.1 || true

# Set DNS server
cat > /etc/resolv.conf << EOF
nameserver 8.8.8.8
EOF</pre>
```



Step 3: Press the Save button below and switch the node to boot from the startup-config.

13.1.4 Docker multi-interfaces setup

Step 1: Add the node to the topology and make sure the DHCP option is **disabled** under the edit node window Reference section 13.2 for the correct console type.

Step 2: On the left sidebar menu open Startup-config and use the example syntax below to set the ip for your Docker node. Make sure you are using the exact syntax for your static IP setup. It is recommended to add static routes under interfaces to reach specific networks if required.

```
# Set ip address eth0
```

© EVE-NG LTD Page 205 of 272



```
ip addr add 192.168.1.200/24 dev eth0 || true
ip route add default via 192.168.1.1 || true

# Set ip address eth1
ip addr add 172.16.1.201/24 dev eth1 || true
# Set static route for eth1
ip route add 10.100.100.0/24 via 172.16.1.1 dev eth1 || true

# Set ip address eth2
ip addr add 10.1.1.10/24 dev eth2 || true
# Set static route for eth2
ip route add 10.10.10.0/24 via 10.1.1.1 dev eth2 || true
# Set DNS server
cat > /etc/resolv.conf << EOF
nameserver 8.8.8.8
EOF</pre>
```

13.1.5 Docker server-gui custom WEB page


Step 1: Add the node to the topology and make sure the DHCP option is **disabled** under the edit node window Reference section 13.2 for the correct console type.

Step 2: On the left sidebar menu open Startup-config and use the example syntax below to set the ip and html page for your Docker node. Make sure you are using the exact syntax for your static IP setup and custom HTML values:

```
# Set ip address and Default route
ip addr add 10.100.12.100/24 dev eth0 || true
ip route add default via 10.100.12.10 || true
# Set DNS server
cat > /etc/resolv.conf << EOF</pre>
nameserver 8.8.8.8
EOF
# Create a Default web page
# Use 'EOF' do avoid variable from expanding
# Delete default index page
rm /var/www/html/index.html || true
# Create a Default web page
# Use 'EOF' do avoid variable from expanding
cat > /var/www/html/index.php << 'EOF'</pre>
<center>
<?php
echo gethostname();
?>
<hr>
<img width="596" height="239" src="data:image/png;base64,---</pre>
imagecode ommittedg==">
<hr>
```

© EVE-NG LTD Page 206 of 272





Step 3: Press the Save button below and switch the node to boot from the startup-config.

© EVE-NG LTD Page 207 of 272






13.1.6 Docker server-gui SSL WEB page

Following previous chapter, you can enable on the server-gui node SSL/HTTPS certificate.

Step 1: Open Applications/System Tools/MATE Terminal



Step 2: Create SSL certificate, single line command, and fill up requested details.

openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout /etc/ssl/private/apache-selfsigned.key -out /etc/ssl/certs/apache-selfsigned.crt

Step 3: Enable SSL certificate for web page.

/usr/sbin/a2enmod ssl

© EVE-NG LTD Page 208 of 272



/usr/sbin/a2ensite default-ssl

Step 4: Restart apache2 service

sv stop apache2
sv start apache2

13.1.7 Docker server-gui SSH root access activation

Step 1. Use Mgmt_Server MATE Terminal, type:

vi /etc/ssh/sshd config

Step 2. Navigate and find PermitRootLogin and uncomment. (delete #). Locate cursor under # sign and press "x". Then press ESC and type: ":wq", Enter

#LoginGraceTime 2m
PermitRootLogin yes
#StrictModes yes
#MaxAuthTries 6
#MaxSessions 10


Step 3. Restart SSH service

/etc/init.d/ssh restart

13.2 Docker Consoles

To set consoles for EVE Docker stations, right click on node and click Edit. Set the required console type





© EVE-NG LTD Page 209 of 272



Docker Station	Console type
eve-gui-server (napalm, ansible)	RDP/Telnet
eve-chrome (optional)	RDP
eve-wireshark	RDP
eve-firefox	RDP
eve-ostinato (optional)	RDP

13.3 Docker cli root access

All EVE docker stations have the following configured CLI root account.

Username: root

Password: eve

NOTE: The root login for SSH can be commented in sshd file. Use vi to edit and remove comment "#" for PermitRootLogin

vi /etc/ssh/sshd_config
PermitRootLogin yes

Regular user (root user) SSH access to EVE Docker:

Username: nobody

Password: eve

13.4 Dockers re-install/update

To install or fix docker stations in the EVE Pro issue the following commands from the CLI of EVE.

When dockers are properly installed, your EVE CLI command do images output must show:



If you still see some docker line with <none>

© EVE-NG LTD Page 210 of 272



root@eve-ng:~# dc imag REPOSITORY	es TAG	IMAGE ID	CREATED	SIZE
<none></none>	<none></none>	cc286e6ac274	16 seconds ago	1.87GB
eve-qui-server	latest	f3aa6e0e9a56	3 minutes ago	3.04GB
eve-wireshark	latest	638ed7cf5b80	12 minutes ago	887MB
eve-firefox	latest	259293d73b07	13 minutes ago	1.49GB
eve-desktop	latest	78e9c2e618a5	15 minutes ago	2.79GB

please use reinstall dockers command:

```
apt install --reinstall eve-ng-dockers
```

Reference for Dockers reinstall and upgrade: http://www.eve-ng.net/documentation/eve-ng-upgrade

13.5 Extra docker packages

NOTE: Not included in the default EVE Pro installation. This can take some time depending on your Internet connection and disk speed.

Chromium Linux http, to install issue CLI command:

```
apt update
apt install eve-ng-chrome
```

Ostinato docker, to install issue CLI command:

```
apt update
apt install eve-ng-ostinato
```

Docker-in-docker (DinD) docker. This docker is dedicated for complex docker stacks. Refer section: 13.6.2. To install issue CLI command:

```
apt update apt install eve-ng-dind
```

To verify Installed dockers, issue CLI command

```
dc images
root@eve-ng:~# dc images
                                                           CREATED

3 days ago
REPOSITORY TAG
eve-dind latest
                                         IMAGE ID
                                                                                   SIZE
                                         6e067b53b145
                                                                                   747MB
eve-gui-server
                                         0c764bb836f9
413aae02d43d
                   latest
latest
                                                             2 months ago
                                                                                   3.69GB
eve-wireshark
                                                              4 months ago
                                                                                   1.62GB
                                        8882ac260c1f
63497fd2da4d
b041a187ded9
eve-firefox
                   latest
                                                             4 months ago
                                                                                   2.15GB
eve-ostinato
                    latest
                                                              4 months ago
                                                                                   1.79GB
eve-desktop
                    latest
                                                              4 months ago
                                                                                   3GB
                                         be03f3b46439
                                                                                   1.29GB
dockergui-rdp
                    latest
                                                              4 months ago
root@eve-ng:~#
```

13.6 Third parties dockers

Starting EVE-NG Pro version 2.0.6-52, the third party dockers can be installed on the EVE. However, some limitation still exists. You are free to evaluate by yourself if a specific one is working.

Two main categories of dockers require each a specific method for EVE integration:

Simple Docker

© EVE-NG LTD Page 211 of 272



❖ Docker's Stack

13.6.1 Simple docker installation

Simple docker is the classic docker running in a standalone mode. You could find large choice of docker images on https://hub.docker.com or create the Docker by yourself.

Complete guide about dockers can be found on https://docs.docker.com/

Note: Internet access is a must. For simple docker, you only have to use:

```
dc pull <dockername>
```


Note: "dc" is EVE-NG alias for docker -H tcp://127.0.0.1:4243 which simplify docker operations in the EVE.

Once your new docker is pulled, you are able to use it in EVE-NG topologies. EVE-NG will start it using correct parameters automatically.

Example: SSH to your EVE. Install adosztal AAA docker:



New docker use: Open a new lab, add docker and select adosztal/aaa with console in tenet mode.



© EVE-NG LTD Page 212 of 272



13.6.2 Docker stack installation

Docker's Stack is a complex structure of multi intercommunicating dockers. For example, a Web service docker is using another Database Docker service.

To avoid involve EVE host internal process and network, the new add-on docker is provided: "eve-dind". This add-on is a dedicated docker container allowing to build complex stack. The classic method is based on docker-compose.

The example below illustrates how to build complex docker LibreNMS, Network Management System.

Note: Internet access is a must. SSH to your EVE as root.

Sample

Step 1: On eve cli, type:

```
apt update
apt install eve-ng-dind
```

Note: install eve-ng-dind add-on docker and is required only once.

Step 2: Create a new lab

Step 3: Add on the lab:

- a. NAT network
- b. Docker eve-dind (set console to 'telnet' and enable dhcp)
- Step 4: Connect docker to NAT network
- Step 5: Start Docker
- Step 6: Open Docker Console
- Step 7: Type in console:

```
git clone https://github.com/librenms/docker.git librenms-src

cp -r librenms-src/examples/compose librenms

rm -fr librenms-src

cd librenms

docker-compose up -d
```

Commit your created docker with new name.

Step 8: Open a cli access to your EVE server

Step 9: Type within the EVE cli:

Find your current running container ID using eve-dind image

```
container identification in the container in the containe
```

© EVE-NG LTD Page 213 of 272




Step 10: IMPORTANT: On the Lab UI stop docker. Do not wipe, but stop.

Step 11: Commit your created docker with custom name.

dc commit <containerid> eve-librenms

Step 12: On LAB UI: Stop all nodes, Close Lab, Delete Lab

Note, when you add newly created docker in lab, use vendor advised settings, x4 CPU and 8GB Ram for librenms docker. Console: Telnet. Graphic Interface https.




13.7 Customize docker image with your own changes.

Step 1. Connect your existing docker node to the internet

Sometimes you may have your own packages to be installed on the docker and kept for future labs. For this connect your docker to the Internet. It can be achieved connecting docker to Management Cloud0 or NAT cloud. **Example below**, Sever-gui docker is connected to Cloud NAT.

© EVE-NG LTD Page 214 of 272





Step 2. Make your installs, packages. Example:

In the screen above I did install genisoimage package

```
apt install genisoimage
```

Step 3. Obtain your RUNNING docker container ID:

From EVE CLI issue command:

```
root@eve-ng:~# dc ps
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS
NAMES
0d4b3f8c314c eve-gui-server:latest "/sbin/my_init" 33 hours ago Up 2 minutes
b37bf9cb-0c6f-4bcb-b838-10d877ecce78-10-55 packages Example:
root@eve-ng:~# ^C
root@eve-ng:~# in the screen above I did install genisoimage package
```

Step 4. Commit your prepared docker image with new name. example below I called it evegeniso

dc container commit <containerid> <newimagename>

```
dc container commit 0d4b3f8c314c eve-geniso
```

Step 5 check if new Docker image is created

dc images

dc ps

© EVE-NG LTD Page 215 of 272



~ 1 1				
root@eve-ng:~# dc	ımages			
REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
eve-geniso-	latest	e6dd56c3b26c	4 seconds ago	3.19GB
eve-kali	latest	d1fda568e8a0	3 weeks ago	4.77GB
eve-nso	latest	f2a7a3d6a423	8 weeks ago	3.95GB
eve-ostinato	latest	e89cad6b1813	2 months ago	1.34GB
eve-gui-server	latest	a13cb401c8dd	3 months ago	3.11GB
eve-firefox	latest	8900664e9f3b	4 months ago	1.49GB
eve-chrome	latest	51fd92216b99	4 months ago	1.61GB
eve-wireshark	latest	0c49fe2dc6bb	7 months ago	888MB
eve-desktop	latest	c285d1ec833c	7 months ago	2.39GB
dockergui-rdp	latest	a65b62fa69b6	9 months ago	553MB
phusion/baseimage	0.9.22	877509368a8d	2 years ago	225MB
root@eve-ng:~#				

Step 6. Optional, If you want to keep this image and later load in other EVE installs, then you must create exportable .tar image.

```
dc image save -o /root/mysuperimage.tar <image name>
```

Step 7 Optional, upload your .tar file in new EVE root, and install it in Dockers location.

```
dc image load -i /root/mysuperimage.tar
```

13.8 Custom docker name tags

For different docker containers you may need to set different rights for your custom docker development. EVE-NG Supports 3 levels of dockers' privileges. To achieve it, rename your deployed docker image.

Standard Docker Name Tag:

```
dc tag <yourdockername>:latest <yourdockername>:latest
```

Privileged Docker Tag:

```
dc tag <yourdockername>:latest <yourdockername>:privileged
or
dc tag <yourdockername>:latest <yourdockername>-privileged:latest
```

DinD Docker Name Tag:

```
dc tag <yourdockername>:latest <yourdockername-dind:latest</pre>
```

Example to create gui-server docker in privileged mode:

```
dc tag eve-gui-server:latest eve-gui-server-privileged:latest
```

13.9 Delete docker image from EVE

Step 1. From EVE CLI issue command to check docker ID to be removed.

```
dc images
```

```
REPOSITORY
                                                  IMAGE ID
                                                                           CREATED
                         TAG
                         latest
eve-qeniso
                                                                                                       77GB
95GB
34GB
eve-kali
                                                                             weeks ago
                                                                             weeks ago
eve-ostinato
                         latest
eve-gui-server
                                                  a13cb401c8dd
8900664e9f3b
                                                                             months ago
                         latest
```

Step 2. Use command: dc rmi -f <id of docker image>.

© EVE-NG LTD Page 216 of 272



dc rmi -f e6dd56c3b26c

Step 3. Check with dc images if docker is removed.

Step 4. Finish removal with apt remove --purge eve-ng-chrome, where eve-ng-chrome is your docker repository name.

© EVE-NG LTD Page 217 of 272



14 EVE Cluster System

The EVE-NG cluster refers to a group of EVE-NG nodes working together as a single entity to provide users with better scalability and availability.

The EVE-NG cluster model is designed to work as a one + many systems, the EVE-NG management server is acting as "Master" node, EVE-NG installations as "Satellite" can be members of this cluster.

One "Master" EVE-NG can have several satellites joined into its cluster but each satellite can only be joined to one Cluster/Master.

Any existing EVE-NG Pro installation is already a EVE-NG "Master", cluster members will need to be installed as "satellite" and can then easily be joined.

14.1 EVE Cluster Licensing

EVE-NG Cluster system only the Master node is required to have a license. It is classic EVE Professional or LC/Corporate license.

Satellite nodes has special light EVE-NG Agent installation described below in Chapters: 14.5, 14.6 and 14.7. The Satellite nodes need not special EVE-NG License


One "Master" EVE-NG can have several satellites joined into its cluster but each satellite can only be joined to one Cluster/Master.

14.2 EVE Cluster design models

14.2.1 Bare metal servers cluster

Design 1 EVE-NG Cluster Bare HW servers, recommended

EVE Cluster 208 vCPU, 896GB RAM, 16TB SSD. Cluster members can be different HW configuration. The 1GB LAN connection or better is required




© EVE-NG LTD Page 218 of 272



14.2.2 ESXi Virtual Machines cluster

Design 2 EVE-NG Cluster VM Ware ESXi Virtual Machines


EVE Virtual ESXi Cluster 112 vCPU, 384GB RAM, 8TB SSD. Cluster members can be different VM configuration and located on same or different ESXi servers



14.2.3 Hybrid cluster

Design 3 Hybrid EVE-NG Cluster Bare metal and VM Ware ESXi Virtual Machines


EVE Hybrid Bare HW and ESXi Cluster 120 vCPU, 384GB RAM, 6TB SSD. Cluster members can be different VM configuration and located on same or different ESXi servers



14.2.4 VM Ware workstation light cluster

Design 4 Light EVE-NG Cluster Desktop PCs and Wifi Laptop with VM Ware workstation and Virtual Machines

Light EVE Cluster with Desktop PCs and Laptop Wifi.




14.2.5 Google Cloud cluster

NOTE: Your EVE Master must have Public IP address to join GCP satellite

© EVE-NG LTD Page 219 of 272





14.3 EVE Cluster pre-requisites

14.3.1 Firewall rules between Master and Satellite nodes

Node	Protocol	Port	Direction	Source	Destination
MASTER	TCP	22	ingress and egress	MASTER node IP	SATELLITE nodes IPs
MASTER	UDP	60569	ingress and egress	MASTER node IP	SATELLITE nodes IPs
SATELLITE	TCP	22	ingress and egress	SATELLITE node IP	MASTER Node IP
SATELLITE	UDP	60569	ingress and egress	SATELLITE node IP	MASTER Node IP

14.3.2 EVE Cluster interface MTU settings

IMPORTANT: The management interface MTU for all EVE-NG Cluster members MUST have the same value. The default ethernet MTU value is 1500.

14.3.3 EVE Cluster internal management network

An EVE Cluster for internal management is using network 172.29.130.0/24. Please avoid use it in your network.

© EVE-NG LTD Page 220 of 272



14.3.4 EVE Cluster Member's hardware requirements

Any suitable Hardware or virtual device. Please refer Chapter 2

14.3.5 NTP Synchronization requirements

It is mandatory that during install your cluster Satellite member have same time NTP synchronization as the Master server.

14.4 EVE Cluster MASTER Node Installation


- Mandatory Prerequisites: Internet must be reachable and DNS must resolve from your EVE Server. EVE ISO installation requires internet access and DNS to get updates and install the latest EVE-PRO version from the EVE-NG repository, to check it, do a named ping, for example ping www.google.com
- It is mandatory that during install your cluster Satellite member have same time NTP synchronization as the Master server.

Any existing EVE-NG Pro installation is already a EVE-NG "Master", cluster members will need to be installed as "Satellite" and then can be easily joined. Please refer Chapter 3


14.5 ESXi EVE Satellite VM installation

Download EVE-NG Professional Full ISO distribution image: https://www.eve-ng.net/index.php/download/

14.5.1 EVE-NG Satellite ESXi VM Setup and Settings




Step 1: Upload Full EVE ISO image to the




© EVE-NG LTD Page 221 of 272



Step 3: Enter the name for your EVE-PRO-SAT VM and select Guest Operating system Linux and version: Ubuntu 64-bit




Step 4: Select Location where your EVE VM will be stored in HDD.




Step 5: A IMPORTANT OPTION for ESXi 6.7.x or later.

Set Processors "Number of processors" and Set "Cores per Socket". If your server has dual CPU, then Cores per socket will be divided by 2. Example below, shows dual CPU Server VM setup with 48 CPU with 24 cores per socket (2).

Set Expose hardware assisted virtualization to the guest OS to ON (checked) and set Expose IOMMU to the guest OS to ON (checked)



Step 6: Assig desirable RAM for your EVE




Step 7: Set the size of HDD for your new EVE VM. It is recommended to set "Thick Provisioned eagerly provisioned". Server


Step 8: Set your Management network. Adapter type VMXNET3

© EVE-NG LTD Page 222 of 272





Step 9: Set DVD drive to "Datastore ISO File" and browse your uploaded Full-EVE-PRO.iso (ISO name can vary). Make sure that Status is checked ON, "Connect at power on"



Step 10: Set DVD drive to "Datastore ISO File" and browse your uploaded Full-EVE-PRO.iso (EVE ISO name can vary). Make sure that Status is checked ON, "Connect at power on" Hit the "Finish"




Step 11: IMPORTANT If you are using ESX 8.0 or later, select the Edit your VM and switch to "VM Options". Firmware *EFI Boot*.

Follow to "Boot Options" and de-select (uncheck) "Whether or not to enable UEFI secure boot for this VM"

Step 12: Start VM

© EVE-NG LTD Page 223 of 272






14.5.2 EVE-NG Satellite ESXi VM Installation steps

Satellite EVE ESXi VM Installation from ISO has 3 Phases

Phase 1 (Ubuntu installation)



Step 3: Make sure if English US keyboard is selected and confirm with Enter.

© EVE-NG LTD Page 224 of 272



```
| Replace | Flexible |
```

EVE VM Installation Phase 2 (EVE-NG installation)

```
Step 5: Please wait, the EVE-NG installation Phase 2 will start automatically.

Do NOT login in this stage!

Step 6. After installation EVE VM will auto reboot and EVE login screen will appear, login in CLI with root/eve and follow installation Phase 3

Ubuntu 22.04.4 LTS eve-ng tty1 eve-ng login:
```

EVE VM Installation Phase 3 (Management IP setup and updates)

```
Step 7: Setup EVEs Management IP address. A Static IP address setup is preferred.

Follow steps in section:

3.5.1 for static IP, 3.5.2 for DHCP IP

Step 8: Internet and DNS reachability is a MUST

After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

If required, follow steps in section: 5.1, 5.2
```

NOTE: To verify your EVE Satellite server installation type "dpkg -l eve-agent" it should display latest EVE Agent/Satellite version:

© EVE-NG LTD Page 225 of 272



ii eve-agent 6.0.1-XX amd64 Agent
for EVE-NG Sat Cluster member
root@eve-sat01:~#

IMPORTANT NOTE: If your Network interfaces order has been changed, please follow instruction to section 16.6

14.6 Bare hardware (BM) server EVE Satellite installation

14.6.1 BM Satellite server installation EVE PRO Full ISO


Download EVE PRO Full ISO distribution image: https://www.eve-ng.net/index.php/download/

Phase 1 (Ubuntu installation)

Step 1: Create a bootable DVD disk or USB flash drive (*Rufus tool is strongly recommended*) with a Full EVE ISO image. Boot your server from ISO. Chose Bare metal Option, following by following by Install BM EVE-NG Satellite and confirm with Enter.



Step 2: Select English language. Confirm with Enter.




Step 3: Make sure if English US keyboard is selected and confirm with Enter.

Step 12: Select "Continue" and confirm with Enter.

© EVE-NG LTD Page 226 of 272





EVE BM Installation Phase 2 (EVE-NG installation)

```
Step 5: Please wait, the EVE-NG installation Phase 2 will start automatically.

Do NOT login in this stage!

Second stage install in progress...

Step 6. After installation EVE VM will auto reboot and EVE login screen will appear, login in CLI with root/eve and follow installation Phase 3

Ubuntu 22.04.4 LTS eve-ng tty1

eve-ng login:
```

EVE BM Installation Phase 3 (Management IP setup and updates)

```
Step 7: Setup EVEs Management IP address. A Static IP address setup is preferred.

Follow steps in section:

3.5.1 for static IP, 3.5.2 for DHCP IP

Step 8: Internet and DNS reachability is a MUST

After your EVE is rebooted,

Login to EVE CLI and type:

apt update
apt upgrade

If required, follow steps in section: 5.1, 5.2
```

Verification: Verify your EVE-Satellite server installation, type "dpkg -I eve-agent" command, it must display latest EVE Satellite version

© EVE-NG LTD Page 227 of 272



root@eve-sat01:~#

14.6.2 BM Satellite installation Ubuntu legacy ISO

▲ IMORTANT: Internet must be reachable from your Server. This ISO installation requires internet access to get updates and install the latest EVE-PRO version from the EVE-NG repository. DNS must resolve names!

Download Ubuntu Legacy Server installation image/ISO https://releases.ubuntu.com/jammy/

Phase 1 (Ubuntu installation)

Follow the Phase 1 BM Ubuntu installation Chapter 3.3.2

EVE Installation Phase 2 (EVE Satellite installation)

Step 28: SSH to your EVE IP using Putty or other SSH client. Log in as root user execute:

apt update

apt upgrade

Step 29: Run EVE Pro online installation script. (it is single line command below)

wget -0 - https://www.eve-ng.net/jammy/install-eve-agent.sh | bash -i

At the end of eve server installation, reboot eve

EVE Satellite Installation Phase 3 (Management IP setup and updates)

Step 30: After reboot login into your Agent server as root and follow Management IP setup instructions described in section 3.5.1 for Static IP

Verification: Verify your EVE-Satellite server installation, type "dpkg -l eve-agent" command, it must display latest EVE Satellite version

IMPORTANT NOTE: If your Network interfaces order has been changed, please follow instruction to section 16.6

© EVE-NG LTD Page 228 of 272




14.7 Google Cloud EVE Satellite installation

14.7.1 Google account

Pre-Requisites: Your EVE Master server must have Public IP address or static NAT to public IP to join GCP satellite.


Step 1: Connect to Google Cloud Platform (GCP) https://console.cloud.google.com/getting-started



- Step 2: Sign into GCP. Create a new GCP account if you do not already have one.
- Step 3: Open your Google Project which assigned to your Google account

14.7.2 Preparing Ubuntu boot disk template

Step 1: On the left side navigate to Compute Engine and press "Activate Cloud Shell"



Step 2: Create a nested Ubuntu 22.04 image. Copy and paste the below command into the shell. Use copy/paste. crtl +c/ctrl +v. **It is single line command**. Confirm with "enter":

gcloud compute images create nested-ubuntu-jammy --source-image-family=ubuntu-2204-lts --source-image-project=ubuntu-os-cloud --licenses https://www.googleapis.com/compute/v1/projects/vm-options/global/licenses/enable-vmx

Welcome to Cloud Shell! Type "belp" to get started.

Your Cloud Platform project in this session is set to bashoo-storm-457508-10.

We 'geloud config set project [PROJECT | Delough | Del

You will get the following output when your image is ready:

Welcome to Cloud Shell! Type "help" to get started.

Your Cloud Platform project in this session is set to bashoo-storm-457508-10.

Use 'geloud config set project [PROMOTE] IN to change to a different project.

Use 'geloud config set project [PROMOTE] IN to change to a different project.

Camboo-storm-457508-103 good compute language create nested-ubuntu-jammy --mource-image-family-ubuntu-2204-lts --mource-image-project-ubuntu-os-cloud --license s https://www.googleapls.com/compute/v1/projects/morptions/global/licenses/enable-vmx

NAMS: nested-ubuntu-jammy |

N

© EVE-NG LTD Page 229 of 272



14.7.3 Network MTU 1500 settings and firewall rules for GCP

If your GCP VM is expected to be as a part of EVE-NG Cluster system please complete the MTU network settings and firewall rules setup before creating the instance.

NOTE: GCP VM by default has MTU 1460 set for the interfaces by default. You may require to set VM machine custom MTU (1500) which is commonly known default setting for ethernet. The MTU settings on the GCP interface must be adjusted if you want it to use as the part of EVE-NG cluster system.

Open the google cloud shell and press: Press "Activate Cloud Shell"

Copy the following commands in SHELL Cloud console:

```
##### Create 1500 MTU subnet #####
gcloud compute networks create mtu1500 --subnet-mode=auto --mtu=1500
--bgp-routing-mode=regional
##### Create 1500 MTU firewall rules #####
gcloud compute firewall-rules create wireguard-in --direction=INGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=udp:60569 --
source-ranges=0.0.0.0/0
gcloud compute firewall-rules create wirequard-out --direction=EGRESS
--priority=1000 --network=mtu1500 --action=ALLOW --rules=udp:60569 --
destination-ranges=0.0.0.0/0
gcloud compute firewall-rules create ssh-in --direction=INGRESS --
priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:22 --
source-ranges=0.0.0.0/0
gcloud compute firewall-rules create ssh-out --direction=EGRESS --
priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:22
destination-ranges=0.0.0.0/0
```

Firewall rules summary:

Name	Туре	Targets	Filters	Protocols/ports	Action	Priority	Network ↑	Logs
ssh-out	Egress	Apply to all	IP	tcp:22	Allow	1000	mtu1500	Off
wireguard- out	Egress	Apply to all	IP	udp:60569	Allow	1000	mtu1500	Off
ssh-in	Ingress	Apply to all	IP	tcp:22	Allow	1000	mtu1500	Off
wireguard- in	Ingress	Apply to all	IP	udp:60569	Allow	1000	mtu1500	Off

14.7.4 Optional: GCP MTU 1500 Firewall rules for native console use

Open the google cloud shell and press: Press "Activate Cloud Shell""

Copy the following commands in SHELL Cloud console:

Create MTU 1500 firewall rules for native console use

© EVE-NG LTD Page 230 of 272



gcloud compute firewall-rules create allow-all-in --direction=INGRESS --priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:0-65535 --source-ranges=0.0.0.0/0


gcloud compute firewall-rules create allow-all-out --direction=EGRESS --priority=1000 --network=mtu1500 --action=ALLOW --rules=tcp:0-65535 --destination-ranges=0.0.0.0/0

Summary FW rules.



14.7.5 Creating VM


Step 1: Navigate: Navigation Menu/Compute Engine/VM Instances and press "CREATE INSTANCE"



Step 2: Assign the name for your VM

Step 3: Set your own region and zone

Step 4: Edit your **Machine Configuration**. General-Purpose. Choose the series of CPU platform, Preferred are *Intel CPU Cascade Lake*. *Series N2 CPU*



© EVE-NG LTD Page 231 of 272




Step 5: Choose Machine Type your desirable CPU and RAM settings.

Machine type


Choose a machine type with preset amounts of vCPUs and memory that suit most workloads. Or, you can create a custom machine for your workload's particular needs. Learn more ☑



Step 6: Edit your OS and Storage configuration. Press Change




Step 7. IMPORTANT Select Custom images, select OS nested-ubuntu-jammy **you created previously**. Choose Boot Disk type: HDD disk type and size. HDD size can vary depends of your needs.




Step 8: Edit your Data Protection, select No backups.

© EVE-NG LTD Page 232 of 272






Step 10: Edit Security and Disable Secure Boot and vTPM



Step 10: (Optional), Skip this step if your EVE VM will not a part of EVE-NG Cluster. Before to select MTU1500 network please follow steps how to create it 3.4.7 Select Networking/Network Interfaces.

Edit network interface and select created network: MTU1500




Step 11: Create VM.

© EVE-NG LTD Page 233 of 272



14.7.6 EVE-NG Satellite installation

Step 1: Click VM Instances to get access SSH to your VM, Connect to the VM with the first option "Open in browser window"



Step 2: Launch installation with:

Type the below command to become root:

```
sudo -i
```

Start EVE-PRO installation

wget -0 - https://www.eve-ng.net/jammy/install-eve-agent.sh | bash -i

Step 3: Update and upgrade your new EVE-Pro

apt update

apt upgrade

Confirm with Y

Step 4. Reboot EVE. Allow some time for reboot and then press "Reconnect"

```
w version of config file /etc/console-setup/compose.ISO-8859-1.inc ...

w version of config file /etc/console-setup/compose.ISO-8859-13.inc ...


w version of con sev version of con sev
```

Step 5: IMPORTANT: Setup IP

Once the IP wizard screen appears, press ctrl + c and type the below command to become root: sudo -i

© EVE-NG LTD Page 234 of 272





Now follow the IP setup wizard. **IMPORTANT**: set IP as DHCP!

Step 6: Reboot

14.7.7 GCP Firewall rules for Cluster

If your EVE-NG Master server is behind the firewall, make sure it has allowed access to the GCP VM with following firewall rules

Node	Protocol	Port	Direction	Source	Destination
MASTER	ТСР	22	ingress and egress	MASTER node IP	SATELLITE node IPs
MASTER	UDP	60569	ingress and egress	MASTER node IP	SATELLITE node IPs

14.8 Cluster Management

14.8.1 Join Satellite nodes to the Master

Step 1: Make sure that you have reachability between Master and Satellite nodes and firewall rules are configured in your network if FW is set between them. Firewall rules Section 14.3.1

Step 2: Navigate: System/Cluster Management




© EVE-NG LTD Page 235 of 272





Step 3: Press Add Member and fill your Satellite details:

- Member's Name: use any suitable name for your satellite node
- IP address: Your satellite IP. In GCP version it will be public IP
- Member's Root Password: Your Satellite node password
- Press Add Member



Step 4: After certain of time Satellite will join to the Master



14.8.2 Remove Satellite nodes from the Master

Step 1: Navigate: System/Cluster Management

Step 2: Press Delete Member

© EVE-NG LTD Page 236 of 272






14.8.3 Re-join Satellite nodes from the Master

Step 1: Navigate: System/Cluster Management

Step 2: Press Delete Member



Step 3: IMPORTANT! Go to Satellite node CLI and reset IP address. It is necessary to refresh SSH key for re-join Satellite to the Master. CLI:

Login as root to the Satellite node and type:

```
rm -fr /etc/wireguard/*
rm -f /opt/unetlab/go/eve-agent.yaml
ip link set wg0 down
ip link del wg0
rm -f /root/.ssh/authorized_keys
```

Step 4: Join Satellite accordingly Section 14.8.1

14.8.4 Change Satellite IP address

Step1: Remove satellite from cluster system accordingly chapter 14.8.2

Step 2: Login as root to the Satellite node and type:

```
rm -f /opt/ovf/.configured
su -
```

EVE Satellite will initiate IP setup wizard. Follow Section 3.5.1

© EVE-NG LTD Page 237 of 272



14.9 Cluster assignment hierarchy

14.9.1 Single Satellite server assignment

The Cluster Hierarchy depends which of the option is assigned:

Option 1 - User assignment to cluster

Option 2 - Lab assignment

Option 3 - Individual node assignment

	Cluster		
	assignment Options	Description	Conditions
Option 1	EVE WEB GUI Management/User Management/Edit User/Satellite	Admin, Editor or User is forced to use only Cluster Satellite assigned by Admin. User cannot edit Lab or set individual nodes for other cluster Satellites. This Option can be assigned or edited only by Admin	If User account is set to use specific Satellite server, Users can NOT apply Options 2 and 3. This option applies to Admin user as well until Admin user will set his account to use "any"
Option 2	Lab is set to use Specific Cluster Satellite. Select Lab you want Edit/Select Satellite	If Option 1 is set to "any", then Admin or Editor is allowed to set Lab settings globally to use Lab on specific Cluster Satellite	Admin or Editor user accounts Satellite assignment (option 1) must be set to "any"
Option 3	Set lab nodes individually run-on specific Cluster server	Admin or Editor can assign single Lab nodes run on specific Cluster Satellite servers	Options 1 and 2 must be set to "any"

Lab User is not allowed to use any of options above

14.9.1.1 User assignment to the dedicated Satellite (Option 1)


Step 1: Navigate to Management/User Management



© EVE-NG LTD Page 238 of 272



Step 2: Create or Edit existing user



Step 3: Choose the Satellite or Satellites to be assigned for this user.




Step 4. User will be locked and will use only selected Satellite node. Editor and User roles cannot change or choose other satellite members. Use select Satellite from list which is dedicated for user.

14.9.1.2 Lab assignment to dedicated cluster Satellite (Option 2)

Step 1: Navigate to Lab tree, Select Lab you want assign for dedicated Satellite

Step 2: Click "Edit"




Step 3: Select Satellite for Lab

© EVE-NG LTD Page 239 of 272



Lab properties




Note: Accordingly, Cluster hierarchy matrix above, this Option will be in force if Option 1 is left to default "any"

14.9.1.3 Creating EVE labs in Cluster (Option 3)

- Step 1: Create new or edit your existing lab
- Step 2: On lab Node right click/edit







Option to assign cluster nodes for single lab devices.

Lab Side bar/Nodes, column SATELLITE, Select your cluster satellites for devices in the lab.



Note: Accordingly, Cluster hierarchy matrix above, this Option will be in force if Options 1 and 2 settings are left default "any"

© EVE-NG LTD Page 240 of 272




14.9.2 Multi Satellite servers' assignment

This option is dedicated for advanced EVE user assignment for multi-Satellite servers. User can choose and assign and run their labs to run on dedicated servers only.


14.9.2.1 Multi Satellites user Profiles

User Profile and Lab nodes Satellite use hierarchy



14.9.2.2 User assignment to the dedicated Satellites

Step 1: Navigate to Management/User Management




Step 2: Create or Edit existing user

© EVE-NG LTD Page 241 of 272





Step 3: The User Cluster Server value "any" is set by default. Choose the Satellite or Satellites to be assigned for this user.



Satellites assignment per user (Editor or User) require Administrator account

Set the Cluster Satellites for the Lab Editor. This applies for Lab Editor roles. Lab Editor will stick to selected Satellites. Lab Editor will be forced and allowed to use only selected Satellite server or choose between the Satellite servers if it is assigned more than one server. If the Lab has set to use any satellite server, then Lab Editor will be assigned to use lowest satellite ID.

Example: Lab Editor has assigned to use SAT1 (ID1) and SAT2 (ID2). The Lab has set to use "any" satellite. This Editor lab will be automatically assigned to use first available Satellite with lowest ID1, SAT1.

Editor has rights to change Satellite per node for own created Labs.

Editor cannot change satellite assignments for Shared Lab. The Shared Lab is recommended to set "any" Cluster Satellite,

If the Lab is created on the Satellite servers which are NOT in the Lab Editor allowed Satellites list, this lab will not start.

Example: Lab is created to use Master server only, but Lab Editor is allowed to use only SAT1 Server. Lab Editor will not be allowed to start this Lab.

If the Lab contains nodes which are assigned to run on the Satellite server which is NOT in Lab Editor allowed Satellites list, this node will not start.

Example: Lab several nodes are assigned to use Master server only, but Lab Editor is allowed to use only SAT1 Server. Lab Editor will not be allowed to start these nodes.

Set the Cluster Satellites for the Lab User. This applies for Lab User roles. Lab User will stick to selected Satellites. Lab User will be forced and allowed to use only selected Satellite server or servers.

© EVE-NG LTD Page 242 of 272



Example: Lab User has assigned to use SAT1 (ID1) and SAT2 (ID2). The Lab has set to use "any" satellite. This Lab User lab will be automatically assigned to use first available Satellite with lowest ID1, SAT1.

If the Lab is created on the Satellite servers which are NOT in the Lab User allowed Satellites list, this lab will not start.

Example: Lab is created to use Master server only, but Lab User is allowed to use only SAT1 Server. Lab User will not be allowed to start this Lab.

If the Lab contains nodes which are assigned to run on the Satellite server which is NOT in Lab User allowed Satellites list, this node will not start.

Example: Lab several nodes are assigned to use Master server only, but Lab User is allowed to use only SAT1 Server. Lab User will not be allowed to start these nodes.

Option to assign cluster nodes for single lab devices.

Lab Side bar/Nodes, column SATELLITE, Select your cluster satellites for devices in the lab.



14.9.3 Master images synchronization with Satellites

Once you have assigned certain lab device to use cluster Satellite node and start it, the automatic rsync process is initiated from Master node copy necessary image to the Satellite cluster member. During rsync process between Master and Satellite lab device will display "Clock" sign beside device. After image rsync process is completed, Lab device will turn sign to "Play", running state.



Large size lab devices/images, rsync process can take some time. It depends of the network speed between the cluster members.

Once the image is copied into Satellite node, lab device will start immediately. RSYNC process initiates only once if particular device image does not exist on Satellite node.

14.10 Cluster system monitoring

14.10.1 Cluster Monitoring page

Navigate: System/Cluster Management

Information columns displaying live information about cluster members utilization Satellite nodes have option to reboot or shutdown.

© EVE-NG LTD Page 243 of 272



If the cluster is healthy and fully functional, the Status column will display "GREEN" name label beside the cluster members.



If the Satellite node is down or not reachable, the Status column will display "RED" name label.



If the Satellite node is reachable but malfunctioning, Agent service is stopped or crashed, Status will be displayed as 'YELLOW' name label. (stop/reboot possible)




14.10.2 Satellite disaster recovery

Use case: If a satellite node crashed, was powered off while lab devices were running on it or the connection to the satellite was lost, the Master node will still have these nodes in a running state even if this is no longer the case.

To remediate this situation, you have to purge the local state information about the satellite before recovering the satellite, booting it back up or recovering the connection.

Step 1: To verify status of lab nodes:

Navigate Management/Nodes management. If you observing that crashed Satellite nodes are still alive and visible follow Step 2



© EVE-NG LTD Page 244 of 272



Step 2. Navigate: System/Cluster Management

Use Purge Button to clean crashed Satellite devices from the Master.





14.10.3 EVE Cluster Status

Navigate: System/Cluster Management



14.10.4 Cluster monitoring cli commands

On EVE Master:

Cluster System CLI Commands:

Check Cluster status:

SSH to the Satellite node from the Master status:

```
ssh 172.29.130.<satId>
```

```
#####Example SSH to SAT1#####
root@eve-ng:~# ssh 172.29.130.1
Welcome to Ubuntu 22.04.5 LTS (GNU/Linux 4.20.17-eve-ng-uksm-wg+x86 64)
```

* Documentation: https://help.ubuntu.com

* Management: https://landscape.canonical.com
* Support: https://ubuntu.com/advantage

 * Canonical Livepatch is available for installation.

© EVE-NG LTD Page 245 of 272



```
- Reduce system reboots and improve kernel security. Activate at:
   https://ubuntu.com/livepatch
Last login: Sun Jan 31 22:24:06 2021 from 10.6.6.14
root@eve-sat1:~#
Check Cluster Satellite version:
root@eve-sat03:~# dpkg -l eve-agent
Desired=Unknown/Install/Remove/Purge/Hold
      Status=Not/Inst/Conf-files/Unpacked/halF-conf/Half-inst/trig-
aWait/Trig-pend
|/ Err?=(none)/Reinst-required (Status, Err: uppercase=bad)
||/ Name
                             Version
                                             Architecture
Description
_____
ii eve-agent
                      6.0.1-XX
                                 amd64
                                                   Agent
for EVE-NG Sat Cluster member
root@eve-sat03:~#
```

14.11 Cluster system upgrade

Pre-requisites: The Master node must reach internet and resolve DNS.

On the EVE Master CLI run commands:

```
apt update apt upgrade
```

The cluster Satellites will upgrade automatically with EVE master. There no need any extra upgrade run for Satellite nodes.

To update manually Satellite nodes from Master EVE:

© EVE-NG LTD Page 246 of 272



15 EVE Troubleshooting

15.1 CLI diagnostic information display commands

15.1.1 Display full EVE Pro diagnostic

eve-info

15.1.2 Display the currently installed EVE Pro version:

dpkg -l eve-ng-pro

15.1.3 Display if EVEs Intel VT-x/EPT option on/off:

kvm-ok

```
root@eve-ng:~# kvm-ok
INFO: /dev.kvm exists
KVM acceleration can be used
root@eve-ng:~#
```

15.1.4 Display EVEs CPU INFO:

lscpu

15.1.5 Display EVEs CPU manufacturer:

lsmod | grep ^kvm_

```
root@eve-ng:~# lsmod | grep ^kvm_
kvm_intel 212992 74
root@eve-ng:~#
```

© EVE-NG LTD Page 247 of 272



15.1.6 Display EVEs HDD utilization.

If the eve—ng—vg—root reaches 98% or 100% then you will need to expand the HDD in order to continue using EVE. The Solution to expand your HDD is described in section 15.1

```
df -h
```

```
root@eve-ng:"# df -h
Filesystem Size Used Avail Use% Mounted on udev 406 0 406 0% /dev
tmpfs 7.96 52M 7.96 1% /run
/dev/mapper/eve--ng--vq-root 6816 3706 2836 57% /
tmpfs 406 0 408 0% /dev/shm
tmpfs 5.0M 0 5.0M 0% /run/lock
tmpfs 406 0 406 0% /sys/fs/cgroup
/dev/sda1 472M 83M 365M 19% /boot
```

15.1.7 Display EVEs Bridge interface status

```
brctl show
```

```
        root@eve-ng:"# brctl show
        STP enabled interfaces

        bridge name
        bridge id docker0
        STP enabled no no nat0
        s000.00242c0db8435 no no eth0

        nat0
        8000.000229d0aa94 no eth1
        eth0

        pnet1
        8000.000229d0aabc no eth1
        eth1

        vunl1_0_1_0
        vunl1_0_1_0

        pnet2
        8000.000c29d0aa9e no eth3
        eth3

        pnet3
        8000.000c29d0aab2 no eth3
        eth4

        pnet5
        8000.0000c29d0aab2 no eth4
        eth4

        pnet5
        8000.00000000000 no pnet6
        eth4

        pnet7
        8000.00000000000 no pnet7
        8000.00000000000 no pnet8
        eth4

        pnet8
        8000.0000000000000 no pnet9
        no pnet9
        8000.000000000000 no pnet9
```

15.1.8 Display EVEs system services status

```
systemctl list-unit-files --state=enabled
```

```
| Note |
```

15.2 Correct EVE server network interfaces order

NOTE: Sometimes after installation the Ubuntu or ESXi (known reported issue), your system can change network interfaces (NICs) order.

EVE-NG, starting from version PE 5.0.1-77 has implemented NIC order script to fix your network interfaces order.

© EVE-NG LTD Page 248 of 272



- Log into your EVE as SSH, or native VNC server console as root user.
- 2. Navigate to cd /opt/ovf/
- 3. Run the script:

```
root@eve-ng-master:~# cd /opt/ovf/
root@eve-ng-master:/opt/ovf# ./nicorder-wizard
```

4. Follow the instructions on the screen to re-order your interfaces.

```
Reorder Nics

***********

UP/DOWN Select interface
LEFT/RIGHT Move interface
ESC Discard change
ENTER Accept new order

> enx000c2967dbcb eth0 -> eth0
enx000c2967dbd5 eth1 -> eth1
enx000c2967dbdf eth2 -> eth2
enx000c2967dbe9 eth3 -> eth3
```

- 5. After correction the initial boot order will be saved on your EVE server
- 6. Reboot your EVE server, the new order settings will be in force now.

NOTE: if you will run order script again, it will show you last saved order.

15.3 Expand EVEs System HDD

▲ IMPORTANT NOTE: DO NOT expand your current/existing HDD on your EVE VM!

15.3.1 HDD space alert


Important: by default, EVE will trigger alerts if there are 3GB or less HDD space available. Additional nodes will not start until more space is added or freed up. A link is provided in the notification bubble on how to properly add an additional HDD.



To edit HDD space threshold for the alert is customizable. please follow section: 7.4.1

© EVE-NG LTD Page 249 of 272





15.3.2 Expand HDD on VMware Workstation

Expanding your EVEs system HDD is achieved by adding an additional HDD to your EVE VM.

Step 1: Stop all your labs and shutdown EVE.

Use EVE CLI command: shutdown -h now

Step 2: Go to edit VM settings and add a new Hard drive. Then click Next.

Step 3: Leave the recommended SCSI HDD option and then click Next

Step 4: Make sure you have selected the option "Create a new Virtual disk."




Step 6: Make sure you have set the option "Store Virtual disk as a single file" and then click Next

Step 7: Optional: Specify the location of where your new HDD will be stored, then click Finish.

Step 8: Boot your EVE VM, HDD size will be expanded automatically. To verify, use the command to verify HDD utilization referenced in section 15.1.6

15.3.3 Expand your HDD on ESXi

Expanding your EVEs system HDD is achieved by adding an additional HDD to your EVE VM.



Page 250 of 272



Step 1: Stop all your labs and shutdown EVE.

Use EVE CLI command: shutdown -h now

Step 2: Go to edit VM settings and add a new Hard drive. Then click Next

Step 3: Make sure you have selected the option "Create a new Virtual disk." Then click Next

Step 4: Set your desirable HDD Size; example 200GB.



Step 6: Specify the location of where your new HDD will be stored and then click Next

Step 7: Leave the recommended SCSI HDD option as is and click Finish.

Step 8: Boot your EVE VM, the HDD size will be expanded automatically. To verify, use the command to verify HDD utilization referenced in section 15.1.6

15.3.4 Expand your HDD on a Bare Metal EVE Server

It is a complicated process to expand a HDD for a bare metal EVE server.

https://www.eve-ng.net/wp-content/uploads/2023/03/EVE-Doc-3023-LVM-HDD-systems.pdf Please open a ticket in our Live chat support for advice.

https://webchat.eve-ng.net/login/

Use a google account to join in the Live Chat or create new chat account.

15.4 Reset Management IP

Type the following commands into the CLI followed by enter:

rm -f /opt/ovf/.configured


su -

http://www.eve-ng.net/documentation/installation/bare-installIP address setup wizard. Please follow the steps in section 3.5.1 for Static IP or 3.5.2 for DHCP IP setup.

15.5 EVE PRO SQL Database recovery

Starting EVE PRO version 3.0.1-21 and later, you can recover SQL user database in case of disaster:

unl wrapper -a restoredb



Page 251 of 272



Below is SINGLE LINE Command to restore SQL Database.

unl_wrapper -a restoredb ; grep -q default_time_zone
/etc/mysql/mysql.conf.d/mysqld.cnf || echo
"default_time_zone='+00:00'" >> /etc/mysql/mysql.conf.d/mysqld.cnf ;
systemctl restart mysql

15.6 EVE PRO Migration from host to host

Step 1: On newly installed EVE navigate to:

```
cd /opt/unetlab/scripts
```

Step 2: Run migration script migrate.sh where source IP is your old EVE host IP and root password of old EVE. [./migrate.sh -s <old eve ip> -p <root password>]

Example:


```
root@eve-ng:/opt/unetlab/scripts# ./migrate.sh -s 192.168.1.100 -p eve
```

Step 3: After migration is completed, deactivate EVE license on old host, and load license in the new EVE machine.


https://www.eve-ng.net/index.php/documentation/howtos/recover-rehosting-eve-ng/

15.7 EVE Log files

EVE log Files can be obtained from the System Logs page under the System dropdown menu



Use the menu to collect log file data you are interested in.



15.8 EVE cli diagnostic info

Use EVE cli to obtain your EVE information:

eve-info

© EVE-NG LTD Page 252 of 272



16 EVE Extras

16.1 EVE Pro Radius server setup for user authentication

Mandatory Prerequisites: Updated EVE-PRO version 2.0.6-30 or later.

Please follow section: 7.4.1




16.1.1 EVE User setup for Radius authentication


Step 1: Open the User management submenu. Management>User management and click Add user

Step 2: The Add New User management window will pop up. Fill in the main information about your EVE user. Make sure that you're the username of the account created in EVE matches with the Radius server database.

Step 3: Select Authentication "radius". Any existing password will be removed, because the authenticator will check with the Radius server for credentials.



Step 4: If you have purchased licenses for different EVE user roles, you can choose the preferred user role. For licensing and user roles please refer to section 4



© EVE-NG LTD Page 253 of 272



Step 5: Set the access date and time From - to. If the fields are left empty (untouched), your user will have no time restrictions for accessing the EVE Server. Account validity with time settings is available for Editor and User roles only.

Admin accounts have no time limit for account validity, and Account Validity time cannot be set. To remove Account validity, delete Date From and To, and put value "-1"



To remove Account validity, delete Date From and To, and put value "-1"




Step 6: The POD number is a value assigned to user accounts automatically. POD numbers are like user profiles inside of EVE and are a unique value for every user Think of PODs like a virtual rack of equipment for each user. Admins can assign a preferred number between 1-32786. Please keep POD numbers unique between users!

Step 7: Press ADD



Step 8. The username created inside EVE must match the username on the Radius server

Example: EVE user authenticated with ISE 2.1 Radius server.



16.2 Active Directory user authentication

Mandatory Prerequisites: Updated EVE-PRO version 2.0.6-30 or later.

To join Active Directory to the EVE, please follow section: 7.4.1

© EVE-NG LTD Page 254 of 272





16.2.1 EVE User setup for AD (LDAP) authentication

Step 1: Open the User management submenu. Management>User management and click Add user


Step 2: The Add New User management window will pop up. Fill in the main information about your EVE user. Make sure that you're the username of the account created in EVE matches with the Radius server database.

Note: The username in of the Active directory user account must match with AD username. Username must have domain at the end of username. Example: evelabuser@eve.lab

Step 3: Select the Active Directory from Authentication menu. Any existing password will be removed, because the authenticator will check with the Active Directory server for credentials.



Step 4: If you have purchased licenses for different EVE user roles, you can choose the preferred user role. For licensing and user roles please refer to section 4



© EVE-NG LTD Page 255 of 272



Step 5: Set the access date and time From - to. If the fields are left empty (untouched), your user will have no time restrictions for accessing the EVE Server. Account validity with time settings is available for Editor and User roles only.

Admin accounts have no time limit for account validity, and Account Validity time cannot be set.



To remove Account validity, delete Date: From and To, and put value "-1"




Step 6: The POD number is a value assigned to user accounts automatically. POD numbers are like user profiles inside of EVE and are a unique value for every user Think of PODs like a virtual rack of equipment for each user. Admins can assign a preferred number between 1-32786. Please keep POD numbers unique between users!

Step 7: Press Save

Step 8. The username created inside EVE must match the username on the Radius server

16.3 Lab Chat




16.4 Custom MAC address for node management


NOTE: Custom first MAC is supported for Qemu nodes only.

Qemu nodes has option to change first interface MAC address.

Page 256 of 272 © EVE-NG LTD







16.5 Windows node settings for Wifi dongle

Using a Wifi USB dongle, you can connect a WiFi-adapter to windows host inside EVE.

Step 1. Connect your USB Wifi dongle to your EVE server.

Step 2. Issue the following command on the EVE CLI to obtain BUS and host numbers which your USB WiFi is connected to:

```
root@eve-ng:~# lsusb

Bus 002 Device 002: ID 0cf3:9271 Atheros Communications, Inc. AR9271 802.1ln

Bus 002 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub

Bus 006 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub

Bus 005 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub

Bus 001 Device 003: ID 0424:2514 Standard Microsystems Corp. USB 2.0 Hub

Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub

Bus 004 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub

Bus 003 Device 002: ID 04e6:5116 SCM Microsystems, Inc. SCR331-LC1 / SCR3310 Sma

rtCard Reader

Bus 003 Device 001: ID 1d6b:0001 Linux Foundation 1.1 root hub

root@eve-ng:~#
```

Step 3. Add the windows node onto the topology and edit the Qemu line:

Change the type value:

type=q35

lsusb

Add a comma and then the following line:

© EVE-NG LTD Page 257 of 272




if=virtio -usb -device usb-host,hostbus=2,hostaddr=2

Where hostbus is your Bus value and hostaddr is your Device ID as seen in the figure above.

Full Windows host qemu line will look like this:

-machine type=q35,accel=kvm -cpu
host,+pcid,+kvm_pv_unhalt,+kvm_pv_eoi,hv_spinlocks=0x1fff,hv_vapic,hv
_time,hv_reset,hv_vpindex,hv_runtime,hv_relaxed,hv_synic,hv_stimer vga std -usbdevice tablet -boot order=cd -drive
file=/opt/qemu/share/qemu/virtio-windrivers.img,index=1,if=floppy,readonly,if=virtio -usb -device usb-host,hostbus=2,hostaddr=2



© EVE-NG LTD Page 258 of 272



16.6 Master Server NIC ports order change

Some of the servers has Network interface cards with multi and various ethernet type ports. Example: Some DELL R series servers has first 2 Fibre ports (SFP) and additional 4 Ethernet ports. Requirement is to set EVE management on the 3rd port.

Supported starting from version 5.0.1-93.

Workaround:

- SSH or use serial console to your EVE CLI as root user.
- Navigate CLI to:

```
cd /opt/ovf/
```

· Run NIC order setup wizard

```
./nicorder-wizard
```

Follow the instructions on the screen to set primary NIC for your EVE

```
Reorder Nics

***********

UP/DOWN Select interface
LEFT/RIGHT Move interfacer V5 Fixes
ESC Discard change
ENTER Accept new order

Name

> enx000c29617481 eth0 -> eth0
enx000c2961748b eth1 -> eth1
```

16.7 Satellite Server NIC ports order change

Some of the servers has Network interface cards with multi and various ethernet type ports. Example: Some DELL R series servers has first 2 Fibre ports (SFP) and additional 4 Ethernet ports. Requirement is to set EVE management on the 3rd port.

Workaround:

- SSH or use serial console to your EVE CLI as root user.
- Execute link set up command for all interfaces

```
ls -1 /sys/class/net/ | while read i ; do ip link set $i up ; done
```

Detect which interface is up state

ls -1 /sys/class/net/ | while read i ; do echo \$i \$(ethtool \$i | grep Link) ; done

```
root@eve-sat01:~# ls -1 /sys/class/net/ | while read i ; do ip link set $i up ; done root@eve-sat01:~# ls -1 /sys/class/net/ | while read i ; do echo $i $(ethtool $i | grep Link) ; done docker0 Link detected: no ens160 Link detected: yes a son or use serial console to your EVE CLI as root user ens192 Link detected: no ens224 Link detected: yes to Link set up command for all interfaces
```

© EVE-NG LTD Page 259 of 272



Edit netplan yaml file with correct interface name:

nano /etc/netplan/01-netcfg.yaml

```
GNU nano 4.8

# This file describes the network interfaces available on your system

# For more information, see netplan(5).

network:

version: 2

renderer: networkd

ethernets:

ens160:

addresses: [ "192.168.98.101/24" ]

gateway4: 192.168.98.1

nameservers:

addresses: [ "8.8.8.8", "1.1.1.1" ]

* Execute link set up command for all interfaces
```

- ❖ To save netplan settings use: CTRL +o [letter o]; Enter; CTRL +x [for exit]
- * Run test the new network settings, enter

netplan try

```
root@eve-sat01:~# netplan try
Do you want to keep these settings?

Press ENTER before the timeout to accept the new configuration

Changes will revert in 112 seconds

Configuration accepted.
```

Apply new network settings and reboot

netplan apply reboot

© EVE-NG LTD Page 260 of 272



17 Images for EVE

Images must be uploaded and prepared before they can be used in labs. The best way to upload images is to use the WinSCP tool for Windows environment or FileZilla for MAC OSX and Linux.

Link to download WinSCP:

https://winscp.net/eng/download.php

Link to download FileZilla:

https://filezilla-project.org/

To access EVE, use SSH protocol (port 22).

Supported images for EVE are stored in the three locations:

- IOL (IOS on Linux), /opt/unetlab/addons/iol/bin/
- Dynamips images, /opt/unetlab/addons/dynamips
- Qemu images, /opt/unetlab/addons/gemu

17.1 Qemu image naming table

▲ IMPORTANT NOTE: Intel VT-X/EPT must be enabled to run Qemu nodes in EVE. For information on how to enable this option, Refer to section 3: EVE Installation.

The directory names used for QEMU images are very sensitive and must match the table below exactly in order to work.

Ensure your image folder name starts as per the table. After the "-" you can add whatever you like to label the image. We recommend using the version of your image.

Folder name examples:

firepower6-FTD-6.2.1 acs-5.8.1.4

The image hdd inside the folder must be named correctly:

Example: hda.qcow2 or virtioa.qcow2

Full path Example: opt/unetlab/addons/qemu/acs-5.8.1.4/hda.qcow2

The table of proper folder names is provided in our website:

https://www.eve-ng.net/index.php/documentation/gemu-image-namings/

Supported HDD formats and Qemu versions for the EVE images:

HDD Format	HDD name example
lsi([a-z]+).qcow	lsia.qcow
hd([a-z]+).qcow	hda.qcow
virtide([a-z]+).qcow	virtidea.qcow

© EVE-NG LTD Page 261 of 272



virtio([a-z]+).qcow	virtioa.qcow
scsi([a-z]+).qcow	scsia.qcow
sata([a-z]+).qcow	sataa.qcow

Supported Qemu Versions
1.3.1
2.0.2
2.2.0
2.4.0
2.5.0
2.6.2
2.12.0
3.1.0
4.1.0
5.2.0
6.0.0
7.2.9
8.2.1
9.2.2

17.2 How to prepare images for EVE

How to add EVE-NG images please refer to:

https://www.eve-ng.net/index.php/documentation/howtos/

17.3 How to add custom image template

17.3.1 Templates folder choice

⚠ IMPORTANT NOTE: Starting from EVE-PRO Version 2.0.6-42, EVE installation is autodetecting what kind of CPU manufacturer has your server: Intel or AMD, to choose proper templates set. You can check it manually on EVE cli: example below, showing that EVE has Intel CPU.

- If you have Intel CPU, then your template files are in "/opt/unetlab/html/templates/intel/"
- If you have AMD CPU, then your template files are in "/opt/unetlab/html/templates/amd/"

17.3.2 Prepare template file

NOTE: For templates development use templates folder which is matching your EVE server CPU.


© EVE-NG LTD Page 262 of 272



Example below will be based for Intel CPU EVE custom image template. Use EVE cli or WinSCP/Filezilla to create template.

Step 1: Navigate to EVE location: /opt/unetlab/html/templates/intel/

Step 2: Choose your most suitable template from which you want to make copy and create own image template. (example: newimage.yml)



Step 3: Make a copy from source template newimage.yml. Example: Using CLI create template and name it ngips.yml.

You can create new template using WinSCP or Filezilla as well.

```
root@eve-ng:"# cp /opt/unetlab/html/templates/intel/newimage.yml /opt/unex/yml /op
```

IMPORTANT: The new name of your template will be related to your image foldername. Your image foldername must start with prefix "ngips-"

Example: image foldername under /opt/unetlab/addons/gemu/ngips-6.5.0-115

17.3.3 Prepare interface format and name lines

EVE Pro has included option to create various interface names, sequences and numbering. Please refer table below.

Formula	Template example	line	format	Will produce
---------	------------------	------	--------	-----------------

© EVE-NG LTD Page 263 of 272



eth_format: <pre><pre><pre> eth_format: <pre><pre></pre></pre></pre></pre></pre>	eth_format: Gi{1}/{0-8}	Gi1/0 Gi1/1 Gi1/2 Gi1/3 Gi1/4 Gi1/5 Gi1/6 Gi1/7 Gi2/0 Gi2/1
eth_format: <pre>cth_format: <pre>cth_fo</pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre>	eth_format: Ge{0}/{0-4}	Ge0/0 Ge0/1 Ge0/2 Ge0/3 Ge1/0 Ge1/2 Ge1/3 Ge2/0 Ge2/1 Ge2/2
eth_format: <pre style="color: blue;">eth_format: <pre><pre><pre><pre></pre></pre></pre></pre></pre>	eth_format: Gi{0}	Gi0 Gi1 Gi2 Gi3
eth_format: <pre><pre><pre>eth_format: <pre><pre><pre><pre><pre><pre><pre><pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre></pre>	eth_format: G0/{0}	G0/0 G0/1 G0/2 G0/3
eth_name: <pre><pre><pre>cth_name</pre></pre></pre>	eth_name: - M1 - T1 - T2	M1 T1 T2
eth_name: <pre><pre><pre>cth_name</pre></pre></pre>	eth_name: - MGMT - DATA - TRAFFIC	MGMT DATA TRAFFIC

Combined first named interface following by formatted interfaces Example: We have to set first node interface name "eth0/mgmt" and next following interfaces must start from eth1 and change sequence accordingly. eth1, eth2,....,ethx


As your node first interface will be custom named (eth0/mgmt), therefore in the template "eth_name:" must be added before "eth_format:"

eth_name:
 eth0/mgmt
eth format: eth{1}

© EVE-NG LTD Page 264 of 272



This adding will produce Node interfaces.



17.3.4 Edit your new template file:

For edit newly created template you can use WinSCP, FileZilla or cli. Example below shows template edit using cli and *nano* editor

```
cd /opt/unetlab/html/templates/intel/
nano ngips.yml
```

Change content, setting for various images can vary depends of vendor requirements. The interface name lines please refer Section: 17.3.3

```
# Copyright (c) 2016, Andrea Dainese
 Copyright (c) 2018, Alain Degreffe
 All rights reserved.
# Redistribution and use in source and binary forms, with or without
  modification, are permitted provided that the following conditions are met:
      * Redistributions of source code must retain the above copyright
       notice, this list of conditions and the following disclaimer.
      * Redistributions in binary form must reproduce the above copyright
       notice, this list of conditions and the following disclaimer in the
        documentation and/or other materials provided with the distribution.
      * Neither the name of the UNetLab Ltd nor the name of EVE-NG Ltd nor the
        names of its contributors may be used to endorse or promote products
        derived from this software without specific prior written permission.
 THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
# ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
# WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
# DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
# DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
 (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
# ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
  (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
# SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
→ Node list name
description: Cisco FirePower NGIPS
cpulimit: 1
                                                ADD A NEW NODE
icon: IPS.png
cpu: 4
ram: 8192
ethernet: 3
```

© EVE-NG LTD Page 265 of 272



```
eth_name:
    eth0/mgmt
eth_format: eth{1}
console: vnc
shutdown: 1
qemu_arch: x86_64
qemu_version: 2.4.0
qemu_nic: e1000
qemu_nic: e1000
qemu_options: -machine type=pc,accel=kvm -serial none -nographic -no-user-config
    -nodefaults -display none -vga std -rtc base=utc -cpu host
...
```

Note: Qemu options in the line may vary per image requirements. Please check manufacturer advice how to run KVM image

17.3.5 Prepare new icon for your template:

Step 1 Use Filezilla or Winscp to copy your custom icon IPS.png (icon filename IPS.png used in ngips.yml)

This icon should be about $30-60 \times 30-60$ in the png format (switch.png is for example 65×33 , 8-bit/color RGBA)

Step 2 Copy this new icon into /opt/unetlab/html/images/icons/

17.3.6 Template use

Step 1 Create directory /opt/unetlab/addons/qemu/ngips-6.5.0-115

```
mkdir /opt/unetlab/addons/qemu/ngips-6.5.0-115
```

Step 2 Upload image NGIPS, Refer Section: 17.2

17.4 How to hide unused images in the node list

Please follow section 7.4.1 or 7.9.1.1

© EVE-NG LTD Page 266 of 272



18 EVE Backup Solution

EVE NG Software provides full and partial content backup Starting from:

EVE Professional 5.0.1-131 with Cluster

EVE Community 5.0.1-20

EVE Backup Solution supported transfer protocols: SFTP port 22 or FTP port 23.

EVE Backup solution requires to have an external SFTP/FTP server where the EVE-NG content will be stored. The SFTP/FTP server HDD size must be chosen appropriately.

18.1 Backup manager

18.1.1 Backup Manager Installation

Mandatory Prerequisites: The Internet must be reachable from your server. DNS names must be resolved. This Backup solution installation requires internet access to get updates and install the latest EVE-Professional or Community version from the EVE-NG repository.

SSH to your EVE as root user and execute following commands.

```
root@eve-ng:~# apt update
root@eve-ng:~# apt install eve-backup-manager
root@eve-ng:~# reboot
```

18.1.2 Setup external SFTP or FTP server

SFTP server setup is EVE user's responsibility and not covered under EVE-NG support.

In order to use the backup tool, you are required to set up an external SFTP/FTP server. This part is not supported by EVE-NG support, because every user can install and establish a server in its own way. The main pre-requisite is: The SFTP server must be reachable two ways from the EVE server and back from the SFTP server to EVE.

Examples of external SFTP server setup:

https://www.eve-ng.net/wp-content/uploads/2024/03/EVE-Doc-2024-External-SFTP-Server.pdf

18.1.3 Backup Manager SFTP/FTP settings

⚠ IMPORTANT NOTE: It's a must to stop all running labs (nodes) before starting a backup process. If you have satellites, then make sure they are and connected to the Master. Satellites backup will be done automatically.

SSH to your EVE as root user and execute following command.

root@eve-ng:~# backup-manager

© EVE-NG LTD Page 267 of 272



```
| (e) Edit Backup Server required to setup external SFTP/FTP server. This part is out of EVE-
| No support because every user can install and establish its own way. The main pre-requisite
| (c) Create Backup | (g) Restore Backup |
| (g) Restore Backup |
| (g) Quits of external SFTP server setup:
| Link to document |
| SFTP server setup is EVE user responsibility and not covered under EVE-NG support.
```

Select option (e) Edit Backup Server

ŗServer	Configuration		
i i			
Ï.			
W(c			
Virtual Enviro		Server Protocol	SFTP Version 5.13
		Server Label	store
Server		Server Address	192.168.70.32
		Remote Directory	/sftpuser/
ï			
į		Username	sftpuser
		Password	***
		Submit Quit	t

Server Protocol: Select your designated backup server protocol FTP or SFTP

Server Label: Name your Server Label, free to name it.

Server Address: Put your backup server IP,

Remote directory: For Linux servers, specify the target directory. The example above is /sftpuser/. This is the directory where the backup uploads will be stored. On the Windows SFTP server, this part can be left clear. All uploads will be stored in the sftp user-designated directory.

Username: Put your SFTP server username **Password**: Put your SFTP user password

Submit

18.2 Create an EVE-NG Backup

SSH to your EVE as root user and execute following command.

```
root@eve-ng:~# backup-manager
```

Select option (c) Create Backup.

```
(e) Edit Backup Server Select option (e) Edit Backup Server

(c) Create Backup

(r) Restore Backup

(q) Quit
```

18.2.1 Backup option All

Every time when you run All backup process, EVE backup manager will create new backup folder [hostname]-[date]-[backup ID] with selected backup content.

Select your backup items:

© EVE-NG LTD Page 268 of 272



```
Choose item(s) to Backup

Choose item(s) to Backup

All

Labs backup

Database backup

Images backup

Server Protocol: Select your designated backup server protocol FTP or SFTP

Templates/Icons/Config-scriptabackup Xame your Server Label, free to name it.

Server Address: Put your backup server IP.

Remote directory: For Linux server specify target directory, example above is /sftpuser/. This is directory who is the backup uploads will be stored. In the Windows SFTP server this part can be left clear. The all uploads will be stored in the sftp user designated directory.

Username Put your SFTP user massword.
```

Select All: the backup manager will create directory with all contents of EVE which includes:

- Labs,
- Users Database,
- All images (Dynamips, IOL, Qemu),
- Templates of all images including Custom templates, config scripts and icons,
- TMP Folder (TMP folder contains all of your labs saved configurations and qemu nodes)

18.2.2 Backup option custom selected

Every time when you run a custom selected backup process, EVE backup manager will create new backup folder [hostname]-[date]-[backup ID] with selected backup content.

Select Custom items: For example, if you want to back up only labs, images and full labs with a tmp directory, your selection should look like the screenshot below.

```
Choose item(s) to Backup

All

Select All: the backup manager will create directory with all content of the EVE which include:

Labs backup

Database backup

Images backup

Templates/Icons/Config-script backup

Tmp Folders backup

X

Mirroring

Create

Cancel
```

This backup folder will only contain Lab files (topologies), all images (vendor images) from the EVE in the current stage and the TMP folder (saved labs with all configurations) for all EVE users.

18.2.3 Backup option with Mirroring selected

First time when you run Mirror backup process, EVE backup manager will create new backup folder "[hostname]-eve-ng-mirror" with selected backup content.

Select Mirroring: The mirroring option creates a single Folder named "[hostname]-eve-ng-mirror".

© EVE-NG LTD Page 269 of 272



Using this option will only back up content of the new data added after the first backup. EVE Backup will compare data that already persists in the backup folder and will update only new items which have been changed after the backup is saved in the "[hostname]-eve-ng-mirror". It is recommended to select all items with a mirror option.

```
Choose item(s) to Backup

Templates for all your images also Custom templates, config scripts and icons,
TMP Folder (TMP folder holding all your labs saved configurations with gemu nodes)

Select Custom items: For example, if you want send to backup only labs, images and full lab saved work (tmp directory), your items selection will look like below.

Labs backup

Database backup

Images backup

Templates/Icons/Config-script backup X

Tmp Folders backup

Mirroring

Create

Cancel

Templates item(s) to Backup

Templates (TMP folder holding all your labs saved configurations with gemu nodes)

**Total Constant Configurations with gemu nodes)

**Total Configurations with gemu nodes with genus n
```

18.3 Restore data from EVE-NG Backup

SSH to your EVE as root user and execute following command.

```
root@eve-ng:~# backup-manager
```

Select option (r) Restore Backup.

```
(c) Create Backup

(r) Restore Backup

(g) Quit
```

18.3.1 Select restore backup folder

IMPORTANT: Select a desired backup folder, following by Restore.

```
Restore Backup.

Select Item to restore

Select option (r) Restore Backup.

/tmp/eve-bkp-storage
|---cache | ---eve-bck-master-20240218-203005 | ---eve-bck-master-20240218-203005 | ---eve-bck-master-mirror | --
```

© EVE-NG LTD Page 270 of 272




18.3.2 Select the items to restore

All: (Mirroring disabled) This option is useful to restore all data from backup to the new EVE installation. Backup manager will compare your existing data on your EVE with backup content and will restore only missing data.

Custom selected items: (Mirroring disabled) This option will restore custom selected items' data from backup to the new EVE installation. Backup manager will compare your existing data on your EVE with backup content and will restore only missing data.

Important: Restoring cluster satellite server TMP folder content for the new EVE install. Make sure that the Satellite ID matches your tmp-satellite folder number (ID)



Careful! Mirroring enabled! This option will restore selected data from backup to the EVE installation. Backup manager will replace all data on your EVE with backup content and will destroy data which does not exist in backup.



© EVE-NG LTD Page 271 of 272



19 EVE Resources

For additional updated information please follow our web site: https://www.eve-ng.net

How to updates: https://www.eve-ng.net/index.php/documentation/howtos/

How to videos: https://www.eve-ng.net/index.php/documentation/howtos-video/

https://www.eve-ng.net/index.php/documentation/knox-hutchinson-videos/

How to create images: https://www.eve-ng.net/index.php/documentation/howtos/

FAQ: https://www.eve-ng.net/index.php/faq/

Live support chat: https://webchat.eve-ng.net/login/ For access to live chat use your Google account or create new chat account.

EVE forum: https://www.eve-ng.net/forum/ To access forum resources, please create a new forum account.

EVE YouTube channel:

https://www.youtube.com/playlist?list=PLF8yvsYkPZQ0myW7aVMZ80k8FU04UUgiV

EVE Professional downloads: https://www.eve-ng.net/index.php/download/

EVE Community version downloads, free: https://www.eve-ng.net/index.php/community/

EVE Supported images: https://www.eve-ng.net/index.php/documentation/supported-images/

© EVE-NG LTD Page 272 of 272